MILITARY SPECIFICATION

PROJECTILE, 155MM, M718/M741
METALLIC HARDWARE FOR

This specification is approved for use by U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the fabrication and packing of metallic hardware for use with Projectile 155MM, M718/M741.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169	Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

FSC 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DRAWINGS

U. S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKAGING DRAWINGS

9277747 - Plate, Pusher
9278017 - Shim

(Copies of specifications, standards, drawings, and publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the test of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on the drawings and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. The parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurous to any part, nor shall the part be contaminated by the cleaning agents. All markings and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item.

a. First article inspection

b. Quality conformance inspection

4.3 First Article Inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in the quantities as indicated:

Part Description	Drawings	Quantity
Plate, Pusher	9277747	15
Shim	9278017-1	15
Shim	9278017-2	15

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63985(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Projectile Metal Parts				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Pusher (Dwg. 9277747) Examination for Defects	15	-	3.2	4.4.2.1
	Shim (Dwg. 9278017 - 1) Examination for Defects	15	-	3.2	4.4.2.2
	Shim (Dwg. 9278017 - 2) Examination for Defects	15	-	3.2	4.4.2.2

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIl-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63985(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Plate, pusher				9277747
					NEXT HIGHER ASSEMBLY 9277852
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	Small outside diameter		0.40%	3.2	Gage
103	Thickness of flange		0.40%	3.2	Gage
104	Height from flange to shoulder		0.40%	3.2	Gage
105	Height from flange to top		0.40%	3.2	Gage
106	Spherical radius to top		0.40%	3.2	Gage/Comparator
Minor					
201	Radius of curvature of flange		0.65%	3.2	Gage/Comparator
202	Diameter of cutout		0.65%	3.2	Gage
203	Depth of cutout		0.65%	3.2	Gage
204	Protective finish inadequate of damaged		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

Quality conformance inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63985(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Shim				9278017 1 & 2
					NEXT HIGHER ASSEMBLY 9277852
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. Inspection equipment required to perform the inspections prescribed in this specification are identified in 4.4.2.1 and 4.4.2.2. See 6.2 for details concerning responsibilities for inspection design and approval.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C. The parts shall be preserved and packaged in accordance with MIL-STD-1169.

5.2 Packing.

5.2.1 Level C. The parts shall be packed for shipment in accordance with MIL-STD-1169.

5.3 Marking. Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping. When parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required, to Commander, Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A640)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.