INCH-POUND

MS25321P
05 October 2020
SUPERSEDING
MS25321N
27 November 2003

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 5 AMPERES, 2 PDT, TYPE I, SOCKET MOUNTED, MECHANICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 5 JUNE 87. NO SUPERSEDING SPECIFICATION.
(FOR NEW DESIGN USE MIL-PRF-83536/1 OR MIL-PRF-83536/2).

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.




FIGURE 1. Design, dimensions, and circuit diagram.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.001	0.03	.176	4.47
.005	0.13	.203	5.16
.010	0.25	.304	7.72
.040	1.02	.344	8.74
.047	1.19	.456	11.58
.062	1.57	.608	15.44
.075	1.91	.687	17.45
.088	2.24	1.500	38.10
.093	2.36	1.812	46.02
.143	3.63	1.844	46.84
.147	3.73	2.187	55.55
.152	3.86		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Terminal numbers shall not appear on relay headers. There shall be affixed to the relay a legible circuit diagram that permanently and positively identifies each term in allocation specified herein.
5. The use of diodes on ac relays is optional. Actual application shall be shown on label.
6. Pins shall be perpendicular to header surface within one degree.
7. In the event of conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
8. Referenced Government documents of the issue listed in that issue of the Acquisition Streamlining and Standardization Information System (ASSIST) specified in the solicitation forms a part of this standard to the extent specified herein.
9. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
10. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 20 ±5, thickness .075 ±.005 recessed .047 into bracket. Gasket material according to SAE-AMS3332 has been considered acceptable.

FIGURE 1. Design, dimensions, and circuit diagram - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, dimensions, and circuit diagram: See figure 1.

Part or Identifying Numbers (PIN's) and general characteristics: See table I.

Contact data:

Load ratings: See table II.

Maximum contact drop:

Initial: 0.150 volt.

After life test: 0.175 volt.

Overload current: 20 amperes.

Rupture current: 25 amperes.

Coil data: See table III.

Duty rating: Continuous.

RFI specification: MIL-STD-461 (applicable to coil circuits of ac operated relays).

Electrical data:

Minimum insulation resistance:

Initial: 100 megohms.

After life or environmental test: 50 megohms.

Dielectric strength (sea level):

	Initial	After life tests
Coil to case	1,000 V rms	750 V rms
Aux contacts	N/A	N/A
All other points	1,000 V rms	1,000 V rms

Dielectric strength (80,000 ft):

	Initial	After life tests
Coil to case	250 V rms	N/A
Aux contacts	N/A	N/A
All other points	250 V rms	N/A

Environmental characteristics:

Temperature range: -70° to +125°C.

Maximum altitude rating: 80,000 feet.

Shock g-level: 50 g's.

Duration: 6 ms.

Max duration contact opening: 100 μs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

Vibration (sinusoidal):

G-level: 10 g's.

Frequency range: 5 - 1,500 Hz.

Acceleration: 15 g's.

Performance of groups B and C tests is not applicable.

Part or Identifying Number (PIN): MS25321 - (plus dash number from table I).

Qualification by similarity: See MIL-PRF-6106.

TABLE I. Dash numbers and general characteristics.

PIN MS25321-	Type	Coil	Terminal type	Maximum weight pounds
D2	I	dc	Plug in	0.18
A2	I	ac	Plug in	0.20
A3	I	ac	Plug in	0.20

TABLE II. Rated contact load (amperes per pole) (case grounded). 1/

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase				See notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	
Resistive	100	5	5			5	4							
	100													
Inductive	20	3	3			3	2							
Motor	100	1.5	1.5			1.5	1							
Lamp	100	0.8	0.8			0.8	0.6							
Transfer load														2/
Mechanical life reduced current	400	1.25	1.25			1.25	1							
Mixed loads	Applicable per MIL-PRF-6106													

1/ Absence of value indicates parameter is not applicable to this specification.
2/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

TABLE III. Operating characteristics.

PIN MS25321 -	Coil data											Time - milliseconds max 2/					
	Coil	Rated			Max		Max pick-up voltage			Hold volt-age 2/	Drop out vol-tage 2/	Oper -ate 3/	Re-leae 4/	Contact Bounce			
														Main		Aux	
		Volts 1/	Freq Hz	Res Ω	Volts	Amp	Nor-mal 2/	High temp test	Cont cur-rent test					NO	NC	NO	NC
D2	X1, X2	28	dc	N/A	29	0.15	18	19.8	22.5	7.0	1.5	20	20	2	2	N/A	N/A
A2	X1, X2	115	400	N/A	122	0.06	90	95	103	35	5.0	25	50	2	2	N/A	N/A
A3	X1, X2	115	50/ 60	N/A	122	0.07	90	95	103	35	5.0	25	50	2	2	N/A	N/A

1/ CAUTION: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With rated coil voltage.
4/ From rated coil voltage.
5/ Absence of value indicates parameter is not applicable to this specification.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:

MIL-STD-461 SAE-AMS3332 ASTM-B488

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2020-054)

Review activities:
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.