NOTICE OF
CHANGE

DOD-STD-35-70A(MI)
NOTICE 3
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

SWITCHES, TOGGLE

TO ALL HOLDERS OF DOD-STD-35-70A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-70A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	31 AUGUST 1987 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	31 AUGUST 1987
3	18 SEPTEMBER 1992	3	31 AUGUST 1987
4	31 AUGUST 1987 (Reprinted without change)		
7	18 SEPTEMBER 1992	7	31 AUGUST 1987
8	18 SEPTEMBER 1992	8	31 AUGUST 1987
35	15 DECEMBER 1978 (Reprinted without change)		
36	18 SEPTEMBER 1992	36	15 DECEMBER 1978
37	18 SEPTEMBER 1992	37	15 DECEMBER 1978
38	15 DECEMBER 1978 (Reprinted without change)		
153	15 DECEMBER 1978 (Reprinted without change)		
154	18 SEPTEMBER 1992	154	15 DECEMBER 1978
155	18 SEPTEMBER 1992	155	15 DECEMBER 1978
156	15 DECEMBER 1978 (Reprinted without change)		

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-70A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A427)

AMSC N/A

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Switches, Toggle.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSEs for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on a SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference. When more than one document is listed for an MSE title, this information will be useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SWITCH, TOGGLE	015001	W-S-896	FLUSH MOUNTED
		MIL-S-3950	ENVIRONMENTALLY SEALED
		MIL-S-5594	ELECTRICALLY HELD
		MIL-S-8834	POSITIVE BREAK
		MIL-S-9419	MOMENTARY
		MIL-S-13735	28 VDC
		MIL-S-27624	EXPLOSION PROOF
		MIL-S-81551	HERMETICALLY SEALED
		MIL-S-83731	UNSEALED AND SEALED
		MS14001	SINGLE POLE 25 AMPS
		MS14002	DOUBLE POLE 25 AMPS
		MS14003	4 POLE 25 AMPS
		MS16656	SINGLE POLE SINGLE THROW
		MS18150	2 CIRCUIT
		MS18151	1 POLE
		MS18152	2 POLE
		MS21026	MINIATURE SINGLE POLE
		MS21027	MINIATURE DOUBLE POLE
		MS21346	SINGLE POLE IWT
		MS21347	DOUBLE POLE IWT
		MS24655	SOLDER LUG SINGLE POLE
		MS21351	SOLDER LUG SINGLE POLE

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SWITCH, TOGGLE (CONT)	015001 (CONT)	MS24656	SOLDER LUG DOUBLE POLE
		MS21353	SOLDER LUG DOUBLE POLE
		MS21354	PC BOARD TERM SINGLE POLE
		MS21355	PC BOARD TERM DOUBLE POLE
		MS21356	PC BOARD TERM SINGLE POLE
		MS21357	PC BOARD TERM DOUBLE POLE
		MS21433	1 POLE RT ANGLE
		MS21434	2 POLE RT ANGLE
		MS21436	SINGLE POLE
		MS21437	2 POLE
		MS24523	1 POLE
		MS24524	2 POLE
		MS24525	4 POLE
		MS24612	SCREW TERMINAL SINGLE POLE
		MS24613	SCREW TERMINAL DOUBLE POLE
		MS24614	SCREW TERMINAL 4 POLE
		MS24655	SOLDER LUG SINGLE POLE
		MS24656	SOLDER LUG DOUBLE POLE
		MS24658	1 POLE LEVER LOCK
		MS24659	2 POLE LEVER LOCK
		MS24660	4 POLE LEVER LOCK
		MS25306	SCREW TERMINAL SINGLE POLE
		MS25307	SCREW TERMINAL DOUBLE POLE
		MS25308	SCREW TERMINAL 4 POLE
		MS27406	4 POLE

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SWITCH, TOGGLE (CONT)	015001 (CONT)	MS27407	2 POLE
		MS27408	2 POLE LEVER LOCK
		MS27409	4 POLE LEVER LOCK
		MS27708	4 POSITION
		MS27716	SINGLE POLE UNSEALED
		MS27717	DOUBLE POLE UNSEALED
		MS27718	SINGLE POLE TOGGLE SEAL
		MS27719	DOUBLE POLE TOGGLE SEAL
		MS27720	SINGLE POLE LEVER LOCK
		MS27721	DOUBLE POLE LEVER LOCK
		MS27722	1 POLE IWT
		MS27723	2 POLE IWT
		MS27724	4 POLE IWT
		MS27734	1 POLE SOLDER TERMINAL
		MS27735	2 POLE SOLDER TERMINAL
		MS27736	4 POLE SOLDER TERMINAL
		MS27737	1 POLE LEVER LOCK
		MS27738	2 POLE LEVER LOCK
		MS27739	4 POLE LEVER LOCK
		MS27753	DOUBLE POLE
		MS27754	DOUBLE POLE LEVER LOCK
		MS27781	1 POLE IWT LEVER LOCK
		MS27782	2 POLE IWT LEVER LOCK
		MS27783	4 POLE IWT LEVER LOCK

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:58Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-S-8834	Switches, Toggle, Positive Break, General Specification For
MIL-S-9419	Switches, Toggle, Momentary, Four-position On, Center Off
MIL-F-13927	Fungus Resistance Test; Automotive Components
MIL-F-14256	Flux, Soldering, Liquid (Rosin Base)
MIL-S-81551	Switches, Toggle, Hermetically Sealed, General Specification For
MIL-S-83731	Switches, Toggle, Unsealed and Sealed Toggle, General Specification For

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation Systems

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-1184	Electrical Components for Automotive Vehicles; Waterproofness Tests
MIL-STD-1285	Marking of Electrical and Electronic Parts
DOD-STD-1866	Soldering Process, General (Non-Electrical)

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

TERMINATION CONFIGURATION. THE TERMINATION CONFIGURATION SHALL BE AS SPECIFIED IN THE TERMINATION CONFIGURATION TABLE.

TERMINATION CONFIGURATION TABLE

ITEM	SIZE	LENGTH/THICKNESS	QUANTITY
SCREW ATTACHMENT	3900	3901	3902
WIRE LEAD	3903	3904	3905
SINGLE TURRET	3906	3907	3908
DOUBLE TURRET	3909	3910	3911
J-HOOK	3912	3913	3914
SOLDER EYE	3915	3916	3917
SOLDER LUG	3918	3919	3920
SLIP-ON LUG	3921	3922	3923
CONNECTOR	3924	3925	3926
3927	3928	3929	3930
3931	3932	3933	3924
3935	3936	3937	3938

TYPE OF OPERATION. THE TYPE OF OPERATION SHALL BE AS FOLLOWS:

1614 KEYWAY: 1614.

1616 CENTER: 1616.

1618 OPPOSITE KEYWAY: 1618.

1580 TERMINAL DESIGNATION. THE TERMINAL DESIGNATION(S) SHALL BE IN ACCORDANCE WITH ILLUSTRATION 1580.

1582 STYLE 1582 SHALL APPLY.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
ACTUATING LEVER	
INSULATED FROM ALL CURRENT-CARRYING PARTS.	1584
LUSTERLESS FINISH.	1586
MOUNTING ALTITUDE (SELECT ONE)	
ANY POSITION.	1588
OTHER ____	1590
SOLDERING	
PER DOD-STD-1866.	1592
PER REQUIREMENT 5, MIL-STD-454.	1594
FLUX PER MIL-F-14256.	1596
NOT USED FOR MECHANICAL STRENGTH.	1598
OTHER ____	1600
ALTITUDE	
OPERATING (SELECT ONE)	
SEA LEVEL TO (FEET)	6790
SEA LEVEL TO (METERS)	6791

Source: DLA Document Services -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	ACTUATING LEVER.
1584	THE ACTUATING LEVER SHALL BE INSULATED FROM ALL CURRENT-CARRYING PARTS.
1586	THE ACTUATING LEVER SHALL HAVE A LUSTERLESS FINISH.
	MOUNTING ALTITUDE.
1588	THE ITEM(S) SHALL BE CAPABLE OF BEING MOUNTED IN ANY POSITION.
1590	THE ITEM(S) SHALL BE CAPABLE OF BEING MOUNTED 1590.
	SOLDERING.
1592	SOLDERING SHALL BE IN ACCORDANCE WITH DOD-STD-1866.
1594	SOLDERING SHALL BE IN ACCORDANCE WITH REQUIREMENT 5 OF MIL-STD-454.
1596	FLUX SHALL BE IN ACCORDANCE WITH MIL-F-14256.
1598	SOLDERING SHALL NOT BE USED FOR MECHANICAL STRENGTH.
1600	1600.
6790	OPERATING ALTITUDE. THE OPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6790 FEET.
6791	OPERATING ALTITUDE. THE OPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6791 METERS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
ALTITUDE (CONT)	
NONOPERATING (SELECT ONE)	
SEA LEVEL TO (FEET)	6792
SEA LEVEL TO (METERS)	6793
TEMPERATURE	
MAXIMUM OPERATING (DEGREES CELSIUS)	6794
MAXIMUM NONOPERATING (DEGREES CELSIUS)	6795
MAXIMUM STORAGE (DEGREES CELSIUS)	6796
MAXIMUM SERVICE (DEGREES CELSIUS)	6797
MAXIMUM AMBIENT OPERATING (DEGREES CELSIUS)	6798
MINIMUM OPERATING (DEGREES CELSIUS)	6799
MINIMUM STORAGE (DEGREES CELSIUS)	6801
MINIMUM SERVICE (DEGREES CELSIUS)	6802
MINIMUM AMBIENT OPERATING (DEGREES CELSIUS)	6803
NOMINAL STORAGE (DEGREES CELSIUS)	6804

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1453	THE MONITORING INSTRUMENTATION OF THE VIBRATION EXCITATION SHALL BE A CALIBRATED AC TO DC CONVERTER SYSTEM.
1459	THE MONITORING INSTRUMENTATION OF THE VIBRATION EXCITATION SHALL BE A CALIBRATED OSCILLOSCOPE.
1430	THERE SHALL BE 1430 VIBRATION MONITORING POINT(S).
1439	THE LOCATION OF VIBRATION MONITORING POINTS SHALL BE ANY SUITABLE LOCATION.
1462	THE LOCATION OF VIBRATION MONITORING POINTS SHALL BE AS CLOSE AS PRACTICAL TO THE TEST SPECIMEN(S).
1402	MONITORING DURING THE TEST SHALL BE IN ACCORDANCE WITH METHOD 310 OF MIL-STD-202. TEST CIRCUIT LETTER 1402 SHALL APPLY.
1382	TEST CONDITION LETTER 1382 IN ACCORDANCE WITH METHOD 310 OF MIL-STD-202 SHALL APPLY.
4678	THE LOAD SHALL BE 4678 PERCENT OF THE RATED LOAD.
4977	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
4976	MOUNTING SHALL BE BY THE NORMAL METHOD.
4975	MOUNTING SHALL BE IN ACCORDANCE WITH 4975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WATERPROOFNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2680
NO EVIDENCE OF WATER LEAKAGE.	2682
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2684
PER MIL-STD-1184.	2686
TYPE (SELECT ONE)	
I.	2688
II.	2690
CLASS (SELECT ONE)	
1.	2692
2.	2694
3.	2696
4.	2698
MOUNTING HARDWARE (SEE TABLE X. DOD-STD-35)	
NOTE: AUTOMATIC WHEN TABLE X IS USED.	

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2680	WATERPROOFNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2680.
2682	WATERPROOFNESS. THERE SHALL BE NO EVIDENCE OF WATER LEAKAGE.
2684	WATERPROOFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2684.
2686	WATERPROOFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-STD-1184.
2688	THE SWITCH SHALL BE CLASSIFIED AS TYPE I.
2690	THE SWITCH SHALL BE CLASSIFIED AS TYPE II.
2692	THE SWITCH SHALL BE CLASSIFIED AS CLASS 1.
2694	THE SWITCH SHALL BE CLASSIFIED AS CLASS 2.
2696	THE SWITCH SHALL BE CLASSIFIED AS CLASS 3.
2698	THE SWITCH SHALL BE CLASSIFIED AS CLASS 4.

MOUNTING HARDWARE. MOUNTING HARDWARE IDENTIFIED IN THE FOLLOWING TABLE SHALL BE FURNISHED WITH EACH ITEM.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WORKMANSHIP	
(DOC DES)	6870
ADDITIONAL REQUIREMENTS	
A ____	7001
B ____	7002
C ____	7003
D ____	7004
E ____	7005
PART MARKING (SELECT ONE)	
(DOC DES)	6372
MIL-STD-1285.	7360
MIL-STD-130.	7629
ADDITIONAL PART MARKING	
A ____	6991
B ____	6992
C ____	6993
D ____	6994
E ____	6995

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:58Z
Check the source to verify that this is the current version before use.