MIL-STD-1169A (AR)
NOTICE 1
9 September 1983

MILITARY STANDARD

PACKAGING, PACKING AND MARKING
FOR SHIPMENT OF
INERT AMMUNITION COMPONENTS

TO ALL HOLDERS OF MIL-STD-1169A (AR):

1. THE FOLLOWING PAGES OF MIL-STD-1169A (AR) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	10 November 1977	(reprinted without change)	10 November 1977
2	30 June 1983	2	10 November 1977
7	10 November 1977	(reprinted without change)	10 November 1977
8	30 June 1983	8	10 November 1977
9	30 June 1983	9	10 November 1977
10	10 November 1977	(reprinted without change)	10 November 1977
15	10 November 1977	(reprinted without change)	10 November 1977
16	30 June 1983	16	10 November 1977

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-1169A (AR) will verify that page changes and additions indicated above have been entered. This notice will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A631)

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 This standard establishes general packaging, packing, palletizing, and marking instructions for shipment of inert ammunition components. Domestic requirements are intended for use when storage will be of short duration in warehouse and when shipment is normally expected to be made in full carloads or truckloads. Overseas requirements are intended for normal hazards of overseas shipment and storage.

1.2 CLASSIFICATION: Shipping requirements shall be of the following levels and components as specified:

Level A: Overseas Shipment
- Unit Packaging
- Intermediate Packaging
- Packing
- Palletization

Level B: Domestic Shipment (See Notes, Section 6)
- Unit Packaging
- Intermediate Packaging
- Packing
- Palletization

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

2. REFERENCED DOCUMENTS

2.1 ISSUE OF DOCUMENTS. The following specifications, drawings, and publications, of the issue in effect on date of invitation for bids or request for proposals, form a part of this standard to the extent specified herein:

SPECIFICATIONS

Federal

- NN-P-71 - Pallet, Materials, Handling, Wood, General Construction Requirement
- QQ-S-781 - Steel Strapping Flat
- MMM-A-178 - Adhesive, Paper Label, Water Resistant
- PPP-B-26 - Bag, Plastic
- PPP-F-320 - Fiberboard, Corrugated and Solid Sheet Stock Container Grade and Cut Shapes
- PPP-B-566 - Boxes, Folding, Paperboard
- PPP-B-585 - Box, Wood, Wireboard
- PPP-B-601 - Boxes, Wood, Cleated
- PPP-B-621 Boxes, Wood Nailed and Lock-Corner
- PPP-B-636 - Boxes, Fiber
- PPP-B-676 - Boxes, Set-Up Paper
- PPP-C-843 - Cushioning, Material Cellulosic

Military

- MIL-P-116 - Preservation, Method of
- MIL-B-117 - Bag Interior Packaging
- MIL-B-121 - Barrier Material, Greaseproofed, Flexible
- MIL-B-2427 - Boxes, Ammunition Packing Wood Nailed
- MIL-C-2439 - Containers, Fiber
- MIL-A-2550 - Ammunition and Special Weapon General Specification for
- MIL-C-3955 - Cans, Composite Spirally Wound
- MIL-L-10547 - Liners Case and Sheet Overwrap Water, Vaporproof or Waterproof, Flexible
- MIL-P-15011 - Pallets, Material Handling Hardwood, Post Construction 4 Way
- MIL-B-46506 - Boxes, Ammunition, Packing Wood Wirebound
- MIL-T-43036 - Tape, Pressure Sensitive Adhesive, Plastic Film, Fildment Reinforced and Sealing Fiber Containers and Cans

STANDARDS

- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
- MIL-STD-109 - Quality Assurance Terms and Definitions

Source: https://assist.dla.m -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

barrier shall not exceed 8 percent when tested in accordance with Method 205 of Fed. Test Method No. 101.

4.3.1.2.3 Greaseproof packages. Items coated with an easily transferable perservative coating shall be wrapped in a greaseproof paper complying with Type I or II, Grade A of MIL-B-121 prior to being placed in a barrier bag described in 4.3.1.2.1 or 4.3.1.2.2. Alternatively, the fiber container specified in 4.3.1.2.2 may be used.

4.3.2 Level B. Items shall be packaged as specified in 4.3.1, 4.3.1.1 and 4.3.1.2. Taping of fiber containers may be omitted if fiber containers are tightly overpacked provided waterproofness of moistureproofness is not required.

4.3.2.1 Additional requirements. When required by the nature of the item or when specifically called for, waterproofness, moistureproofness and greaseproofness shall comply with 4.3.1.2.1, 4.3.1.2.2, or 4.3.1.2.3 as applicable.

4.3.2.2 Bags. The unit package may be a bag. Bags shall comply with MIL-B-117, any Type and Class as appropriate. Bags shall be closed by heat sealing. Alternatively bags for small parts or for dust covers may be made from .002 inch minimum nominal thickness polyethylene film in accordance with MIL-B-43165. Polyethylene bags shall be impulse sealed. Dust covers need not be sealed but shall be long enough to stay closed when folded.

4.4 Intermediate packaging.

4.4.1 Level A. When unit packages are not waterproof or are less than 5 pounds in weight or less than 500 cubic inches in size, except for fiber containers, they shall be packaged in W-board or V-board boxes made and closed in accordance with PPP-B-636. Alternatively, domestic class, fiber boxes, each inclosed in a heat sealed liner complying with Type I, Grade A or B of MIL-L-10547 may be used. Intermediate packages shall not exceed 30 pounds net weight or 2 cubic feet in volume.

4.4.2. Level B. Intermediate packages may be used, if desired to consolidate small unit packages or to facilitate packing and assembly line handling. Intermediate boxes shall meet the requirements for domestic class fiber boxes of PPP-B-636. Closure shall be accomplished by stapling, stitching, taping, gluing or a combination of these methods.

4.5 Packing.

4.5.1 Level A. Shipping containers for Level A use shall be nailed wood or wirebound boxes except that for very light, bulky items weather resistant V-board grades of fiberboard boxes may be used. These fiberboard boxes may also be used for air shipment of other items when authorized by the ordering agency. Boxes shall comply with the overseas requirements of one of the

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the current version before use.

following Specifications PPP-B-621, MIL-B-2427, PPP-B-585, MIL-B-46506, PPP-B-636. Overseas types of containers other than those listed above conforming to approved Government specifications may be used if approved by the ordering agency. The gross weight of a shipping container shall in no case exceed the weight specified in referenced government container specifications or applicable Interstate Commerce Commission regulations. Unless otherwise specified by the contracting officer the gross weight of fiberboard shipping containers shall not exceed 70 pounds and the exterior cube size shall not exceed 2.5 cubic feet; the gross weight of wood boxes shall not exceed 150 pounds or 4 cubic feet. Individual shipping containers shall be not less than one cubic foot in size. Small quantities of items in unit or intermediate packages may be consolidated in one shipping container within the above requirements for shipment to a single destination. Container closure and strapping, shall be in accordance with the applicable container specification. Strapping of MIL-B-46506 wirebound boxes is not required.

4.5.2 Level B. Domestic containers, together with interior packaging, shall be so constructed as to give assurance that the items being shipped will remain in prime condition. The containers shall be sufficiently rigid to withstand transportation and permit storing in tiers at least 10 feet high without damage to containers or contents. Shipping containers shall comply with the applicable Interstate Commerce Commission regulations for shipment by truck or railroad. In addition, corrugated or solid fiberboard boxes shall comply with Specification PPP-B-636; nailed wood boxes shall comply with Specification PPP-B-621; wirebound boxes shall comply with PPP-B-585. The gross weight of fiberboard boxes shall not exceed 70 pounds. The gross weight of wood containers shall not exceed 150 pounds without skids or 1000 pounds with nominal 4" by 4" skids attached to the bottom. Closure of domestic type fiberboard cartons shall be in accordance with Uniform Freight Classification Regulations, Rule 41 or in accordance with Specification PPP-B-636. Other containers shall be closed and strapped, if required, in accordance with the applicable box specification.

4.6 Palletization.

4.6.1 Level A. Shipping containers that are not on skids shall be palletized. Pallets shall comply with MIL-P-15011 or NN-P-71. Palletization procedures shall be in accordance with MIL-STD-147 with the following exceptions:

a) Pallet sizes mayi be 40" x 48" (NN-P-71 or MIL-P-15011), 35" x 45-1/2" (MIL-P-15011) or 42" x 53" (MIL-P-15011). Pallets will be constructed from MIL-STD-731 Group III or IV wood.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

b) Gross weight of loaded pallet shall not exceed 4,000 pounds.

c) Strapping shall be metallic.

d) Shrink-film or stretch wrap bonding shall not be used.

4.6.2 Level B. Shipping containers may be palletized at the contractor's option, unless otherwise directed. Pallets shall be in accordance with MIL-P-15011 or NN-P-71. Palletization procedures and strapping illustrations are in accordance with MIL-STD-147 except:

a) Pallet sizes may be 40" x 48" (NN-P-71 or MIL-P-15011), 35" x 45-1/2" (MIL-P-15011) or 42" x 53" (MIL-P-15011). Pallets will be constructed from MIL-STD-731 Group III or IV Wood.

b) Gross weight of loaded pallet shall not exceed 4,000 pounds.

c) Shrink film and stretch wrap bonding shall not be used for loads weighing more than 3,000 pounds.

4.7 Marking.

4.7.1 Unit and intermediate package.

4.7.1.1 Level A. Each unit and intermediate container or bag shall be labeled, printed or stamped with the following identification:

PART NO.
QUANTITY - NOMENCLATURE
FOR: (MAJOR ITEM)
LOT NO.
PACKED (MO/YR)

Lettering shall be all capitals. All markings shall be 1/4 inch in size. When space is insufficient for this size, markings shall be as large as space permits. Marking ink shall be commercial, waterproof, black in color except white ink shall be used when a contrast to the marking surface is necessary for better visibility. Labels shall be ungummed, white paper having a minimum 22 pound basis weight (500 sheets - 17 x 22 inches). Label adhesive shall conform to MMM-A-178. All exterior surfaces of the label shall be coated with MMM-A-178 adhesive, clear com- mercial varnish or shellac. Gummed labels or commercial label adhesive without exterior coating are acceptable when the labeled container is further overpackaged in another container or bag. Labels may be placed loose inside transparent plastic bags.

4.7.1.2 Level B. Each unit and intermediate container or bag shall be marked the same as Level A except labels may be commercial gummed or ungummed; commercial label adhesive may be used; and no overcoating of label is required.

4.7.2 Exterior container.

4.7.2.1 Level A. Each shipping container shall be printed or stenciled on the upper portion of one end or side near

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

one end with the following information (see fig. 1):

PART NO.
QUANTITY - NOMENCLATURE
LOT NO. PACKED (MO/YR)
CONTRACT NO.
WT. CU.

Lettering shall be all capitals. All markings shall the following size:

	Minimum	Maximum
Stenciling or printing	7/16"	1"
Labels	1/4"	1/2"

Labels may be used only if there is insufficient space or the nature of the container is such as to make printing or stenciling impractical. Labels and label adhesive and manner of application shall conform to 4.7.1.1. Printing and stenciling ink shall be commercial, waterproof ink manufactured expressly to withstand outdoor exposure for a period of 6 months or more without fading or obliteration.

4.7.2.2 Level B. Each shipping container shall be marked the same as Level A except labels may be commercial gummed or ungummed applied with commercial label adhesive. No exterior coating of labels is required.

4.7.3.1 Level A. The following destination markings shall be labeled, printed or stenciled on the upper 1/3 of one side of the exterior container (see fig. 1):

FROM NAME OF CONTRACTOR
ADDRESS

TO NAME OF CONSIGNEE
ADDRESS

The domestic address is not required when shipment is by carload lot to a common destination. Lettering and size shall be the same as specified in 4.7.2.1. Labels shall be commercial gummed or ungummed labels applied with commercial label adhesive. No exterior coating of labels is required. Stenciling or printing shall be the same for exterior container markings 4.7.2.1

4.7.3.2 Overseas address. The overseas address in code or in the clear shall be stenciled or printed on the bottom 1/3 of the same box side on which the domestic address appears. Letters shall be capitalized. All markings shall be minimum 3/4" maximum 1 1/2". Stenciling and printing material requirements shall be the same as specified in 4.7.2.1 (see fig. 1). Labeling may be used only when authorized by the contracting officer.

4.7.3.3 Level B. Destination marking shall be the same as Level A.

4.7.4 Marking for palletized loads. Containers shall be arranged on the pallet so that the identification markings of one or more containers is visible on at least two of the four pallet sides.

4.7.4.1 Domestic address. Domestic address markings as specified in 4.7.3 shall appear on a container located on the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

5.2.1.3 Unit containers.

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Container interior contaminated with dirt, lint or other foreign matter	Visual
Minor:	AQL 1.5 percent	
201.	Container improperly closed or sealed	Visual
202.	Container markings, illegible, missing, incorrect or incomplete	Visual
203.	Number of containers incorrect	Visual

5.2.1.4 Palletization.

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Pallet damaged or members insecure	Visual
102.	Strapping loose or insufficient	Visual
Minor:	AQL 2.5 percent	
201.	Marking incorrect	Visual
202.	Strapping improperly applied	Visual
203.	Splinters projecting	Visual
204.	Nails or fasteners projecting	Visual
205.	Load not tightly stocked	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Level B of this standard is intended only for known schedule usage when storage prior to use of the items contained can be reasonably expected to be of short duration and in good warehouse conditions. Level A should be used for all other specifications.

6.2 When a specification requires a contractor to perform packaging in accordance with "Level C of MIL-STD-1169", Level B packaging shall be used.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A416)

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the current version before use.