INCH-POUND

MS53232B
W/AMENDMENT 1
1 August 2023
SUPERSEDING
MS53232B
31 August 2007


MILITARY SPECIFICATION SHEET

COILS, RADIO FREQUENCY, ENCAPSULATED, VARIABLE, MICRO-MINIATURE, FERRITE CORE, LT11V060 TO LT11V076, INCL

Inactive for new design.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification and MIL-PRF-15305.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 1. Dimensions and configuration.

AMSC N/A
FSC 5950

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.

INCHES	mm
.015	0.38
.040	1.02
.097	2.46
.100	2.54
.145	3.68
.250	6.35
.260	6.60
.325	8.26
.350	8.89
.475	12.07

FIGURE 1. Dimensions and configuration – Continued.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Weight: .2 gram, maximum.

Operating temperature range: -55° to +105°C.

Ambient temperature: +90°C maximum.

Temperature rise: 15°C.

Power dissipation: 225 mW maximum.

Lead material: -1 through -13 is .018 (0.46 mm) diameter gold plated Kovar.
-14 through -17 is .013 (0.33 mm) diameter gold-plated Kovar.

Terminal pull: -1 through –13 is 2 pounds, minimum.
-14 through –17 is 1 pound, minimum.

Tuning torque: .005 - .15 in. oz.

Stop torque: .2 in. oz. max.

Altitude: 70,000 feet.

Shock, specified pulse: MIL-STD-202-213, test condition I, is applicable.

Dielectric withstanding voltage:

At sea level: MIL-STD-202-301, test voltage 1,000 V rms minimum.

At reduced barometric pressure: MIL-STD-202-105, test condition C, test voltage 300 V rms minimum.

Electrical characteristics: See tables I and II.

Inductance: See table I.

Q values: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.

Self-resonant frequency (SRF): See table I.

DC resistance (DCR): See table I.

Marking: Marking shall be as specified in MIL-PRF-15305 except that the marking shall be on the unit package or container.

Part or Identifying Number (PIN): MS53232 - (dash number from table I).

TABLE I. Electrical characteristics (initial).

Dash Number MS53232	Inductance L Max. µH	Inductance L Min. µH	Q Min. At L Max.	Test Frequency (MHz)	SRF Minimum (MHz)	DC resistance At 25°C, max (Ohms)	Rated DC current, maximum (mA)
-1	10.0	5.5	25	2.5	40	2.8	57
-2	13.0	6.5	25	2.5	35	3.0	53
-3	16.0	8.0	30	2.5	26	3.4	50
-4	20.0	10.0	30	2.5	20	3.5	43
-5	22.0	11.0	30	2.5	14	4.0	43
-6	30.0	15.0	30	2.5	10	4.5	40
-7	36.0	18.0	30	2.5	9	5.0	40
-8	47.0	24.0	30	2.5	6.5	5.7	39
-9	56.0	28.0	30	2.5	6.3	7.0	35
-10	68.0	34.0	30	2.5	6.2	8.0	30
-11	75.0	38.0	30	2.5	5.9	9.0	30
-12	86.0	43.0	30	2.5	5.6	10.0	28
-13	100.0	50.0	30	.79	5.4	12.0	27
-14	120.0	60.0	25	.79	4.4	14.0	25
-15	470.0	240.0	20	.79	2.1	30.0	16
-16	680.0	340.0	20	.79	2.0	35.0	15
-17	1 mH	.5 mH	20	.79	1.1	75.0	11

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.


TABLE II. Electrical characteristics (final).

Inspection group	Allowable variation from Initial measurement	Allowable variation from Initial measurement	Allowable percent from specified minimum value in electrical characteristics (initial) table	Allowable percent from specified minimum value in electrical characteristics (initial) table
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±5	---	---	-10
Group III	±10	±(2% +.001 ohm)	-15	-20
Group IV	±5	±(2% +.001 ohm)	-10	-20
Conformance inspection group C				
Subgroup I	±5	---	---	-10
Subgroup II	±5	±(2% +.001 ohm)	-10	-20
Subgroup III	±10	±(2% +.001 ohm)	-15	-20

Application notes:

1. The test fixture in the diagram following shall be used for electrical measurements. Inductance values are effective inductance as indicated on a HP260A, HP190A or equivalent Q meter, when tested in the test fixture. Add 5 percent to Q reading to account for loss of Q in the test jig.
2. Polarization during moisture resistance test is not applicable.
3. Coils are held rigidly by the body during vibration and mechanical shock testing.
4. Resistance to soldering heat test, per MIL-STD-202-210, test condition B, is applicable.
5. For dielectric withstanding voltage, barometric pressure and insulation resistance units shall be placed on Flat metal plate with leads insulated from surface. Measurement of dielectric withstanding voltage, barometric pressure and insulation resistance shall be between the leads of the coil connected together and the metal plate.
6. Screw core assembly shall be set at maximum specified inductance value indicated in the electrical characteristics table (initial), prior to all inspection tests. This setting shall not be changed until electrical characteristics (final) measurements are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.



INCHES	MM
.012	0.30
.080	2.03
.1405	3.570
.175	4.45
.250	6.35
.300	7.62
.340	8.64
.420	10.67

FIGURE 2. Test fixture for electrical measurements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-15305, this document references the following:

MIL-STD-202-105 MIL-STD-202-210 MIL-STD-202-213 MIL-STD-202-301

Custodians:
Army – CR
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA – CC

Project 5950-2023-019

Review activities:
Army – AR, MI
Navy – AS, MC, OS, SH
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:22Z
Check the source to verify that this is the current version before use.