INCH-POUND

MIL-M-38761/1B(AS)
15 DECEMBER 1994
SUPERSEDING
MIL-M-38761/1A(AS)
1 MAY 1982

MILITARY SPECIFICATION

MICROFILM IMAGE CARDS AND TABULATING CARDS USED FOR RECORDING ENGINEERING DRAWINGS AND ASSOCIATED DATA

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 SCOPE This specification covers the acquisition of microfilm image cards and tabulating cards for the microfilm frame deck used for recording engineering drawings and associated data.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, System Standardization, Code 4.1.11B120-3, Naval Air Warfare Center Aircraft Division, Highway 547, Lakehurst, NJ 08733-5100 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA EDRS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

G-C-116 - Card, Tabulating.

MILITARY

MIL-M-9868 - Microfilming of Engineering Data, 35mm, Requirements for.
MIL-M-38761 - Microfilming and Photographing of Engineering/Technical Data and Related Documents, PCAM Card Preparation, Engineering Data Micro-Reproduction System, General Requirements for, Preparation of.

STANDARDS

MILITARY

MIL-STD-100 - Engineering Drawing Practices.
MIL-STD-804 - Formats and Coding of Aperture, Camera, Copy and Tabulating Cards.
MIL-STD-1806 - Marking Technical Data prepared by or for the Department of Defense.

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

PUBLICATIONS

FEDERAL

FAR - Federal Acquisition Regulation

(Application for copies of FAR should be addressed to the Commerce Clearing House, 4025 West Peterson Ave., Chicago, IL 60646)

DEPARTMENT OF DEFENSE

H4/H8 - Federal Supply Catalog Cataloging Handbook - Commercial and Government Entity (CAGE)

(Application for copies of H4/H8 should be addressed to the Defense Logistics Service Center, Battle Creek, MI 49017-3084)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI X3.11 - Specification for General Purpose Paper Cards for

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

Information Processing

(Application for copies should be addressed to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The complete requirements for microfilm image cards and tabulating cards are contained in this document, a completed DD Form 1423, a completed DD Form 2554, and the issue in effect of MIL-M-9868 and MIL-M-38761.

3.1.1 Contract number. The number of the government contract under which data is prepared or revised shall appear on every page of the documents. The number of the government contract under which copies of data are furnished shall appear on each page of the data delivered to the government. If copies are furnished under the same contract as that under which the data was prepared, the one entry of the contract number on the document will suffice. The contract number should be added to paper copies by rubber stamping after reproduction or by other means. On photocopies, the contract number should be added by means of an overlay at the time of photographing.

3.1.2 Distribution and export control statement. When the DD Form 1423 of the contract specifies that a distribution and export control statement are required, they shall be affixed to the first page of each document supplied to the Government during microfilming by means of an overlay. Detailed guidance for adding the distribution and export control statements are addressed in MIL-STD-1806.

3.2 Microfilm.

3.2.1 Type and class. Microfilm image cards shall be supplied for each drawing, associated list, and referenced document ordered under the contract. The microfilm set ordered as the repository master shall be Type I, Class I silver halide microfilm, negative type, clear line image in accordance with MIL-M-9868. A microfilm index shall be provided in the form of a microfilm frame deck as specified in 3.3.5. When additional sets of the documents are requested, they shall be supplied on Type II, Class II diazo image cards.

3.2.2 Multiple sources. Data from more than one source may be included in a submittal. The data from each source shall be sorted by Commercial and Government Entity (CAGE) code listed in H4/H8 and separated by a target frame supplied by the contractor who micro-filmed the data. The DD Form 250 shall identify the items covered by the data, the name and address of the contractor who developed the data, and the contract or purchase order under which the data was furnished.

3.2.3 Book form drawings and documents. The one sheet per frame format described in MIL-M-9868 shall apply to the microfilming of book form drawings and documents having page sizes of 8 x 10-1/2 inches or 8-1/2 x 11 inches. All documents shall be photographed so that data is in an upright position, right reading regardless of the position of the format. A reduction ratio of 16X shall be used.

3.2.4 Multiple sheet documents. Multiple sheet (or page) drawings or documents shall be microfilmed in consecutive sheet sequence. After the initial

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

microfilming of a multiple sheet drawing or document, if an individual sheet(s) is revised, only the sheet(s) affected by the revision needs to be remicrofilmed.

3.2.5 Multiple frame documents sequence and microfilming. Drawings requiring multiple frame microfilming shall be microfilmed in consecutive frame sequence. When multiple frame sheets are revised, the entire sheet shall be remicrofilmed.

3.2.6 Design changes, revision of drawing and associated data. Drawings and associated data shall be revised to reflect all approved changes. After initial shipment, copies of all new and revised data shall be prepared and shipped in accordance with of MIL-STD-100, chapter 600 or as otherwise specified in the contract.

3.3 Tabulating and image cards. Cards supplied for either the microfilm frame deck, image card deck or DD Form 1310 (E card) shall be in accordance with MIL-M-38761 except as specified in 3.3.1 through 3.3.3.

3.3.1 Card stock. Tabulating card stock shall be the Type 1, Style A, 80 column card specified in Federal Specification G-C-116.

3.3.2 Card size. The dimensions of the image card, tabulating card and DD Form 1310 (E card) shall be in accordance with ANSI X3.11.

3.3.3 Image card format. The printed image card format shall be in accordance with DD Form 1562 as specified in MIL-STD-804 and 3.3.3.1.

3.3.3.1 Security classification markings. Microfilm frame cards applicable to a classified frame of microfilm and image cards carrying microfilm of classified data shall be marked, stripe coded and contain downgrade markings as specified in MIL-STD-804. The microfilm frame cards that pertain to classified documents but do not contain classified information shall contain the marking, "This card is unclassified," in addition to the security markings of MIL-STD-804.

3.3.4 Corner cut. All image cards and tabulating cards, except those containing classified information, shall have an upper left corner cut. The corner cut shall be 1/4 inch along the top edge of the card and 3/8 inch along the left edge of the card. All other corners shall be rounded with a radius of 1/4 inch.

3.3.5 Microfilm frame deck. A single microfilm frame deck of tabulating cards shall accompany each shipment of microfilm. The microfilm frame deck shall consist of one tabulating card for each frame of microfilm (including targets) in microfilm frame order. The information keypunched on these cards is a duplicate of the information punched on the image cards and is used as source data for a drawing inventory/locator file.

3.3.5.1 Card punching. The standard 80 column tabulating card shall be used for the microfilm frame deck. Microfilm frame card punching and interpretation instructions for DD Form 1562 (card code H/T) using lower legend shall be in accordance with MIL-STD-804 and the following.

3.3.5.1.1 Applicable field definition. Punching and interpreting instructions for the microfilm image cards and the microfilm frame deck are as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

CARD COLUMN	FIELD DEFINITION	REMARKS
1-2	Type of document	When applicable, the type of document codes (see 3.3.5.1.2) shall be punched in this field. When type of document code does not apply, this field shall remain blank. Interpret in print position 1-2.
3-17	Document number	See MIL-STD-804. Interpret in print position 4-18.
18-22	Code identification number	See DoD Catalog H4/H8. The CAGE code of the original design activity shall be punched in this field. Interpret in print position 54-58.
23-25	Sheet number	The sheet/page number of the document identified in columns 3-17 shall be punched in this field. The number shall be right justified and the field shall be filled out with nonsignificant zeros. When documents require multiframe filming, the sheet/page number shall be punched on all cards. Interpret in print position 22-24.
26-27	Revision letter	On initial submittal of new drawings that have not yet been revised, this field shall remain blank. When applicable, the revision letter(s) of the document identified in card columns 3-17 shall be punched in this field. The revision letter(s) shall be right justified. Interpret in print position 19-20.
28-30	Number of sheets	The total number of sheets that compose the document identified in cc 3-17 shall be punched in this field on the card for the first sheet only. When a document requires multi-frame microfilming, the number of sheets shall be entered on all cards in the series of frames for the first sheet of the document. The number shall be right justified and the field shall be filled with nonsignificant zeros. Interpret in print position 25-27.

CARD COLUMN	FIELD DEFINITION	REMARKS
31-32	Frame number	The frame number of each frame in a series of frames shall be entered in this field. The number shall be right justified and the field shall be filled out with nonsignificant zeros. A single frame document shall have "01" entered in this

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

33-34	Number of frames	field. Interpret in print position 29-30. The number of frames in a series of frames shall be entered in this field on the cards for all frames of that series. The number shall be right justified and the field shall be filled out with nonsignificant zeros. A single frame document shall have "01" entered in this field. Interpret in print position 31-32.
35-45	Supplementary sheet number	This field shall be used for all sheet numbers of a document containing one or more complex sheet numbers or requiring supplementary identification; i.e., accompanying document (See 3.3.5.1.4 and 3.3.5.1.5). Interpret in position 33-43.
46	Distribution statement code	See MIL-STD-1806. The distribution statement code letter (A, B, C, D, E, F or X) of the document identified in columns 3-17 shall be punched in this field. Interpret in print position 44.
47	Rights	The indication that the Government does or does not have unlimited rights to the data shown on the microfilm image is annotated in this field. See the Federal Acquisition Regulation (FAR) subpart 227.4 - Rights in data and copyrights for an explanation of these requirements. An "L" for limited rights must be punched in this field when the contractor has proprietary rights to the data being submitted to the Government. A "U" for unlimited rights must be punched if "L" is not applicable. Interpret in print position 50.
48-49	Control activity	"KJ" shall be entered in this field on all cards. Interpret in print position 51-52.
CARD COLUMN	FIELD DEFINITION	
50	Drawing size	REMARKS The drawing size indicated on the document identified in column 3-17 shall be entered in this field. Interpret in print position 46.
51	Card code	The letter "T" shall be punched in this field on all cards. Do not interpret this field.
52	Security classification	See MIL-STD-804 for Security Classification Codes. Interpret in print position 60.
53-80	Open	This field shall remain blank.

3.3.5.1.2 Type of document codes. The following codes, along with those listed in MIL-STD-804, may be punched in this field. Additional codes may be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

used when directed by the procuring activity.

CODE	TYPE OF DOCUMENT	CODE	TYPE OF DOCUMENT
AL	Application List	PL	Parts List
BM	Bill of Material	RL	Running List
CL	Category List	SP	Contractor Specification
DL	Data List		
EL	Equipment List	ST	Contractor Standard
GL	Gage List		
IL	Index List	VL	Vendor List
LC	Content List	WL	Wiring List
ML	Material List	1N	Engineering Change Order/Notice of Revision
NL	Notes List		

3.3.5.1.3 General requirements. All targets shall be punched with the letters TARGET entered in columns 3-8. All rejected aperture cards shall be removed from the submittal by the contractor before shipping.

3.3.5.1.4 Punching and interpreting instructions for accompanying documents. Apply the following instructions to all documents that require supplementary sheet number identification. The documents include but are not limited to all accompanying documents (amendments, addenda, etc.) and all documents containing divisions (volumes, sections, etc.) that are sheet number sequenced by division rather than continuous numbering throughout the entire document. The punching instructions for the sheet number field (cc 23-25) and the supplementary sheet number field (cc 35-45) are as follows:

a. Card columns 23-24 shall remain blank. An asterisk (*) shall be entered in cc 25 and interpreted in print position 24 to indicate that the sheet number has been moved to the supplementary sheet number field, cc 35-45.

b. When the supplementary sheet number field is used to identify accompanying documents, it is segmented into three elements.

(1) A two character abbreviation used to indicate the type of document being identified is entered in cc 35-36. (See example below).

(2) Card columns 37-38 are used to identify the sequence number of the document. If the sequence number is a single digit, place the number in cc 38 and enter a nonsignificant zero in cc 37.

(3) A decimal point shall be entered in cc 39 and the page number of the document shall be entered in cc 40-45. The page number shall be left justified.

EXAMPLE:

Document

1234 Amendment 1, sheet number 1
1.1
1.1.1

1234 Section 45, sheet number 1
1.1

CARD COLUMNS	35	36	37	38	39	40	41	42	43	44	45
	A	M	0	1	.	1					

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

```
A   M   0   1   .   1   .   1
A   M   0   1   .   1   .   1   .   1
S   N   4   5   .   1
S   N   4   5   .   1   .   1
```

c. The following abbreviations shall be used:

(1) Accompanying Documents. The two letter codes specified in MIL-STD-804 apply.

(2) Divided Documents. Use the two letter code "VL" for volume and "SN" for section.

3.3.5.1.5 Punching and interpreting instructions for documents with non-standard sheet numbers. Non-standard sheet numbered documents fall in the following categories:

a. Documents with complex sheet numbers.

b. Documents containing sheet numbers and page numbers.

c. Documents whose title page and front matter are identified by Roman numeral page numbers.

d. Documents whose title page and front matter have no page numbers assigned to them.

All of the sheet numbers for these documents shall be punched in the supplementary sheet number field, cc 35-45. The sheet number field (cc 23-25) is modified to show that the sheet number has been moved. Card columns 23 and 24 shall remain blank and an asterisk (*) shall be punched in cc 25 and interpreted in print position 24.

3.3.5.1.6 Book form or multiple sheet documents containing complex sheet numbers. Complex sheet numbers are those numbers that have more than three characters in them, those that contain a combination of alpha-numeric characters and those that use decimal points to distinguish elements within the number. An example of the various types of complex sheet numbers is shown below, and the punching instructions are as follows:

a. A decimal point shall be punched in cc 39 in order to register the number within the supplementary sheet number field.

b. Those characters of the sheet number in front of the first decimal point, or those in front of the first alpha character are punched in cc 35-38. These numbers shall be right justified and nonsignificant zeros shall be used to fill the blank spaces. The remaining characters of the sheet number shall be punched left justified in cc 40-45.

EXAMPLE:

```
        Sheet numbers 20
                      20.01.0
                      2A
                      2000

CARD COLUMNS   35  36  37  38  39  40  41  42  43  44  45

SHEET NUMBER    0   0   2   0   .
```


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

SHEET NUMBER	0	0	2	0	.	0	1	.	0
SHEET NUMBER	0	0	0	2	.	A			
SHEET NUMBER	2	0	0	0	.				

3.3.5.1.7 Documents containing sheet numbers and page numbers. These documents have individual sheets that are displayed in a multi-page format. The punching instructions for this type of document are as follows:

a. A decimal point shall be punched in cc 39 to establish a point of separation between the page and sheet number sequence.

b. The sheet numbers are punched in cc 35-38. The number is right justified and nonsignificant zeros shall be used to fill the blank spaces. The page number is punched left justified in cc 40-45.

EXAMPLE:

Sheet number 1, page 1 of 3
1, page 2
1, page 3

CARD COLUMNS	35	36	37	38	39	40	41	42	43	44	45
SHEET/PAGE NO.	0	0	0	1	.	1					
SHEET/PAGE NO.	0	0	0	1	.	2					
SHEET/PAGE NO.	0	0	0	1	.	3					

3.3.5.1.8 Book form documents whose title page and front matter are identified by Roman numeral page numbers. Roman numerals cannot be stored in a computer database, therefore, a document with this type of page number must be modified. The punching instructions for this type of document are as follows:

a. A decimal point shall be punched in cc 39 to establish a separation point between the pagination of the front matter and the rest of the document.

b. The page numbers for the front matter are changed from Roman to Arabic numerals and punched left justified in cc 40-45. The page numbers for the rest of the document are punched in cc 35-38. The number is right justified and nonsignificant zeros shall be used to fill the blank spaces.

EXAMPLE:

Title page	sheet/page number I or i
First continuation sheet	sheet/page number II or ii
Second continuation sheet	sheet/page number III or iii

CARD COLUMNS	35	36	37	38	39	40	41	42	43	44	45
TITLE PAGE	0	0	0	0	.	1					
FIRST CONTINUATION SHEET	0	0	0	0	.	2					
SECOND CONTINUATION SHEET	0	0	0	0	.	3					
FIRST PAGE OF DOCUMENT	0	0	0	1	.						

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

3.3.5.1.9 Book form documents whose title page and front matter are not paginated. All pages of a document must be identified to the computer database that tracks the document. Therefore page numbers must be assigned to unidentified front matter. The punching instructions for this type of document are as follows:

a. A decimal point shall be punched in cc 39 to establish a separation point between the pagination for the front matter and the rest of the document.

b. Sequential alpha characters are to be used to identify the pages in the front matter of these documents. They are punched left justified in cc 40-45. The page numbers for the rest of the document are punched in cc 35-38. The number is right justified and nonsignificant zeros shall be used to fill the blank spaces.

EXAMPLE:

Title page	(sheet number not indicated)
First continuation sheet	(sheet number not indicated)
Second continuation sheet	(sheet number not indicated)

CARD COLUMNS	35	36	37	38	39	40	41	42	43	44	45
TITLE PAGE	0	0	0	0	.						
FIRST CONTINUATION SHEET	0	0	0	0	.	A					
SECOND CONTINUATION SHEET	0	0	0	0	.	B					
FIRST PAGE OF DOCUMENT	0	0	0	1	.						

3.3.5.2 Inclusion of card decks with subsequent deliveries. After delivery of the initial shipment of microfilm and tabulating cards, a single microfilm frame deck shall accompany each subsequent shipment of microfilm to cover additions and revisions (see 3.2.6).

3.3.6 DD Form 1310 (E card) part and drawing numbered. A single part and drawing number card deck shall accompany each shipment of microfilm when multiple whole numbers or dash numbers are used to identify individual parts depicted on multi-detail or tabulated drawings. The E card is required to update the computer database that is used to manage the drawings in the data repository. It is used to cross reference the part number depicted by dash numbers on tabulated drawings to the drawing number. Multi-detail drawings that use individual part numbers to identify each detail on the drawing also require an E card to reference the part number to the drawing number. A standard 80 column tabulating card may be used in lieu of the DD Form 1310 card to submit this information to the Government. Card punching and interpreting instructions for DD Form 1310 (E Card) shall be as follows:

CARD COLUMN	FIELD DEFINITION	PRINT LOCATION
1-2	Type of document	Interpret in print position 1-2.
3-17	Part number	Interpret in print position 4-18.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

18-22	Code identification	Interpret in print position 54-58.
23-37	Drawing number	Interpret in print position 23-37.
38-48	Open	This field shall remain blank.
49	Beginning or end code	Interpret in print position 51.
50	Distribution statement code	Interpret in print position 52.
51	Card code	The letter "E" shall be punched in this field on all cards. Do not interpret this field.
52	Security classification	Interpret in print position 60.
53-80	Open	This field shall remain blank.

3.4 Inspection.

3.4.1 Inspection of microfilm. All microfilm shall be inspected according to MIL-M-9868. Failure of the microfilm to meet the specified requirement may constitute cause for rejection by the Government of the entire submittal.

3.4.2 Inspection of tabulating and aperture cards. Inspection of all tabulating and aperture cards shall be in accordance with MIL-M-38761. Failure of cards to meet any specified requirement may constitute cause for rejection by the government of the entire submittal.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

5. PACKAGING

5.1 Packaging requirements. The preparation, packaging and marking for delivery of microfilm shall be in accordance with MIL-M-9868 and tabulating cards in accordance with MIL-M-38761.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The microfilm image cards and tabulating cards covered by this specification are intended for use in engineering drawing repositories and for the reprocurement of spare parts.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

6.3 Data requirements. The appropriate Data Item Description listed in 6.3 of MIL-T-31000 must be listed on the Contract Data Requirements List (DD Form 1423) when this specification is applied on a contract in order to have the data delivered in the proper medium. The exception to this requirement is when the DOD FAR Supplement 227.405-70 exempts the requirement for a DD Form 1423 in the contract. The DID's cited in MIL-T-31000 were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 Subject term (key word) listing.

Card size
Card stock
Classification
Contract
Control activity
Deck
Design activity
Distribution statement
Document
Frame
Index
Legend
Negative
Overlay
Purchase order
Reduction ratio
References
Repositories
Rights
Sheet

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.

Silver halide
Source data

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing Activity:
Navy - AS

Project EDRS-0171

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:24Z
Check the source to verify that this is the current version before use.