MIL-S-0038725B(84)
14 January 1989
USED IN LIEU OF
MIL-S-38725A
3 FEBRUARY 1967

MILITARY SPECIFICATION

SCRUBBING MACHINE, SELF-PROPELLED

HEAVY DUTY, CYLINDRICAL BRUSH

OPPOSED DIRECTION TYPE

"This military specification has been prepared by WR-ALC/MMRVG based upon currently available technical information but it has not been approved for promulgation as a coordinated revision of MIL-S-38725A. It is subject to modification. However, pending its promulgation as a coordinated military specification, it may be used in acquisition."

1. SCOPE.

1.1 Scope. This specification covers a self-propelled, diesel engine drive, hydraulically operated, opposed direction cylindrical brush scrubbing machine equipped with a positive type vacuum squeegee pickup system.

2. APPLICABLE DOCUMENT.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-E-489	Enamel, Alkyd, Gloss (For Exterior and Interior Surfaces).
VV-F-800	Fuel Oil, Diesel.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMVRG, Robins AFB GA 31098-5609 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426 appearing at the end of this document of by letter.

AMSC N/A FSC 3825

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-514	Plates, Identification, Instruction and Marking, Blank.
MIL-T-5624	Turbine Fuel, Aviation, Grades JP-4 and JP-5.
MIL-P-15024	Plate, Tags and Bands for Identification of Equipment.
MIL-D-23003	Deck Covering Compound, Nonslip, Rollable.
DOD-G-24508	Grease, High Performance, Multi-Purpose. (Metric)
MIL-T-83113	Turbine Fuel, Aviation, Kerosene Type, Grade JP-8.
MIL-H-83282	Hydraulic Fluid, Fire Resistant, Synthetic, Hydrocarbon Base, Aircraft, NATO Code Number H-537.
MIL-C-83286	Coating, Urethane, Aliphatic, Isocyanate, for Aerospace Applications.

STANDARDS

FEDERAL

FED-STD-595	Colors.

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-209	Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-461	electromagnetic Emission and Susceptibility requirements for the Control of Electromagnetic Interference.
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities.

(Copies of specifications, standards and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 2240 - Rubber Property - Durometer Hardness

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:20Z
Check the source to verify that this is the currenversion before use.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., ATA Traffic Department, 1616 "P" Street, NW, Washington, DC 20036).

UNDERWRITERS LABORATORY, (UL), INC.

Standard Number 558 - Industrial Trucks, Internal Combustion Engine Powered.

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611).

SOCIETY OF AUTOMOTIVE ENGINEERS

SAE J1056 - Service Performance Requirements for Vehicular Hazard Warning flashers.

(Application for copies of the above listed documents should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract (see 6.2), a sample unit shall be subjected to first article inspection, and testing (see 4.3) to determine compliance with this document. The scrubbers furnished on the balance of the contract shall be identical to the scrubber tested.

3.2 General.

3.2.1 Code and standards. The contractor shall submit to the contracting agency a certificate of compliance in accordance with the data ordering document included in the contract, that the acquisitioned item conforms to the requirements of UL 558 and this specification. Acquisitioned item shall conspicuously display the UL label.

3.2.2 Compliance. Compliance with UL requirements regarding fire and safety hazards does not absolve the contractor from complete compliance with the additional requirements of this specification. In the event of any conflict between any of the requirements of the specification and those of UL, the requirements of this specification shall govern.

3.3 Materials. Materials shall be as specified herein. Materials not definitely specified may be the manufacturer's normal commercial product, but shall meet the test requirements in Section 4. They shall be of the type best suited for the purpose intended. Materials shall be free of defects and imperfections that will affect the reliability of the product. All equip-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

ment, material, and articles incorporated in the products covered by this specification shall be new.

3.3.1 Asbestos. Material used in the construction of the scrubbing machine and accessories shall be asbestos free. A certification of compliance shall be required in accordance with the data ordering document included in the contract.

3.4 Design and construction. The scrubbing machine shall be a self propelled, diesel engine powered, hydraulically driven unit with suitable controls. It shall be the manufacturer's standard commercial product, which meets or exceeds the requirements of this specification, and shall be warranted by the manufacturer. It shall consist of tank to dispense the cleaning solution, a tank to store the recovered cleaning solution, a vacuum squeegee pickup system, a set of rotating cylindrical brushes, vacuumized debris hopper, and a drivers compartment. Handles, levers, pedals, knobs and drivers compartment seating arrangements and dimensions shall enhance effective scrubber operation as specified in MIL-STD-1472. The scrubbing machine shall operate at 0 to 8 miles per hour. The scrubbing machine shall have a minimum rated scrubbing capacity of 50,000 square feet per hour when tested in accordance with 4.5. Scrubbing machines shall be provided with dual caliper brakes in order to remain stable and retain traction while operating on ramped surfaces. The scrubbing machine shall negotiate a 10° ramp which has at least an 8 to 10-inch sill. Resistance to corrosion, wear, damage and misalignment shall be inherent in the design.

3.4.1 Component parts. Component parts and assemblies of the scrubbing machine from any manufacturer shall be fully interchangeable. Such interchangeability shall not require any alterations or modifications.

3.4.2 Engine and transmission. The engine shall be a liquid-cooled diesel model with horsepower; torque, and speed characteristics that meet the performance requirements without exceeding 80 percent of the engine rated speed. The engine shall be capable of operation in any ambient temperature from -20°F to 120°F. The engine shall demonstrate the performance characteristics specified herein when using diesel fuel in accordance with VV-F-800 and shall operate satisfactorily on Grades JP-4 and JP-5 turbine fuel in accordance with MIL-T-5624, and Grade JP-8 in accordance with MIL-T-83133. A dry type air cleaner certified by the engine manufacturer for the application shall be furnished. The engine shall be equipped with a spark and fume arresting exhaust system. An engine cover shall be installed and properly sealed to prevent water leakage to the engine compartment. The cover shall allow for engine servicing without complete removal. Transmission shall enhance the braking capability of the scrubber. The input torque capacity of the transmission shall be at least equal to the maximum torque output of the engine.

3.4.3 Instruments and controls. Instruments and controls shall be of manufacturer's standard industrial quality. Gages to identify critical ranges of ail pressure, water temperature, fuel level, and amperage shall be provided. An indicator light shall be provided to warn of excessive brush pressure. Instruments, switches and gages shall be protected by fuses. An engine hourmeter shall also be furnished. Control levers for brush and squeegee operations and the master speed control devices shall be fabricated of compatible steel. Automotive type, driver controlled foot pedals shall be provided for

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:20Z
Check the source to verify that this is the current version before use.

braking and forward and reverse drive operations and shall withstand constant driver use. The foot pedals shall not interfere with hoses, fittings, and control cables during activation.

3.4.4 Tires and wheels. The scrubbing machine shall be equipped with heavy duty wheels which shall take the static, and dynamic imposed loadings and motions. The tires shall be high traction tubeless type. They shall be at least 8 X 14.00 6-ply rated tubeless and all tires shall be the same size.

3.4.5 Electrical system. The scrubbing machine shall be equipped with a 12-volt negative ground electrical system including a starting system, battery charging generator or alternator of not less than 30-ampere rating, regulator, and ammeter.

3.4.6 Hydraulic system. The hydraulic system shall include the necessary pumps, valves, piping, cylinders, filters, and pressure controls. The hydraulic system shall be sized to provide the necessary power to the scrubbing machine drive mechanism, the scrub brushes, the power steering, and the squeegee circuits. A means of determining the fluid level in the reservoir shall be provided. Relief valves for the protection of the system shall be furnished. The relief valve discharge shall be contained within the system.

3.4.7 Brake system.

3.4.7.1 Service brakes. The scrubbing machine shall be equipped with hydraulic service brakes. The service brakes may be either on the front wheels, on the rear wheels, or on all wheels. The service brakes shall be actuated by a foot pedal located in the drivers compartment. The service brakes shall safely stop the scrubbing machine, with a full tank of cleaning solution, from 5 mph within 7 feet, when traveling forward down a 10° dry, paved ramp.

3.4.7.2 Parking brakes. The scrubbing machines shall be equipped with a hand lever actuated parking brake. The parking brake control shall be provided with a positive lock and shall be either independent of the service brakes or connected to the service brake shoes through a separate mechanical means. The parking brake shall be capable of holding the scrubbing machine, with a full tank of cleaning solution, on a 10°, dry, paved ramp, while heading either up or down the ramp, without evidence of slippage.

3.4.8 Power steering system. The scrubbing machine shall be equipped with hydraulic power steering. Steering hydraulic system shall incorporate a priority hydraulic distribution valve to assure safe, smooth and continuous operation.

3.4.9 Scrubbing head. The scrubbing machine shall be furnished with a scrubbing head housing the scrubbing brushes and a vacuumized debris hopper. The scrubbing head shall be of sheet metal construction.

3.4.9.1 Scrubbing brushes. The scrubbing head shall accommodate a set of scrubbing brushes. They shall be polypropylene and of a cylindrical shape. They shall provide a clean scrubbing swath of 80 to 100 square inches. The scrubbing head shall be so constructed that the scrubbing brushes create a waterlift into the debris hopper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

3.4.9.2 Debris hopper. The scrubbing head shall include a vacuumized debris hopper. The hopper ;shall receive, hold, transport, and dump small items of surface debris. The hopper shall have a capacity of no less than 2 cubic feet. It shall be connected to the recovery tank by means of a vacuum line. The hopper shall be constructed of stainless steel.

3.4.10 Squeegee assembly. A hydraulically operated squeegee system shall be provided. An automatic lift device shall be incorporated into the assembly. It shall automatically lift the squeegee assembly when the transmission is shifted into reverse.

3.4.10.1 Squeegee. A squeegee constructed of gum rubber, neoprene or other similar material shall be provided and shall be mounted behind the scrubbing head and vacuum pickup. The squeegee shall have a hardness of 35-50 when tested in accordance with 4.5.3. The squeegee shall be positioned so that it is as long as the scrub swath. The squeegee shall have no residue while the scrubbing machine is turning at its shortest turning radius. The squeegee shall be easily removable without multiple nuts, bolts and screws. The squeegee blade must be constructed in such a manner that all edges may be used.

3.4.11 Vacuum pickup system. The scrubbing machine shall be equipped with a high-speed vacuum fan to collect the dirty water or sludge developed during the scrubbing cycle and deposit it in the dirty water pickup tank. Vacuum shall be measured at operating revolutions per minute (r/min) with an airflow of at least 300 cubic feet per minute and with a minimum 40-inch water lift when measured in accordance with 4.5.4.

3.4.12 Solution and recovery tanks. Separate tanks shall be provided for the cleaning solution and for the recovered solution. The tanks shall be stainless steel. Easy access cleanout and hose discharge shall be provided to allow for complete drainage. Cleanout doors shall be provided and shall be of a size to permit the removal of sludge from the tank. The solution tank shall have a capacity of not less than 120 gallons and the recovery tank shall have a capacity of not less than 140 gallons. Solution tank fill opening shall be of a size to allow for pouring of cleaning agent. Opening shall have a cover secured with a latching device.

3.5 Attachments.

3.5.1 Squeegee wand. The squeegee wand shall connect to the vacuum line in the scrubber and provide a means of picking up liquid in areas inaccessible to the scrubbing machine.

3.5.2 Lifting and tying down points. The scrubbing machine shall be equipped with lifting and tying down attachments conforming to MIL-STD-209, Type II, except that the manufacturer's recommended method of lifting shall take precedence over MIL-STD-209. The lifting and tie-down attachments shall be indicated on a permanently installed aluminum plate of .063 to .090 inch thickness. The plate shall show the manufacturer's recommended method of lifting the machine.

3.5.3 Light kit. The scrubbing machine shall be equipped with headlights, taillights, brake lights, turn signals, and 360-degree amber warning flasher

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

in array to provide illumination for safe operations at night.

3.6 Size and capacities. Sizes and capacities of scrubbing machine shall conform to the requirements shown below:

Width overall, inches	55-75 inches
Length overall, inches	100-160 inches
Height overall, inches	55-72 inches
Floor clearances, minimum	3-12 inches
Weight in pounds (tanks empty) (minimum)	5000-6000 pounds

3.7 Painting. Unless otherwise specified, the outer surface of the scrubbing machine shall be treated and painted in accordance with the manufacturer's standard commercial practice except that the color of the finish coat shall be Forest Green, Color Number 24052 of FED-STD-595. When specified (see 6.2), the exterior surface of the scrubbing machine and the interior surfaces of all compartments (except the debris hopper, solution tank and recovery tank) shall be coated with paint in accordance with MIL-C-83286 or with a commercial polyurethane paint which meets the following requirements of MIL-C-83286:

(1) Paragraph 3.7.3.4 Low temperature resistance.

(2) Paragraph 3.7.3.6.1 Accelerated weathering.

(3) Paragraph 3.7.3.7 Resistance to taping.

In addition, the paint shall have a minimum hardness of 6H when tested in accordance with paragraph 4.8.12 of MIL-C-83286. The paint color shall be as described above. In either case, all exterior trim items shall be painted with the same paint as the exterior of the vehicle.

3.8 Finish. Exterior surfaces shall be smooth and free from surface defects or obstructions which may contribute to corrosion.

3.9 Lubrication. Parts requiring lubrication shall be lubricated upon assembly and shall be so mounted that they may be lubricated through normal maintenance procedures. Machines shall be ready to operate on delivery with no additional lubrication.

3.9.1 Lubricating oil filters. The engine lubricating oil system shall include a standard type filter mounted in an accessible location for replacement of the element. The element size shall be that recommended by the filter manufacturer for the particular engine so as to achieve maximum filtration efficiency.

3.10 Identification marking. Each scrubbing machine shall have a permanently installed corrosion resistant name plate marked in accordance with MIL-STD-130. The plate shall contain the Manufacturer's Name, Contract Number, Model Number, Serial Number, National Stock Number, Date Shipped, Air Force Regist-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

ration Number, and Engine Number.

3.11 Electromagnetic interference requirements. The scrubber shall meet the electromagnetic interference (EMI) requirements of MIL-STD-461B, part 8, Class C1 with the following exceptions:

a. The limits of UM03 (figure 8-1) shall be relaxed by 20 db.

b. Only the bandwidths listed below shall be used in the appropriate frequency band of the measurement receiver for UM03 testing.

TUNED FREQUENCY	BANDWIDTH	TYPE BW
10KHZ - 1MHz	1 KHZ±10%	Impulse
1 MHz - 30 MHz	10 KHZ±10%	Impulse
30 MHz - 1 GHz	100 KHZ±10%	Impulse

3.12 Reliability. The vehicle and all components thereof shall be constructed in accordance with all codes and standards and local laws and regulations applicable to the design and construction of this type of equipment, which are generally accepted and used as good practice throughout the industry, i.e., NFPA, Underwriters, OSHA standards, SAE publications, Military standards, etc. The designing of all parts and sub-assemblies shall be in accordance with good commercial practice. It is the responsibility of the manufacturer to ensure safe, efficient, and practical design in keeping with the requirements peculiar to this type of vehicle.

3.13 Maintainability. The vehicle shall be designed and constructed to provide:

a. A minimum number of parts consistent with the performance required herein.

b. Parts and components that are located or positioned for ease of inspection for and recognition of excessive wear or potential failure.

c. Ease of adjusting, servicing and replacing parts and components requiring such.

d. Use of readily available standard tools and equipment for maintenance.

e. Maintenance with a minimum number of tools.

3.14 Workmanship. The scrubbing machines and attachments shall be constructed assembled, and finished to assure good quality equipment of a neat general appearance and be free from imperfections which may affect durability, operability, and serviceability.

4. Quality assurance provisions.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

'4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in the specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.'

4.2 Classification of inspection. Inspections shall be as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Packaging inspection (see 4.6).

4.3 First article inspection. The first article (see 3.1), shall be examined for defects listed in table I and tested in accordance with 4.5. Testing shall be conducted at the manufacturer's facilities. The presence of any visual defects, dimensions not as specified of failure to pass any test shall be cause for rejection of the first article. Acceptance of the first article and the approval of the First Article Test Report shall not constitute a waiver by the Government of its rights under the provisions of the contract, and shall not relieve the contractor from meeting all requirements of this military specification.

TABLE 1 - CLASSIFICATION OF DEFECTS

EXAMINE	DEFECT	CLASSIFICATION Major	Minor
Finish	Not finished where required.	X	
	Type of finish not as specified or blistered, peeled, chipped or area of no film or thin film.	X	
	Any component or assembly that is painted or otherwise coated where serviceability may be affected.		X
	Any area of rust.		
Dimensions	not in accordance with the specified requirements.	X	
Construction and workmanship	Part missing or not specified type or size (except as otherwise indicated herein).	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

TABLE 1 continued

EXAMINE	TABLE I - CLASSIFICATION OF DEFECTS DEFECT	CLASSIFICATION Major	Minor
	Fractured, split, punctured, torn, dented, creased, deteriorated, bowed, sprung, malformed, decayed or otherwise impaired.	X	
	Defective or otherwise damaged but not affecting serviceability.		X
	Misplaced, loose, or not in proper alignment.	X	
	Sharp burr, silver, or splinter that may be injurious to personnel.	X	
	Component not readily accessible for servicing where required.		X
Welding or brazing (where applicable)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused.	X	
	Slag inclusion, undercut, not smooth and uniform, scale or flux deposits not removed.		X
Soldering (where applicable)	Missing, not adherent or incomplete,	X	
	Not clean (flux or flux residue not removed), not smooth (surface not finished neatly), or pin holes in solder.	X	
Bolts, nuts, screws, studs and other types of fasteners	Missing, broken, stripped, fractured or loose.	X	
Assembly	Any component not properly assembled or secured.	X	
Marking identification, instruction manual wiring diagrams (where applicable).	Missing, incomplete, not legible, not as specified	X	

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item being offered for acceptance under the contract. Failure of the cleaner to pass the examination or one more tests shall be cause for rejection. Quality conformance inspection shall consist of the following:

a. Examination (see 4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

b. Tests (see 4.4.2).

4.4.1 Examination. Each complete cleaner, including the preproduction sample shall be examined for compliance with the requirements specified in Section 3 of this military specification. Any redesign of modification of the suppliers standard product to comply with special requirements, shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Non-compliance with any specified requirement or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4.2 Operational test. Cleaners produced in fulfillment of the contract or order shall be completely assembled, adjusted, lubricated and otherwise serviced for operation. During this operational test all controls, adjusting mechanisms, brakes, hydraulic systems and other accessories shall be operated sufficiently to insure against restrictions or malfunctions. Failure to pass any phase of this test shall be cause for rejection. The manufacturer's quality assurance list should be reviewed and approved by WR-ALC Engineer or Equipment Specialist.

4.5 First article test.

4.5.1 Test surface. The test surface shall be either a metal surface or an area of broomed or rough finished concrete measuring 13 feet wide by 100 feet long. The following items shall be distributed over the entire test area:

a. One pound of ball bearing grease conforming to DOD-GO-24508.

b. Two gallons of hydraulic fluid conforming to HIL-H-83282.

c. Twenty machine screws, 1/4 inch diameter by 2 inches long.

d. Twenty hexagon nuts, 1/2 inch size.

e. Twenty steel washers, 1 1/2 inch diameter by 1/8 inch thick.

4.5.2 Operation. The scrubbing machine shall be equipped with the necessary brushes and squeegees set at the proper machine to ground clearances. It shall scrub the entire test surface in a period of not more than 3 minutes. Scrubbing paths shall include a 4-inch overlap. At the conclusion of the test, the test surface shall have no visual evidence of foreign matter deposits. Additionally, there shall be no evidence of cleaning solution deposits. Additionally, there shall be no evidence of cleaning solution residue on the testing surface. After the operational tests, the scrubbing machine shall be observed and examined for the following:

a. Overheating.

b. Leakage of lubrication.

c. Uniformity, continuity, and size of scrubbing area.

4.5.3 Squeegee hardness test. Squeegee hardness shall be tested in accordance with ASTM D 2240.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:20Z
Check the source to verify that this is the current version before use.

4.5.4 Vacuum test. Vacuum pressure at the rear squeegee assembly shall be measured by inserting a manometer into the vacuum line. The measurement shall be made at the completion of the operational test with the scrubbing machine idling at the operating rpm.

4.5.5 Light kit and warning flasher test. The light package and 360-degree warning flasher shall be in accordance with SAE J1056.

4.5.6 Electromagnetic interference test. The scrubbing machine shall be tested to prove that it meets the requirement of paragraph 3.12.

4.5.7 Service brake test. The service brakes shall be tested to verify that they meet the requirement 3.4.7.1.

4.5.8 Parking break test. The parking brake shall be tested to verify that it meets the requirement of 3.4.7.2. The scrubbing machine remain on the ramp for 15 minutes without slippage.

4.6 Inspection of packaging. An examination shall be made to determine that packaging requirements specified in section 5 of this specification are met.

5. Packaging. Preservation, packaging, packing and marking shall be in accordance with the terms of this contract see 6.2).

6. NOTES

6.1 Intended use. Scrubbers covered by this specification will be used primary for maintenance cleaning of aircraft ramps, parking areas and hangar areas where oil and grease drippings, fuel spillage and dirt accumulate.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. If a first article is required (see 3.1).

c. Type of painting required (see 3.7).

d. Type of preservation, packaging, packing and marking required (see 5.0).

6.3 Subject term (key word) listing.

Cylindrical Brush
Heavy Duty
Scrubbing Machine
Self-Propelled

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 84
Project Number:
3825-F193

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:20Z
Check the source to verify that this is the current version before use.