INCH-POUND

MIL-DTL-55302/99D
17 November 2004
SUPERSEDING
MIL-C-55302/99C(CR)
4 April 1983

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, STRAIGHT THROUGH, HERMAPHRODITIC CONTACT, WRAPPOST REMOVABLE, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

MIL-DTL-55302/99D is inactive for new design after 24 October 1991.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




FIGURE 1. Connector, receptacle (.100 inch spacing).


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:49Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.005	0.13	.150	3.81
.007	0.18	.156	3.96
.008	0.20	.197	5.00
.010	0.25	.246	6.25
.015	0.38	.273	6.93
.025	0.64	.294	7.47
.050	1.27	.312	7.92
.055	1.40	.477	12.12
.062	1.57	.550	13.97
.086	2.18	.560	14.22
.100	2.54		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .010 (0.25 mm).
4. With connectors fully engaged the mating contacts shall have a minimum overlap distance of .062. As a minimum the contacts shall exhibit a wiping action through this distance.

FIGURE 1. Connector, receptacle (.100 inch spacing) – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:49Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 2. Typical cutout for receptacle in nonconductive chassis.

TABLE I. Dash number and dimensions.

Dash number 1/	Number of contacts	Dimensions 2/				
		A	B ±.010	C Ref	D	E
01	18	.850 (21.59)	1.150 (29.21)	1.300 (33.02)	1.006 (25.55)	1.150 (29.21)
02	30	1.450 (36.83)	1.750 (44.45)	1.900 (48.26)	1.606 (40.79)	1.750 (44.45)
03	36	1.750 (44.45)	2.050 (52.07)	2.200 (55.88)	1.906 (48.41)	2.050 (52.07)
04	42	2.050 (52.07)	2.350 (59.69)	2.500 (63.50)	2.206 (56.03)	2.350 (59.69)
05	54	2.650 (67.31)	2.950 (74.93)	3.100 (78.74)	2.806 (71.27)	2.950 (74.93)
06	72	3.550 (90.17)	3.850 (97.79)	4.000 (101.60)	3.706 (94.13)	3.850 (97.79)

1/ See requirements for complete Part or Identifying Number (PIN) when keying pin is required.
2/ Dimensions are in inches. Metrics are in parentheses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configurations: See figures 1 and 2, and table I.

Material and finish:

Insulator: ASTM D5948, type SDG-F.

End guides: Left hand, sintered brass 90/10, clear chromate in accordance with MIL-C-5541, class 1A.

Mounting screw: Brass, cadmium plated, gold chromate finish.

Flat washer: Stainless steel.

Contact identification: Contact locations are identified in numerical sequence (see figure 1).

Mating and unmating: The maximum insertion force, in pounds, shall not exceed a value equal to .5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of .11 times the number of contacts and shall not exceed the measured insertion force.

Contact retention: 6.0 pounds minimum after five insertions and withdrawals from the same connector position.

Contact resistance: The contact resistance shall not exceed 20 milliohms.

Dry circuit: Connectors shall be tested in accordance with procedure EIA-364-23. The contact resistance shall not exceed 20 milliohms.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 60 Hz.
High altitude: 300 volts rms, 60Hz.

Current rating, maximum: 5 amperes.

Keying: When required, one of the following codes shall be added to the number:

P – Specifying location by contact number where keying pin shall be inserted; for example, M55302/99-01P17. (Keying pin inserted in place of contact number 17.)

H - Specifying location by contact number where contact shall be omitted for mating; for example, M55302/99-01H17. (Keying pin hole has contact number 17 omitted.)

Contacts: Shall conform to MIL-DTL-55302/98.

Contact removal tool: Shall conform to MIL-I-81969/4.

Contact insertion tool: Shall conform to MIL-I-81969/5.

Mating plug: Shall conform to MIL-DTL-55302/53 and MIL-DTL-55302/54.

Contact wrappost tool: Shall conform to MIL-DTL-55302/98.

PIN: M55302/99-(dash number from table I).

Group submission: MIL-DTL-55302/90, MIL-DTL-55302/92, and MIL-DTL-55302/94.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:49Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/53	MIL-C-5541
MIL-DTL-55302/54	MIL-I-81969/4
MIL-DTL-55302/90	MIL-I-81969/5
MIL-DTL-55302/92	ASTM D5948
MIL-DTL-55302/94	EIA-364-23
MIL-DTL-55302/98	

Previous changes. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army – CR
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-4440-018)

Review activities:
Army – AR, AT, AV, CR4, MI

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:49Z
Check the source to verify that this is the current version before use.