MIL-E-60581A(MU)
AMENDMENT 1
12 September 1973

MILITARY SPECIFICATION

EJECTOR, PARACHUTE, CARTRIDGE ACTUATED
M233, METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-E-60581A(MU) dated 24 September 1971.

Change model number "XM233" wherever it appears to "M233".

Para. 2.1, under "Drawings" add, "C9238920, Carton, Alternative Packing, Ammunition for Ejector Parachute."

Para. 3.4.2, delete "14,000 to 15,000 pounds psi for 15 seconds" and substitute "14,000 to 15,000 psi, minimum, for 15 seconds".

Para. 3.5, delete ".370 inches minimum and .425 pounds maximum" and substitute ".370 inches minimum and .425 inches maximum".

Para. 4.3.2.1, delete Drawing "F10536011" and substitute "C10536017".

Para. 4.3.2.5, delete Major defects 112, 113, 114, 115, 116, and 117 in their entirety and substitute:

"112.	Undercut diameter at bottom of large thread cavity	Gage
113.	Diameter of flare angle on small thread	Gage
114.	Length of flare angle small thread end	Gage
115.	Diameter of flare angle on medium threads (2 places)	Gage
116.	Length of large thread undercut	Gage
117.	Diameter of thread lead on medium threads (2 places)	Gage".

Para. 4.3.2.5, delete Minor defects 203, 204, 205, and 206 in their entirety and substitute:

"203.	Location of medium thread holes (2 places)	Gage
204.	Depth of small internal hole	Gage
205.	Length of small threads	Gage
206.	Length of medium thread lead (2 places)	Gage".

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

Para. 4.3.2.6, delete Major defects 106 and 108 in their entirety and substitute:

"106.	Length of internal thread cavity	Gage
108.	Length of small diameter cavity	Gage"

Para. 4.3.2.6, add the following Major defects:

"116.	Parallelism of bottom of thread cavity to external seating surface	Gage
117.	Diameter, internal thread undercut	Gage
118.	Radius of hex. corners	Gage"

Para. 4.3.2.6, delete Minor defect 208 in its entirety. Delete minor defects 205, 206, 209, 210 and 218 in their entirety and substitute:

"205.	Length of counterbore	Gage
206.	Diameter of flare angle, large end	Gage
209.	Diameter, internal thread undercut	Gage
210.	Length from small end to external thread, shoulder	Gage
218.	Length of internal thread undercut	Gage"

Para. 4.3.2.7, delete Major defect 112 in its entirety and substitute:

"112.	Width at threaded end	Gage".

Para. 4.3.2.8, delete Drawing "D10520407" and substitute "D11731644".

Para. 4.3.2.18, delete Major defect 107 in its entirety and substitute:

"107.	Tag missing, incorrect, or illegible	Visual".

Para. 4.3.2.18, delete Minor defect 201 in its entirety.

Add para. 4.3.2.2.2:

"4.3.2.22 Carton, Alternative Packing, Drawing C9238920

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

MINOR

201.	Contents loose	Manual
202.	Carton broken or damaged	Visual
203.	Number of units contained incorrect	Visual
204.	Marking missing, incorrect or illegible	Visual
205.	Tape incomplete	Visual".

Para. 5.1, delete in its entirety and substitute:

"5.1 Packing and marking.-Packing and marking shall be as specified by the procuring agency. Level A-Drawings C9215469 and C9215470. Level B-Drawings C9215469 and C9238920."

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A560

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.