MIL-M-55336 (EL)
Amendment 2
26 November 1974
SUPERSEDING
Amendment 1
28 March 1972

MILITARY SPECIFICATION

MAINTENANCE ACCESSORY KIT, MK-1192( )/ARM
(UNITS OF)

This amendment forms a part of military specification MIL-M-55336 (EL), 3 September 1971 and is approved for use by all Departments and Agencies of the Department of Defense

Page 2

2.1 under SPECIFICATION, MILITARY Delete "MIL-T-5422 Testing, Environmental Aircraft Electronic Equipment".

Page 6

3.12.1.1: Delete "+100°F" and substitute "+131°F".

3.12.2 Delete "procedure prescribed in MIL-T-5422" and substitute "Procedure I, Method 507 of MIL-STD-810".

Page 7

3.12.6: Delete and substitute.

"3.12.6 Vibration (See 4.8.6).-The equipment shall meet the vibration requirements of Test Method 514.1-7 (Curve AY) of MIL-STD-810."

3.12.7 Delete and substitute.

"3.12.7 Shock (See 4.8.7)-The equipment shall not suffer damage or fail to operate after subjection to basic design and bench-handling shock tests conducted in accordance with Method 516.1 of MIL-STD-810. Transit Drop Test shall not be performed "

Delete: "Table I" and "Note A" entirely.

FSC-6625

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:03Z
Check the source to verify that this is the currentversion before use.

Page 15

4.5.3: Delete "Subgroup II" of "Table IV" and substitute:

"SUBGROUP II"

Spray Tight Protection	3.12.4	4.8.4
Shock Tests	3.12.7	4.8.7"

Last paragraph, line 1: Delete "4.5.3" and substitute "4.5.4.3".

Page 17

4.8.2. Delete "Specification MIL-T-5422" and substitute "Procedure I, Method 507 of MIL-STD-810".

Page 18

4.8.7 Delete and substitute

"4.8.7 Shock.-The test set shall be subjected to shock tests in accordance with Procedures I and V, Method 516.1 of MIL-STD-810. At the conclusion of the shock tests, without adjustment or repair, the test set shall be inspected and tested for compliance with the electrical tests and inspections specified in 4.8."

4.8.7.1: Delete and substitute

"4.8.7.1 Shock, Basic Design (See 3.12.7).-The test set shall be subjected to shock test in accordance with Procedure I, Method 516.1 of MIL-STD-810. Figure 516.1-2 shall apply using shock parameters (a) & (c)."

4.8.7.2: Delete and substitute

"4.8.7.2 Shock, bench-handling.-The test set shall be subjected to bench-handling shock test conducted in accordance with Procedure V, Steps 1 and 2 of Method 516.1 of MIL-STD-810."

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:03Z
Check the source to verify that this is the current version before use.

Page 24

5.2.1.1 End of last sentence, add "conforming to QQ-S-781, type I, finish A or shrink film".

5.2.1.2 End of last sentence, delete "class B' and substitute "finish A".

Page 26

6.2 Delete in its entirety and substitute "When rough handling test is required".

CUSTODIAN:
ARMY-EL

PREPARING ACTIVITY
ARMY-EL
Project No 6625-A649

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:03Z
Check the source to verify that this is the current version before use.