MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC DIELECTRIC, DC,

IN NONMETAL CASES, ESTABLISHED RELIABILITY

STYLES CFR13 AND CFR14

This amendment forms a part of Military Specification Sheet MIL-C-55514/9, dated 14 January 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, column 3 heading, delete and substitute: "DC rated voltage at 105°C".

PAGE 3

TABLE I, column 3 heading, delete and substitute: "DC rated voltage at 105°C".

PAGE 4

Burn-in, delete and substitute:

"Burn-in: In accordance with MIL-C-55514 except ac capacitors shall be +105°C +0, -5°C, and the applied voltage shall be 140 percent of the dc voltage specified in table I."

Life (at 105°C), Rated condition, delete and substitute:

"Rated Condition: 100 percent of +105°C rated voltage."

DF: .1 percent maximum, delete in its entirety.

ΔCap, delete and substitute:

"ΔCap (at 25°C): Maximum of 1.0 percent."

AC conditioning, delete and substitute:

"AC conditioning: In accordance with MIL-C-55514. AC conditioning for qualification shall be at the rated ac ripple current at 85°C and 40 kHz. For group B testing, rated ac ripple current at 85°C and 40 kHz shall be run on test samples in accordance with table II herein at 12-month intervals."

TABLE II. AC conditioning test samples.

DC rated voltage (volts)	Sample size	Cap range for selection of sample 1/ (μF)
100	24	1.0 to 30.0
200	24	1.0 to 20.0
400	24	1.0 to 10.0

1/ Each test sample shall contain at least one capacitor of the highest and lowest capacitance value of each voltage group manufactured during the 12-month period.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Navy - OS
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5910-1446-2)

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:29Z
Check the source to verify that this is the current version before use.