INCH-POUND

A-A-54888
2 July 1993

COMMERCIAL ITEM DESCRIPTION

STOPPER, BOTTLE, CORK

The General Services Administration has authorized the use of this Commercial Item Description as replacement for Federal Specification LLL-S-731B, which is cancelled.

This Commercial Item Description covers natural cork stoppers of both the cemented and uncemented types.

Salient characteristics:

The stoppers shall be made of natural corkwood.

Classification. The stopper shall be of the following Types and Grades:

Type I - Uncemented. The stopper shall be tapered and made of one piece uncemented cork.

Type II - Cemented. The stopper shall be tapered and firmly cemented in not more than three pieces with an insoluble cement. The cemented joints shall be in a plane parallel to the length of the stopper.

Grades A - This grade consists of smooth cork stoppers with very few pits or cracks prepared from a superior grade of wood.

B - This grade consists of good quality cork stoppers with irregular cavities prepared from a selected grade of wood.

C - This grade consists of low-quality cork stoppers containing gross imperfections.

D - This grade consists of the lowest quality cork stoppers.

AMSC N/A FSC 6640

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Dimensions. Dimensions for cork stoppers shall be as shown below, for stopper number specified. Type I stoppers shall be furnished for stopper numbers 000 through 19. Either Type I or II may be furnished for stopper numbers 20 through 36.

	Dimensions				
		Class 1 Short		Class 2 Regular	
Stopper No.	Top Diameter* Inch	Length Inches	Bottom Diameter Inch	Length Inches	Bottom Diameter* Inch
000	1/4	3/8	11/64	1/2	5/32
00	5/16	3/8	15/64	1/2	7/32
0	3/8	3/8	19/64	1/2	9/32
1	7/16	1/2	11/32	5/8	21/64
2	1/2	1/2	13/32	11/16	3/8
3	9/16	1/2	15/32	3/4	27/64
4	5/8	1/2	17/32	13/16	15/32
5	11/16	5/8	9/16	7/8	17/32
6	3/4	5/8	5/8	15/16	37/64
7	13/16	3/4	43/64	1	5/8
8	7/8	3/4	47/64	1-1/16	43/64
9	15/16	3/4	51/64	1-1/8	47/64
10	1	1	13/16	1-1/4	49/64
11	1-1/16	1	7/8	1-1/4	53/64
12	1-1/8	1	15/16	1-1/4	57/64
13	1-3/16	1	1	1-1/4	61/64
14	1-1/4	1	1-1/16	1-1/4	1-1/64
15	1-5/16	1	1-1/8	1-1/4	1-5/64
16	1-3/8	1	1-3/16	1-1/2	1-3/32
17	1-7/16	1	1-1/4	1-1/2	1-5/32
18	1-1/2	1	1-5/16	1-1/2	1-7/32
19	1-9/16	1	1-3/8	1-1/2	1-9/32
20	1-5/8	1	1-7/16	1-1/2	1-11/32
21	1-11/16	1	1-1/2	1-1/2	1-13/32
22	1-3/4	1	1-9/16	1-1/2	1-15/32
23	1-13/16	1	1-5/8	1-1/2	1-17/32
24	1-7/8	1	1-11/16	1-1/2	1-19/32
25	1-15/16	1	1-3/4	1-1/2	1-21/32
26	2	1	1-13/16	1-1/2	1-23/32
27	2-1/16	1	1-7/8	1-1/2	1-25/32
28	2-1/8	1	1-15/16	1-1/2	1-27/32
29	2-3/16	1	2	1-1/2	1-29/32
30	2-1/4	1	2-1/16	1-1/2	1-31/32
32	2-3/8	1	2-3/16	1-1/2	2-3/32
34	2-1/2	1	2-5/16	1-1/2	2-7/32
36	2-5/8	1	2-7/16	1-1/2	2-11/32

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Dimensions (Cont'd)

Stopper No.	Top Diameter Inch	Class 3 Extra Long Length Inches	Class 3 Extra Long Bottom Diameter Inch	Class 4 Extra Long Length Inches	Class 4 Extra Long Bottom Diameter* Inch
000	1/4	5/8	1/8	3/4	7/64
00	5/16	5/8	3/16	3/4	11/64
0	3/8	5/8	17/64	3/4	15/64
1	7/16	3/4	19/64	7/8	17/64
2	1/2	13/16	11/32	15/16	21/64
3	9/16	7/8	25/64	1	3/8
4	5/8	15/16	29/64	1-1/16	27/64
5	11/16	1	1/2	11/8	31-64
6	3/4	1-1/16	35/64	1-1/4	33/64
7	13/16	1-1/8	39/64	1-3/8	35/64
8	7/8	1-1/4	41/64	1-1/2	19/32
9	15/16	1-1/4	45/64	1-1/2	21/32
10	1	1-1/2	23/32		
11	1-1/16	1-1/2	25/32		
12	1-1/8	1-1/2	27/32		
13	1-3/16	1-1/2	29/32		
14	1-1/4	1-1/2	31/32		
15	1-5/16	1-1/2	1-1/32		

* Tolerance of ± 0.03 inch permitted.

Assortment. Unless otherwise specified, an assortment of stoppers shall consist of 20 each of stoppers numbers 1, 2, 3, 4, 5, 6, 7, 8, 10, 12, 13, 14, 16, 18 and 20, all contained in one bag or carton.

Workmanship. The stoppers shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Package (PG). One package containing one hundred stoppers for No. 2, No. 3 and No. 4 or twelve stoppers for No. 12 as specified, constitutes one unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Examination. Examination shall be conducted to determine compliance with specification requirements.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and as specified. Unit of product for examination purposes shall be one package of stoppers as specified. Sampling shall be inspection level II with an Acceptable Quality Level (AQL) of 1.0.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for determination of two or more test characteristics.

Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and as specified. Unit of product for test purposes shall be one package of stoppers. Sampling shall be inspection level S-2 with an AQL of 1.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerance specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements.

Federal Food, Drug, and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

Ordering data. Intermediate/exterior package quantities and labeling and marking must be specified in the contract and/or order.

NOTE 1: The following National Stock Numbers, Item Identifications, Types, Grades, Classes and their respective Stopper Numbers are covered by this document:

NATIONAL STOCK NUMBER	ITEM IDENTIFICATION	SPECIFICATION DESIGNATION TYPE	GRADE	CLASS	STOPPER NO.
6640-00-456-2423	STOPPER, BOTTLE, Cork, Regular Taper, 100s	I	A or B	2	2
6640-00-456-2424	STOPPER, BOTTLE, Cork, Regular Taper, 100s	I	A or B	2	3
6640-00-456-2427	STOPPER, BOTTLE, Cork, Regular Taper, 100s	I	A or B	2	4
6640-00-477-6708	STOPPER, BOTTLE, Cork, Regular Taper, 12s	I	A or B	2	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

Preparing Activity:

DoD-MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
USPHS
FDA-MPQAS
GSA-FSS-FCGC

Project Number: 6640-1828
Location: c:\word\doc\eric\stopper\sg

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

   The submitter of this form must complete blocks 4, 5, 6, and 7.

2. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	A-A-54888	2 July 1993

3. DOCUMENT TITLE

STOPPER, BOTTLE, CORK

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Defense Personnel Support Center ATTN: DPSC-MSE	(1) Commercial (215)7372870	(2) AUTOVON 444-2870
ADDRESS (Include Zip Code) 2800 South 20th Street Philadelphia, PA 19145	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.