MIL-C-10082C(MU)
30 September 1964
SUPERSEDING
MIL-C-10082B(CmlC)
15 December 1959

MILITARY SPECIFICATION

CANISTER, PARTICULATE, M14

1. SCOPE

1.1 This specification covers one type of particulate filter canister.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 - Box, Fiberboard.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

DRAWINGS

EDGEWOOD ARSENAL

DL5-3-876 - Canister, Particulate, M14.
(All drawings referenced in this specification are listed on Drawing DL5-3-876.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting office r.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, ***Rules*** and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-3-876 or on subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3. 1.2 Components. All components of the item shall conform to the specifications and drawings listed on DL5-3-876 and subsidiary drawings.

3.2 Manufacture and assembly. The canister shall be manufactured and assembled as specified on Drawing D5-3-876.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

3.3 Airflow resistance. The airflow resistance of the assembled canister, measured os pressure differential, shall not exceed 65 millimeters of water at a flowrate of 85 liters per minute when tested as specified in 4.6.1.

3.4 Dioctylphthalate (DOP) smoke penetration. The canister shall not show a DOP smoke penetration of more than 0.001 percent at a flowrate of 32 liters per minute when tested as specified in 4.6.2.

3.5 Airflow resistance and DOP penetration after rough harding. After rough handling for five minutes as specified in 4.6.3, the canister shall conform to the requirements specified in 3.3 and 3.4.

3.6 Leakage. The assembled canister shall not leak more than 5 milliliters per minute when subjected to an internal air pressure of 5.5 pounds per square inch gage when tested as specified in 4.6.4.

3.7 Preproduction. When specified in the contract or order, a preproduction sample shall be produced for examination and test. The preproduction sample shall be manufactured using the same materials, methods and equipment as will be used during regular production (see 6.2).

3.8 Workmanship. The canister shall be free from damage (dents, bum, crocks, or deformations) and foreign matter (dirt, grease, oil, or viscous material).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Special provisions.

4.201 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2.3 Substation inspection. If the supplier elects to establish inspection substations for the purpose of conducting inspection for certain listed defects, the Acceptable Quality Levels (AQL's) for each inspection substation shall be equal to the AQL which is the next numerically lower value than the AQL specified for the total listed defects. The requirements of MIL-STD-105 are applicable to each substation and to the end item.

4.3 Lotting. A lot shall consist of the canisters produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of canister elements shall be represented in any one lot of finished canisters.

4.4 Sampling.

4.4.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2 For rough handling. Sampling shall be conducted in accordance with MIL-STD-105, level S-4.

4.5 Inspection provisions.

4.5.1 Examination and nondestructive tests. Sample canisters and the level A preparation for delivery shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.5.2 For rough handling tests. Sample canisters shall be tested in accordance with 4.6.3. The acceptance number is zero.

4.5.3 Critical defects. Each canister shall be inspected for critical characteristics listed in the classification of defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

4.5.4 Classification of defects.

4.5.4.1 Canister, particulate M14 - assembly (Dwg M-3-876).

Categories	Defects	Acceptance standards
Critical:		
1	DOP smoke penetration	4.6.2
2	Leakage	4.6.4
Major:	AQL 1.0 percent defective	
101	Component missing	
102	Component incorrect y assembled	
103	Threads (Table on Dwg D5-3-876) Incorrect	
104	Marking incorrect	
105	workmanship	
Maior A:	AQL 0.25 percent defective	
150	Airflow resistance	4.6.1
Minor:	AQL 2.5 percent defective	
201	Marking illegible	
202	Protective finish missing	

4.5.4.2 Preparation for delivery (sectlon 5).

Categories	Defects
Critical:	None defined
Maior:	AQL 2.5 percent defective
101	Marking incorrect
102	Marking illegible

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

4.6 Tests.

4.6.1 Airflow resistance. The airflow resistance shall be determined using indicator, Resistance, Q112.

4.6.2 DOP smoke penetration. The DOP smoke penetration shall be determined using the Penetrometer, Filter Testing, DOP, Q127.

4.6.3 Rough handling. The canister shall be rough handled for five minutes using Machine, Vibrating, Q110. After rough handling, the canister shall be tested as specified in 4.6.1 and 4.6.2.

4.6.4 Leakage. The canister shall be checked for leakage using a commercial can testing machine and subjecting the canister to the required internal pressure.

5. PREPARATION FOR DELIVERY (For repair parts packaging see 6.4.)

5.1 Packaging. Level shall be as specified (see 6. 2).

5.1.1 Level A. Twelve canisters shall be packaged in a W5c, style RSC, fiber box conforming to PPP-6-636, in one layer of three rows, four per row. Interlocking slotted partitions, having twelve individual cells, shall be fabricated from the same material as the box. Closure of the box shall be by taping in accordance with appendix to the box specification for interior boxes.

5.1.2 Level C. The canisters shall be packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.2 Packing. Level shall be as specified (see 6.2).

5.2.1 Level A. Four boxes of canisters, packaged as specified in 5.1,1, shall be packed in a V3c, style RSC fiber box conforming to PPP-8-636. In addition to box closure requirements, the box seams, corners, and manufacture's joint shall be taped. Tape banding shall be used in lieu of metal banding to reinforce box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

5.2.2 Level C. Canisters, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall comply with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The canister covered by this specification is used for the mechanical filtration of particulate matter from respiratory air.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification,
(b) Level of packaging and packing required.
(c) Whether a preproduction sample is required.

(1) Quantity required.
(2) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(3) Name and address of test facility and shipping instructions when testing is performed by the Government.
(4) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Related documents. The following documents support this canister:

MIL-F-13785 - Filter Material.
MIL-C-12850- Cement, Rubber.
MIL-F-51206 - Filter, Cotton.
MIL-F-51208 - Filter Element and Ring Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.

6.4 Repair parts packaging. When repair parts packaging and packing is required for items authorized for stocking as repair parts, the repair parts packaging data sheet covering the canister should be used. (Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, US Army Edgewood Arsenal, Edgewood Arsenal, Maryland - 21010.)

Custodian:

Army - MU

Preparing activity

Army - MU

Project No. 4240-A197

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:31Z
Check the source to verify that this is the current version before use.