MILITARY SPECIFICATION

HOWITZER, 105MM., T96

The following changes shall be made in Specification MIL-H-10063 (ORD) dated 9 December 1949.

Page 1, Change title to read "Howitzer, 105MM., T96E1."

Page 1, Par. 1.1: In the second line, delete "T96" and substitute "T96E1."

Page 1, Par. 2.1: Delete "Federal Specification TT-E-485 - enamel, etc.". Under Military Specifications add "JAN-P-127 - Packaging and Packing for Overseas Shipment - Tape, Adhesive, Pressure-sensitive, water-resistant." Under U. S. Army Secification, delete "57-206-1 - Welding of etc.," and add "100-2-Standard Specification for Marking Shipment by Contractors."

Page 1 and 2, Par. 2.2: In the fourth line, delete "Department" and substitute "Corps." In the fifth line, delete "52-298-1 - Howitzer, 105MM., T96" and substitute "D7305270 - Howitzer, 105MM., T96E1."

Page 2, Par. 3.8: In the fourth line, insert "Type IV" between "to" and "Specification." Add subparagraphs 3.8.1 and 3.8.2 as follows:

"3.8.1 The cylindrical bearing surfaces of the tube, which slide in the mount, shall be prepared as prescribed for surfaces to be painted and shall be coated with primer only. The coating shall be applied by spraying so as to obtain the minimum thickness necessary to eliminate the sheen of the bare metal."

"3.8.2 Except for the threaded and bearing portions, the cylindrical surface at the muzzle end of the tube, which will be covered by the evacuator, shall be prepared as prescribed for surfaces to be painted and shall be given one coat of "Primer, Paint; Synthetic." The primer shall conform with the requirements of Specification TT-P-636.

Page 4, Par. 5.1.2: Add another sentence as follows: "Mating surfaces of howitzer muzzle, and muzzle brake and evacuator shall be similarly preserved."

Page 4, Par. 5.1.3: Add another sentence as follows: "The primer coated bearing surfaces of the tube (see par. 3.8.1) shall be preserved as specified for unpainted exterior surfaces."

Page 4, Par. 5.2: Delete the paragraph and substitute the following:

"5.2 Packaging - Unless otherwise specified, the howitzer shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:30Z
Check the source to verify that this is the current version before use.

packaged in accordance with Method I of Specification JAN-P-116; the complete breech end and the muzzle end (including muzzle brake and evacuator) shall be wrapped with a single thickness of Grade C, Type I, greaseproof material, meeting the requirements of specification JAN-B-121. The wrapping shall be held in position with water-resistant adhesive tape meeting the requirements of Specification JAN-P-127."

Page 4, Par. 5.4: In the third line, delete "Style 2 or 4" and substitute "Style 2, 2½ or 3." Add the following sentence at the end of this paragraph: "The contents of each box shall be immobilized."

Page 4, Under "CUSTODIAN", delete "Department" and substitute "Corps."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:30Z
Check the source to verify that this is the current version before use.