U. S. AIR FORCE
SPECIFICATION
NOTICE

MIL-E-5272C(ASG)
NOTICE 1
22 January 1971

MILITARY SPECIFICATION

ENVIRONMENTAL TESTING, AERONAUTICAL AND ASSOCIATED EQUIPMENT, GENERAL SPECIFICATION FOR

This notice should be filed in front of MIL-E-5272C(ASG) dated 13 April 1959.

1. MIL-E-5272C(ASG) is hereby made INACTIVE FOR NEW DESIGN and is used by the Air Force only in procurement of replenishment spares as necessary to maintain equipment in the field until obsoletion or wear out.

2. For new design, use MIL-STD-810 Environmental Test Methods.

3. Transition from MIL-E-5272C(ASG) to MIL-STD-810B is as follows:

Test	MIL-E-5272C(ASG) Paragraph	MIL-STD-810B Method
High temperature	4.1	501
Low temperature	4.2	502
Temperature shock	4.3	503
Humidity	4.4	507
Altitude	4.5	500
Salt spray	4.6	509
Vibration	4.7	514
Fungus Resistance	4.8	508
Sunshine	4.9	505
Rain	4.10	506
Dust	4.11	510
Immersion (leakage)	4.12	512
Explosion	4.13	511
Temperature-altitude	4.14	504
Shock	4.15	516
Acceleration	4.16	513

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Custodians:
Air Force - 11
Navy - AS

Preparing activity:
Air Force - 11

Review activities:
Air Force - 10, 12, 13, 70, 80

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:27Z
Check the source to verify that this is the current version before use.