MILITARY SPECIFICATION
ROCKET ENGINE, LIQUID PROPELLANT
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-R-5149B dated 15 November 1966.

Page 1, paragraph 2.1:	Delete "MIL-I-6181, Interference Control Requirements, Aircraft Equipment."
Page 2, paragraph 2.1:	Add "MIL-STD-461, Electromagnetic Interference Characteristics Requirements for Equipment."
Page 6, paragraph 3.1.3.4.2:	In last sentence delete "MIL-D-1000" and substitute "MIL-STD-100".
Page 10, paragraph 3.4.6:	In second sentence delete "MIL-R-27542" and substitute "MIL-STD-785".
Page 13, paragraph 3.5.3:	In last sentence delete "MIL-I-6181" and substitute "MIL-STD-461".
Page 32, paragraph 4.9.1.8:	Delete the word "detrimental" in the last sentence.
Page 39, paragraph 4.9.1.11:	Delete entire paragraph and substitute: "4.9.1.11 Burst pressure. The engine shall be subjected to pressures above proof pressure up to and including burst pressure. The burst pressure shall be specified in the model specification. The burst pressure shall be applied and maintained for a period of not less than three minutes. The pressure shall be applied at appropriate pressure ports to simulate the pressure variations between the various portions of the engine that would exist during engine operation. The method of applying the pressure shall be specified in the model specification. As the pressure is increased, failures that would create a hazardous condition (under actual engine operation) or effect the operation thereof shall be recorded. Permanent set is allowed since subsequent functioning of the engine is not required.

FSC 2845

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:23Z
Check the source to verify that this is the current version before use.

Page 46, paragraph 6.2:	In first sentence delete "American Association" and substitute "United States Association".
Page 49, paragraph 6.3.26:	Change first sentence from ".... total number of duty cycles after Quality Conformance tests ...." to ".... total number of duty cycles including Quality Conformance tests ....".
Page 50, paragraph 6.3.40:	In first sentence delete "U.S. Stand Atmosphere 1962" and substitute "U.S. Standard Atmosphere 1962".
Page 50, paragraph 6.3.45:	Insert the following: "6.3.45 Burst pressure. Burst pressure is the highest pressure to which an engine may be subjected without catastrophic failure. Subsequent operation is not required.
Page 85, paragraph 3.4.6:	Delete "MIL-R-27542" and substitute "MIL-STD-785".

Custodians:

Army - MI
Navy - AS
Air Force - 12

Preparing Activity:

Air Force - 12

Review Activities:

Air Force - 19, 70
Army - MI, MO, MU
Navy - AS

Civilian Agency Interest:

NAS

Project No. 2845-0013

Reviewer/user information is current as of the date of this document. For further coordination of changes to this document, draft circulation should be based on the information in the current DOD Index of Specifications and Standards.

Source: https://assist.dla.mil -- Downloaded: 202610-17T04:23Z
Check the source to verify that this is the current version before use.