MIL-H-2514D
24 January 1977
SUPERSEDING
MIL-H-2514C
21 February 1962

MILITARY SPECIFICATION

HAMMERS, PILEDRIVER, DROP;

1,800 AND 3,000 POUNDS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers drop piledriver hammers.

1.2 Classification. The hammer shall be one of the following sizes:

Size 1 - 1,800 pounds.
Size 2 - 3,000 pounds.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

T-R-605 - Rope, Manila and Sisal.

FSC 3895

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-3580	- Cranes and Crane-Shovels, Truck, Crawler, and Wheel Mounted, Full-Revolving, and Their Attachments, Packaging of.
MIL-L-11025	- Lead, Pile-Driver, with Catwalk.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification Marking of US Military Property.

DRAWINGS

ME

13221E4785	- Kit, Hammer, Piledriver, Drop, 1,800 Pounds.
13221E4780	- Kit, Hammer, Piledriver, Drop, 3,000 Pounds.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The drop piledriver hammer shall consist of the hammer, the pile cap with attached rope sling, the plug, and the ring. The 1,800 pound drop piledriver hammer shall be as shown on Drawing 13221E4785 and the 3,000 pound drop piledriver hammer shall be as shown on Drawing 13221E4780, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:05Z
Check the source to verify that this is the current version before use.

procedure, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Materials. Material shall be as specified herein and as shown on the applicable drawings.

3.3 Weight. The weight of finished hammer shall be 1,800 pounds for Size 1 and 3,000 pounds for Size 2, plus or minus 10 percent.

3.4 Plug. The plug shall be free from checks and knots. The grain in the wood shall be paralleled to the length of the plug.

3.5 Rope sling. The rope sling shall be 2-1/4 inch nominal circumference manila rope with a breaking strength of 5,400 pounds or 2-3/4 inch nominal circumference sisal rope with breaking strength of 6,160 pounds, conforming to T-R-605. The rope shall be threaded through the holes of the pile cap and the rope ends shall be spliced to form a loop on each side of the cap. The loops shall be used as a sling over the hooks provided on the sides of the hammer.

3.6 Identification marking. The hammer shall be identified, in accordance with MIL-STD-130. The weight of the finished hammer shall be stenciled on the side of the hammer in such a manner as to be discernible. Stenciling shall conform to MIL-T-704.

3.7 Treatment and painting. The hammer and all components except the guide grooves and the rope sling shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A, color as specified (see 6.2).

3.8 Workmanship. All parts and components which include castings and forgings shall be clean of harmful extraneous material such as sand, dirt, sprues, and flux. Rework shall be limited to procedures which do not reduce mechanical properties or affect function. Holes shall have the burrs removed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:05Z
Check the source to verify that this is the current version before use.

for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.4).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-1705.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined for the major and minor characteristics for possible defects as specified in 4.4.1. AQL shall be 1.0 percent defective for major defects and 2.5 percent defective for minor defects.

4.4 Inspection procedure.

4.4.1 Examination. The sample drop piledriver hammer shall be examined as specified in 4.3.2 for the following characteristics:

Major

101	Components not as specified or missing (see 3.1).
102	Dimensions and tolerances not in accordance with drawings as specified herein (see 3.1.1).
103	Materials not as specified (see 3.2).
104	Weight of hammer not within specified-tolerances (see 3.3).
105	Plug not free from checks and knots, direction of grain not as specified (see 3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:05Z
Check the source to verify that this is the current version before use.

106	Rope sling not as specified or missing (see 3.5).
107	Poor workmanship, presence of burrs, blow holes, voids, fissures, warps, or extraneous fins or protrusions (see 3.8).
108	Machined surfaces not in accordance with drawings as specified herein (see 3.8).

Minor

201	Identification markings incorrect, illegible, or missing (see 3.6).
202	Improper treatment and painting (see 3.7).

4.4 Inspection of packaging. The preservation, packing, and marking shall be examined to determine compliance with the Quality Assurance Provisions of MIL-C-3580.

5. PACKAGING

5.1 Preservation, packing, and marking. The drop piledriver hammer, its parts and components, and the technical publications shall be preserved, packed, and marked in accordance with MIL-C-3580. The preservation and packing shall be Level A, B, or Commercial as specified (see 6.2).

6. NOTES

6.1 Intended use. The drop piledriver hammers are intended for use with piledriving leads conforming to MIL-L-11025.

6.2 Ordering data. Procurement documents should specify the followings:

(a) Title, number, and date of this specification.
(b) Size of hammer required (see 1.2).
(c) Color required (see 3.7).
(d) Preservation and packing required (see 5.1).

Custodians:
Army - ME
Air Force - 99

Preparing activity:
Army - ME

Project 3895-0234

Review activity:
DSA - CS

User activity:
Army - CE

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:05Z
Check the source to verify that this is the current version before use.