MIL-P-2496D (MU)
AMENDMENT #1
26 January 1968

MILITARY SPECIFICATION

PRIMER, PERCUSSION, M29A1
PARTS AND LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-2496D (MU), dated 9 January 1967.

Paragraph 4.4.2.1, delete and substitute:

"4.4.2.1 Sensitivity.- The primers shall be divided into 8 groups of 50 primers each and tested in the following manner: The first group (50) of primers shall be tested by dropping a steel ball 1.94 plus or minus .02 ounces on the firing pin of the test fixture from a height of 5 inches. (The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball.) The number of primers that fire, fail to fire, hangfire or squib (see 6.8) shall be recorded. This procedure shall be repeated as successively increasing heights of 1 inch, using a new group of 50 primers at each different height, until a height is reached at which all primers in the group being tested fire. The test fixture shall then be set at a height of 4 inches and the above procedure repeated at successively decreasing heights of 1 inch, using a new group of 50 primers at each height, until a height is reached at which all primers in the group being tested fail to fire. Acceptance or rejection of the lot shall be determined from calculations based on recorded data (see 6.6). All samples subjected to test shall be scrapped. Any remaining untested samples may be returned to the lot from which they were taken."

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1375-A-1080

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:04Z
Check the source to verify that this is the current version before use.