MIL-S-2607A
3 November 1952
SUPERSEDING
MIL-T-2607
15 February 1951

MILITARY SPECIFICATION

SAMPLER, BUTTER-LARD-MEAT

This specification has been approved by the Departments of the Army, the Navy, and the Air Force

1. SCOPE

1.1 This specification covers sampler suitable for use in testing meat and dairy products.

1.2 **Classification.**—The sampler, meat and dairy, shall be of the following types and classes, as specified (see 6.1):

Type I—Sampler, dairy.
Class A—Sampler, cheese, lard and butter, 6-inch.
Class B—Sampler, lard and butter, 14-inch.
Type II—Sampler, meat.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, and standards, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

GG-I-526—Instruments, Dental and Surgical: General Specifications.
NN-B-621—Boxes, Wood, Nailed and Lock-Corner.

MILITARY

JAN-P-106—Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.
MIL-P-116—Preservation, Methods of.
JAN-P-120—Packaging and Packing for Overseas Shipment—Cartons, Folding, Paperboard.
JAN-P-133—Packaging and Packing for Overseas Shipment—Boxes, Setup Paperboard.
MIL-L-10547—Liners, Case, Waterproof.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking of Shipments.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.**

3.1.1 *Type I.*—Sampler, dairy.

3.1.1.1 *Blades.*—The blade of the sampler shall be made of corrosion-resisting steel conforming to class 2, composition G, of Specification GG-I-526.

3.1.1.2 *Handles.*—The handles shall be made of durable hardwood, such as rosewood or walnut, or shall be made of aluminum or stainless steel.

3.1.2 *Type II.*—Sampler, meat.

3.1.2.1 *Blades.*—The blades shall be made from forged carbon steel, highly tempered, and properly polished.

3.1.2.2 *Handles.*—The handles shall be made of durable hardwood, such as rosewood or walnut.

3.2 **Type I.**—Sampler, dairy.

3.2.1 *Construction.*—The blades shall be made of stainless steel (3.1.1.1), and shaped for efficient and practical use. The handles shall be made of wood, aluminum, or stainless steel (3.1.1.2), be T-shaped, and afford a comfortable grip.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:10Z
Check the source to verify that this is the current version before use.

3.2.2 *Dimensions.*—Sampler, dairy, shall have the following dimensions:

	Over-all Length inches	Length of blade inches	Approximate diameter of blade inches
Class A—Sampler, cheese, lard and butter	6 to 8	5	¼ by ¼
Class B—Sampler, lard and butter	12 to 14	10	¼ by ¼

3.3 **Type II.**—Sampler, meat.

3.3.1 *Construction and dimensions.*

3.3.1.1 *Blades.*—The blade shall be 8 inches long with the tang extending through the handle. The blade shall be a flattened oval, five-sixteenth inch wide and three-sixteenth inch thick, tapering to a sharp point.

3.3.1.2 *Handles.*—The handle grips shall be of the large, rounded type, affording a comfortable and efficient grip to the operator. One surface shall be flattened to prevent the rolling of the trier when laid down. A brass ferrule shall be securely attached to the handle grip where it is entered by the tang. The tang shall be securely retained in the handle grip and fitted with a noncorrosive metal washer where it extends through the handle grip.

3.4 **Finish.**

3.4.1 *Metal.*—All exposed metal parts shall be highly polished.

3.4.2 *Handle.*—The wooden handles, when used, shall be given a coat of hot, water-resisting varnish.

3.5 **Identification marking.**—Each sampler shall be legibly and permanently marked with the name or registered trade-mark of the manufacturer.

3.6 **Workmanship.**—Workmanship shall be first class throughout. Samplers shall be free from defects which detract from their appearance or may impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Sampling.**—Unless otherwise specified, samples shall be submitted in accordance with instructions furnished by the procuring activity (see 6.1). In addition, inspection at contractor's facility by inspector shall be conducted in accordance with Standard MIL–STD–105.

4.2 **Inspection.**—Inspection may be made throughout the entire process of manufacture. The passing as satisfactory of any detail of construction or materials shall not relieve the contractor of responsibility for faulty workmanship or materials which may be discovered at any time prior to final acceptance. Final inspection of the finished article shall be made either at point of production or at point of delivery, as specified (see 6.1). In case of factory inspection, every facility shall be afforded inspectors, by the manufacturer, for the prosecution of their work.

4.3 **Tests.**—Tests shall be conducted in accordance with the applicable specifications, as necessary, to determine compliance with this specification.

5. PREPARATION FOR DELIVERY

5.1 **Packaging.**

5.1.1 *Unit packaging.*—One sampler of the type and class specified constitues one unit.

5.1.1.1 *Cleaning.*—Each unit shall be thoroughly cleaned in accordance with the applicable method as outlined in Specification MIL–P–116.

5.1.1.2 *Wrapping and cartoning.*—Each unit shall be completely wrapped in neutral tissue or other suitable anticorrosive material and then packaged in a carton of appropriate size constructed in accordance with Specification JAN–P–120 or JAN–P–133. Carton shall contain sufficient cushioning material to prevent shifting and breakage, and shall be adequately secured to prevent accidental opening.

5.2 **Packing.**

5.2.1 *For domestic shipment.*—Ninety-six unit cartons (96 units) shall be overpacked in an exterior container constructed in accordance with Specification NN–B–621.

5.2.2 *For oversea shipment.*—Ninety-six unit cartons (96 units) shall be overpacked in an exterior container designed for type 2 load, and constructed in accordance with Specification JAN–P–106. Closure and strapping shall comply with appendix thereto.

5.2.2.1 *Case liner.*—Each box shall be lined with a waterproof case liner conforming to Specification MIL–L–10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:10Z
Check the source to verify that this is the current version before use.

5.2.3 *Packing variation permitted.*—If the number of units in any shipment is not the exact multiple of the number of units specified to be contained in each shipping container, the units not constituting the nearest such multiple shall be packed in an exterior container of suitable size and design and so constructed as to insure safe delivery to specified destination.

5.3 **Marking.**

5.3.1 *Interior packages.*—Each unit carton shall be marked with stock number, nomenclature, unit, quantity, office identifying number, and name of contractor.

5.3.2 *Shipping container.*—Shipping container shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 **Ordering data.**—Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and class required (see 1.2).
(c) Sampling required (see 4.1).
(d) Inspection required (see 4.2).
(e) Place of final inspection (see 4.2).
(f) Whether packing for domestic or oversea shipment is required (see 5.2).

6.2 This specification covers the following items appearing in the Armed Services Catalog of Medical Matériel:

8–129–000—Trier, Cheese, Lard and Butter, 6-inch.
8–131–000—Trier, Lard and Butter, 14-inch.
8–133–000—Trier, Meat, 8-inch.

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of the specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army-Army Medical Service.
Navy-Bureau of Medicine and Surgery.
Air Force.

Other interest:
Army—T.

U. S. GOVERNMENT PRINTING OFFICE: 1953

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:10Z
Check the source to verify that this is the current version before use.