INCH-POUND

MIL-DTL-53126/5A

16 OCTOBER 2012

SUPERSEDING
MIL-E-53126(ME)
20 April 1992

DETAIL SPECIFICATION SHEET
POWER DISTRIBUTION, ILLUMINATION SYSTEMS, ELECTRICAL
ILLUMINATION SYSTEM, SINGLE PHASE

This specification is approved for use within US Army Research Development and Engineering Command, Communications and Electronics Research and Development Center, Product Realization Directorate, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-53126.

1 SCOPE

1.1 Scope. This specification sheet covers the detail requirements for the Power Distribution Illumination Systems Electrical (PDISE), Type V, model: M46, NSN: 6150-01-208-9751.

2 APPLICABLE DOCUMENTS

2.1 Drawings. The following Government drawings form a part of this specification sheet to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING#	NOMENCLATURE	DRAWING #	NOMENCLATURE
CECOM & PM-MEP Drawings - Cage Code: 97403 and 30554			
13226E7046	Utility Assembly, Electrical, Receptacles and Lighting		

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from: PROJECT MANAGER-MOBILE ELECTRIC POWER, 5850 Delafield Road, Bldg 324 FT BELVOIR VA 22060-5809.)

AMSC N/A FSC 6150

Distribution Statement A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:09Z
Check the source to verify that this is the current version before use.

3 REQUIREMENTS

3.1 Requirements. The M46, Utility Kit, PDISE shall consist of the following:

Quantity	Description	Reference
6	Extension cables	3.3.18.7*
2	Branch circuit assemblies	3.3.18.9*
2	Branch Circuit Support Rope Assemblies	3.1.2
2	Utility Lights	3.3.18.8
1	Container	3.20*, 3.1.3
8	Securing Strap	3.3.19.1*
2	In-Line GFCI	3.3.18.10*

*Note: See requirement paragraph referenced MIL-DTL-53126.

3.1.1 Utility light. The light shall be a switched, fuse protected, single tube, 40 watt, ultraviolet stable, fluorescent lamp assembly, 120 VAC, 60 Hz, operating on an input of 0.5 ampere maximum. The 48.00-inch nominal length lamp shall produce 2770 initial lumens and the light shall operate in ambient temperatures of 0 °F to 140 °F, at a relative humidity of up to 80 percent. The lamp ballast shall be screened to preclude electro-magnetic interference. The light shall be provided with power cables, not less than three feet long, connected to each end of the assembly, providing input and flow-through circuits. One cable shall have a straight blade, isolated ground, input plug, and the other shall have a straight blade, isolated ground, output receptacle, both conforming to UL 943. The light shall have means for bulb replacement without the use of tools. A label affixed to the light shall contain the manufacturer's identification, part number, and cautionary notes, at a minimum.

3.1.2 Support line. The branch circuit assembly support line shall consist of 53 ± 0.5 feet of rope or functional equivalent, capable of supporting the cable assembly (see 3.3.18.9 in MIL-DTL-53126) with eight repositionable slides. The slides shall fit onto the line and provide a means of attachment for the support line assembly. The use or repositioning of the slides shall not abrade the line and means shall be employed to preclude the line ends fraying or loss of the slides.

3.1.3 Storage container. The reusable storage container shall be rigidly constructed of a polyethylene or similar non-corroding material that is suitable to extended use in operating temperatures of -25 °F to 120 °F and extended storage at temperatures of -28 °F to 160° F. The case shall not be greater than 36.00 x 24.00 x 16.00 (high) inches, and not greater than 30 pounds with a capacity of not less than 3.5 cubic feet. The case color shall be indelible and unless

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:09Z
Check the source to verify that this is the current version before use.

otherwise specified (see 6.2 of MIL-DTL-53126), shall be a matte black or approximate camouflage green, color no. 34094 of FED-STD-595. The internal components may be finished with the manufacturer's standard commercial color and paint, plating, or treatment. Anti-shear features shall be incorporated to prevent shock slippage between the lid and base of the container. The hinged lid shall have ribs molded to nest into matching recesses provided in the base, for stacking. The case shall withstand stacking eight units high, with each container loaded to a gross weight of 125 pounds. The closure shall effect an environmental seal but shall not be airtight. The container shall be provided with handles, stays, latches, and hinges flush with the exterior surface, recessed, or internal to the container.

3.1.3.1 Handles. The handles shall have a nominal 90 degree stop, for use, and incorporate a method to return the released bail to rest. The bail shall be padded and suitable for use by personnel (see 3.5.9 in MIL-DTL-53126) wearing arctic mittens. The handle, and its mounting, shall withstand the shear of lifting and the tensional and torsional forces of dragging the fully loaded container, in any of the environments specified herein.

3.1.3.2 Stays. The container shall be provided with an integral stay(s) that will hold the lid in an open position of 90 to 105 degrees unassisted, indefinitely, in any of the environments specified herein. Operation shall be incidental to the opening of the chest, except that user intervention is permissible for locking in place.

3.1.3.3 Latches. The latching mechanism shall not require greater than a half turn to fully engage or disengage, and shall be capable of, or supplied with provisions for, locking. The requirement to be flush or recessed applies only in the closed position, but is desirable when fully open. Design of the mechanism shall allow manipulation, to include locking, to be accomplished by personnel (see 3.5.9 in MIL-DTL-53126) wearing arctic mittens.

3.2 This specification sheet had no superseding “base”. The original publication of this specification was a performance specification that was used in-house by CR4. Since this specification is now a detailed specification, this specification sheet is deemed necessary to capture the unique characteristics desired in the end item.

3.3 Changes from previous issues: Marginal notations are not used in this revision to identify changes with respect to the previous issue because this detail specification sheet although a part of the base document, was not published because it was a document with limited circulation and coordination that was used essentially by CR4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:09Z
Check the source to verify that this is the current version before use.

Concluding Material

Custodian:

Army - CR4

Preparing Activity:

Army - CR4
(Project 6150-2012-014)

Review Activities:

DLA – GS

Note: The activities listed above were interested in this document as of the date of this document. Since organization and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:09Z
Check the source to verify that this is the current version before use.