MILITARY SPECIFICATION

GENERATOR, SIGHT CURRENT: 12000239

This amendment forms a part of Military Specification MIL-G-60662B (AR), dated 29 March 1991, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

Table I, Change the elevation and traverse lead angles as shown:

FROM: $(\text{Elevation Lead Angle})^2 = \left(\frac{\theta_A}{25.43}\right)^2$

$(\text{Traverse Lead Angle})^2 = \left(\frac{\theta_B}{25.43}\right)^2$

TO: $(\text{Elevation Lead Angle})^2 = \left(\frac{\theta_A}{25.47}\right)^2$

$(\text{Traverse Lead Angle})^2 = \left(\frac{\theta_B}{26.4}\right)^2$

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

PAGE 9

TABLE I, Change the $\dot{R}$ and elevation lead angles as shown:

FROM: $\dot{R}$ Radar Range Rate Voltage: -32 mV/meter/sec

L_E Elevation Lead Angle = $\frac{\theta_A}{25.43}$

L_E^3 Elevation Lead Angle Cubed = $\left(\frac{\theta_A}{25.43}\right)^3$

TO: $\dot{R}$ Radar Range Rate Voltage: 30.866 V/meter/sec

L_E Elevation Lead Angle = $\frac{\theta_A}{25.47}$

L_E^3 Elevation Lead Angle Cubed = $\left(\frac{\theta_A}{25.47}\right)^3$

PAGE 10

3.5.1.1.4.1 Torque current, Change V_{IT} equation as shown:

FROM: $V_{IT} = (\pm)^* \ 2.840\text{x}10^{-2} (L_E \ L^2 \ V_{IM}^{2.03}) (\pm)^* \ 4.861\text{x}10^{-2}$

$(L_E^3 \ V_{IM}^{2.03}) - 6.952\text{x}10^{-3} \ \dot{R} - 2.006\text{x}10^{-2} \ R + 1.859\text{x}10^{-2} \ \cos \theta_E$

TO: $V_{IT} = (\pm)^* \ 2.840\text{x}10^{-2} (L_E \ L^2 \ V_{IM}^2) (\pm)^* \ 4.861\text{x}10^{-2} \ (L_E^3 \ V_{IM}^2)$

$- 6.952\text{x}10^{-3} \ \dot{R} - 2.006\text{x}10^{-2} \ R + 1.859\text{x}10^{-2} \ \cos \theta_E$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

PAGE 18

3.5.1.2.2.3.3.1 Magnet current, Change V_{IM} equation as shown:

FROM: $$V_{IM} = A_M \left[\left(\frac{-.0295^2 - 18.58}{R} \right) + \ldots \right.$$

TO: $$V_{IM} = A_M \left[\left(\frac{-.0295\ L^2 - 18.58}{R} \right) + \ldots \right.$$

PAGE 19

3.5.1.2.2.3.3.2 Torque current, Change V_{IT} equation as shown:

FROM: $V_{IT} = (\pm) * 2.840 \times 10^{-2} \ (L_E\ V_{IM}^{2.03}) \ (\pm) * 4.861 \times 10^{-2} \ (L_E^3\ V_{IM})^{2.03} \ldots$

TO: $V_{IT} = (\pm) * 2.840 \times 10^{-2} \ (L_E L^2 V_{IM}^2) \ (\pm) * 4.861 \times 10^{-2} \ (L_E^3\ V_{IM}^2) - \ldots$

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A801)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.