INCH-POUND

MIL-G-60662B (AR)
AMENDMENT 2
28 October 1992
SUPERSEDING
AMENDMENT 1
28 February 1992

MILITARY SPECIFICATION

GENERATOR, SIGHT CURRENT: 12000239

This amendment forms a part of MIL-G-60662B (AR), dated 01 May 1991, is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1: Delete **the following military standard:**

"MIL-STD-2000 - Standard Requirements **for Soldering Electrical and Electronic Assemblies"**

PAGE 3

• **2.1.2: Add the following drawing:**

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE **5**

• **3.3.1: Delete in its entirety and substitute the following:**

'3.3.1 vibration. The generator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.3 Altitude operating. The generator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 8

Table 1:

Delete:

$$(\text{Elevation Lead Angle})^2 = \left(\frac{\theta_A}{25.43}\right)^2$$

$$(\text{Traverse Lead Angle})^2 = \left(\frac{\theta_B}{25.43}\right)^2$$

and substitute the following:

$$(\text{Elevation Lead Angle})^2 = \left(\frac{\theta_A}{25.47}\right)^2$$

$$(\text{Traverse Lead Angle})^2 = \left(\frac{\theta_B}{26.4}\right)^2$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

PAGE 9

Table I (cont'd.):

Delete: **R** **Radar Range Rate Voltage : -32 mV/meter/sec**

L_E Elevation Lead Angle = $\frac{\theta_A}{25.43}$

L_E^3 Elevation Lead Angle cubed = $\left(\frac{\theta_A}{25.43}\right)^3$

and substitute the following:

R **Radar Range Rate Voltage : 30.866 V/meter/see**

L_E Elevation Lead Angle = $\frac{\theta_A}{25.47}$

L_E^3 Elevation Lead Angle Cubed = $\left(\frac{\theta_A}{25.47}\right)^3$

PAGE 10

3.5.1.1.4.1: Delete the equation and substitute the following:

$$V_{IT} = (\pm)^{*} 2.840\times10^{-2} (L_E L^2 V_{IM}^2) (\pm)^{*} 4.861\times10^{-2} (L_E^3 V_{IM}^2) - 6.952\times10^{-3} \dot{R} - 2.006\times10^{-2} R + 1.859\times10^{-2} \cos \theta_E$$

*** (+) sign is (+) for a positive lead angle elevation and (-) for a negative lead elevation**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

PAGE 19

3.5.1.2.2.3.3.1:

Delete: $V_{IM} = A_M \left[\left(\frac{-.0295^2 - 18.58}{R} \right) + \cdots \right.$

and substitute the following:

$$V_{IM} = A_M \left[\left(\frac{-.0295\ L^2 - 18.58}{R} \right) + \cdots \right.$$

3.5.1.2.2.3.3.2:

Delete: $V_{IT} = (+) = 2.840 \times 10^{-2} (L_E^2\ V_{IM}^{2.03}) (+) . 4.861 \times 10^{-2} (L^2\ V_{IM})^{2.03}$

and substitute the following:

$$V_{IT} = (+) 2.840 \times 10^{-2} (L_E^2\ V_{IM}^2) (+) . 4.861 \times 10^{-3} (L_E^3\ V_{IM}^2)$$

PAGE 34

* **3.9: Delete in** its entirety **and substitute the following:**

"3.9 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877. "

PAGE 44

• 4.7.1.1: Delete first sentence and substitute the following:

"4.7.1.1 vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.

- **4.7.1.3: Delete in its entirety and substitute the following:**

"4.7.1.3 **Altitude operating. This test shall be performed as specified in Procedure II, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."**

PAGE 54

4.8: Delete in its entirety and substitute the following:

"4.8 **Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.9."**

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-A.R

Preparing activity:
Army-AR

(Project 1285-A858)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:54Z
Check the source to verify that this is the current version before use.