INCH-POUND

MIL-I-60518A
15 January 1992
SUPERSEDING
MIL-I-60518
25 July 1966



MILITARY SPECIFICATION

# INITIATOR, CARTRIDGE ACTUATED, M28 METAL PARTS ASSEMBLY

*This specification is approved for use by all Departments and Agencies of the Department of Defense.*

## 1. SCOPE

**1.1 Scope.** This specification covers the requirements for the M28 Cartridge Actuated Initiator Metal Parts Assembly (see 6.1).

## 2. APPLICABLE DOCUMENTS

### 2.1 Government documents.

**2.1.1 Specifications and standards.** The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-A-2550 | Ammunition, General Specification For |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures And Tables For Inspection By Attributes |
| MIL-STD-109 | Quality Assurance Terms And Definitions |
| MIL-STD-413 | Visual Inspection Guide for Elastomeric O-rings |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 3730), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

**DISTRIBUTION STATEMENT A:** Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

**2.1.2 Other Government documents, drawings, and publications.** The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

NAVAL ORDNANCE STATION (CAGE Codes 19200 and 19203)

| | |
|---|---|
| 10520556 | Initiator, Cartridge Actuated, M28 Metal Parts Assembly |
| 8830992 | Box, Fiberboard (Inner), Packing, Ammunition, For Initiator, Cartridge Actuated, M28 |
| 8830993 | Box, Packing, Ammunition, For Initiator, Cartridge Actuated, M28 |
| 9216932 | Box, Fiberboard (Outer), Alternative, Packing Ammunition, for Initiator, Cartridge Actuated, M28 |

U.S. Air Force

| | |
|---|---|
| TPO 00-724-9886 | Initiator, Cartridge Actuated, M28 |

(Application for copies should be addressed to: Commanding Officer, Naval Ordnance Station, Data Control Branch (Code 3720), Indian Head, MD 20640-5035.)

**2.2 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 First article.** When specified in the contract or purchase order (see 6.2), a sample shall be subjected to the first article inspection (see 4.3 and 6.3).

**3.2 Materials.** All materials used in the manufacture of the initiators shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

**3.2.1 Raw material.** The contractor shall be responsible for selecting from the classification list contained in the raw material specification the surface and physical condition of the raw material intended for use in manufacture.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

**3.3 Hardness and other physical properties.** Hardness and other physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

**3.4 Hydrostatic pressure.** The initiator chamber and cap shall withstand a hydrostatic pressure of 14,000 to 15,000 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.4.1).

**3.5 Shear pin strength.** The shear pin, after application of protective finish, shall shear when a load of 41 ± 5 pounds is applied at the steady rate of 0.125 inch per minute.

**3.6 Metal parts assembly.** Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

**3.7 Protective finish.** Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of contour configuration.

**3.8 Residual magnetism.** The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using procedures in 4.6.5.

**3.9 Workmanship.** Initiators shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

**3.9.1 Metal defects.** All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

**3.9.2 Burr.** No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

**3.9.3 Foreign matter.** No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

**4.1.1 Responsibility for compliance.** All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

**4.1.2 Quality assurance terms and definitions.** Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

**4.1.3 Inspections.** Inspections shall be in accordance with MIL-A-2550.

**4.2 Classification of inspections.** The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

**4.3 Inspection conditions.** Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: room ambient (68 to 77•F)
b. Altitude: sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

**4.4 First article inspection.** At the beginning of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of five metal parts assemblies, nine sets of unassembled parts, one set of unassembled parts without plating or final protective finish, and fifty shear pins from the same lot of shear pins tested by the contractor. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, must be the same as will be used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the first article sample shall be inspected for all requirements of the drawings and specifications. The Government reserves the right to require new first article samples until an acceptable sample is submitted (see 6.3).

**4.5 Quality conformance inspection.**

**4.5.1 Lot.**

**4.5.1.1 Submission of product.** Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

**4.5.1.2 Size of lot.** The production lot size shall be as specified in the contract.

**4.5.2 Examination.** One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4x) magnification may be used in performing visual examination for



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

**4.5.2.1 Chamber, Initiator, Drawing 10520407, covering a detail of Drawing 10520556.**

| Characteristics | Defect | Method of Inspection |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| 101 | Pitch diameter of large external thread, min | Gage |
| 102 | Major diameter of large external thread, min | Gage |
| 103 | Pitch diameter of small external thread, min | Gage |
| 104 | Major diameter of small external thread, min | Gage |
| 105 | Pitch diameter of internal thread, max | Gage |
| 106 | Minor diameter of internal thread, max | Gage |
| 107 | Concentricity of datum location with pitch diameter of small external thread | Gage |
| 108 | Concentricity of pitch diameter of large external thread with cavity | Gage |
| 109 | Concentricity of large external thread pilot with large external thread | Gage |
| 110 | Concentricity of counterbore cavity, including perpendicularity with base of counterbore | Gage |
| 111 | Diameter of counterbore | Gage |
| 112 | Diameter of large thread pilot | Gage |
| 113 | Depth of cavity | Gage |
| 114 | Length to datum location | Gage |
| 115 | Thickness of wall, min | Gage |
| 116 | Metal defective | Visual |
| 117 | Protective finish inadequate or defective | Visual |
| 118 | Surface finish of cavity and angle of gas port, improper | Visual |
| 119 | Burr or sharp corner | Visual |
| 120 | Foreign matter | Visual |
| Minor | | |
| 201 | Pitch diameter of large external thread, max | Gage |
| 202 | Pitch diameter of small external thread, max | Gage |
| 203 | Pitch diameter of internal thread, min | Gage |
| 204 | Diameter of small external thread relief | Gage |
| 205 | Diameter of small external thread pilot | Gage |
| 206 | Diameter of hole in gas port | Gage |
| 207 | Diameter of cavity | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 208 | Depth of counterbore | Gage |
| 209 | Length of gas port | Gage |
| 210 | Length of small thread relief | Gage |
| 211 | Length from face of gas port to small thread | Gage |
| 212 | Length of large external thread pilot | Gage |
| 213 | Thickness of wall, max | Gage |
| 214 | Depth of threaded hole | Measure |
| 215 | Diameter of chamfer at internal thread | Measure |
| 216 | Total length | Measure |
| 217 | Length of large external thread | Measure |
| 218 | Marking missing, incorrect, or illegible | Visual |
| 219 | Radius or chamfer missing or incorrect | Visual |
| 220 | Surface finish improper, except as otherwise classified | Visual |

#### 4.5.2.2 Cap, Initiator, Drawing 10520557, covering a detail of Drawing 10520556.

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Pitch diameter of large internal thread, max | Gage |
| 102 | Minor diameter of large internal thread, max | Gage |
| 103 | Pitch diameter of shear pin setscrew thread, max | Gage |
| 104 | Minor diameter of shear pin setscrew thread, max | Gage |
| 105 | Pitch diameter of small internal thread, max | Gage |
| 106 | Minor diameter of small internal thread, max | Gage |
| 107 | Concentricity of sidewalls of boss cavity with pitch diameter of large internal thread | Gage |
| 108 | Concentricity of large internal thread with midsection cavity | Gage |
| 109 | Concentricity of striker hole with firing pin cavity | Gage |
| 110 | Concentricity of body, large end, with pitch diameter of large internal thread | Gage |
| 111 | Concentricity of undercut behind large internal thread with pitch diameter of large internal thread | Gage |
| 112 | Concentricity of body with firing pin cavity | Gage |
| 113 | Concentricity of pitch diameter firing pin cavity internal thread with small cavity | Gage |
| 114 | Concentricity of chamfer at striker hole with body, large end | Gage |
| 115 | Perpendicularity of internal boss face with pitch diameter of large internal thread | Gage |
| 116 | Symmetry of flats with body | Gage |
| 117 | Symmetry of thickness of mounting lugs with body, large end | Gage |
| 118 | Symmetry of shear pin hole with small cavity | Gage |
| 119 | Variation of centerline of mounting holes with centerline of firing pin cavity | Gage |
| 120 | Diameter of large thread undercut | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 121 | Diameter of striker hole | Gage |
| 122 | Diameter of boss cavity, max | Gage |
| 123 | Diameter of shear pin hole, max | Gage |
| 124 | Diameter of small thread counterbore | Gage |
| 125 | Diameter of chamfer, small thread | Gage |
| 126 | Diameter of firing pin cavity | Gage |
| 127 | Diameter of chamfer and angle of chamfer at striker hole | Gage |
| 128 | Depth of small thread cavity counterbore, max | Gage |
| 129 | Depth of shear pin setscrew counterbore, max | Gage |
| 130 | Depth of large thread cavity to face of internal boss | Gage |
| 131 | Depth from large thread undercut to base of cartridge head recess Gage | |
| 132 | Length to end of effective thread, min | Gage |
| 133 | Length to end of effective thread, max | Gage |
| 134 | Thickness of wall, min | Gage |
| 135 | Height of boss | Gage |
| 136 | Marking missing, incorrect, or illegible | Visual |
| 137 | Metal defective | Visual |
| 138 | Protective finish inadequate or defective | Visual |
| 139 | Surface finish of firing pin cavity, undercut and mouth of large cavity and small cavity, improper | Visual |
| 140 | Burr | Visual |
| 141 | Foreign matter | Visual |
| 142 | Sharp corners | Visual |
| | | |
| Minor | | |
| 201 | Pitch diameter large internal thread, min | Gage |
| 202 | Pitch diameter shear pin setscrew thread, min | Gage |
| 203 | Pitch diameter setscrew thread | Gage |
| 204 | Minor diameter setscrew thread, max | Gage |
| 205 | Pitch diameter small internal thread, min | Gage |
| 206 | Diameter of boss cavity, min | Gage |
| 207 | Diameter of body, large end | Gage |
| 208 | Diameter of body, small end | Gage |
| 209 | Diameter of shear pin hole, min | Gage |
| 210 | Diameter of mounting holes | Gage |
| 211 | Diameter of internal boss | Gage |
| 212 | Depth of shear pin setscrew thread, min | Gage |
| 213 | Depth of small thread cavity counterbore, min | Gage |
| 214 | Depth to base of small thread cavity, including chamfer | Gage |
| 215 | Depth of cartridge head recess | Gage |
| 216 | Length of shoulder from face of small end | Gage |
| 217 | Total length | Gage |
| 218 | Length of body, large end | Gage |
| 219 | Length of mounting lugs | Gage |
| 220 | Width across flats | Gage |
| 221 | Width of large thread undercut | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 222 | Thickness of mounting lugs | Gage |
| 223 | Location of mounting lugs | Gage |
| 224 | Location of setscrew holes | Gage |
| 225 | Location of shear pin hole | Gage |
| 226 | Radius or chamfer missing or incorrect, except as otherwise classified | Visual |
| 227 | Surface finish improper, except as otherwise classified | Visual |

**4.5.2.3 Pin, Shear, Drawing 10520475, covering a detail of Drawing 10520556.**

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Diameter, max | Gage |
| 102 | Total length, min | Gage |
| 103 | Metal defective | Visual |
| 104 | Protective finish inadequate or defective | Visual |
| 105 | Surface finish improper | Visual |
| 106 | Burr | Visual |
| 107 | Foreign matter | Visual |

Minor

| | | |
|---|---|---|
| 201 | Total length, max | Gage |
| 202 | Profile of end | Measure |

**4.5.2.4 Filter, Drawing 10520414, covering a detail of Drawing 10520556.**

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Pitch diameter of thread, min | Gage |
| 102 | Major diameter of thread, min | Gage |
| 103 | Concentricity of thread with center hole and outside diameter | Gage |
| 104 | Symmetry of holes with outside diameter | Gage |
| 105 | Diameter of center holes | Gage |
| 106 | Diameter of holes | Gage |
| 107 | Depth of center hole | Gage |
| 108 | Depth of slot, max | Gage |
| 109 | Location of holes | Gage |
| 110 | Angular location of holes | Gage |
| 111 | Nylon patch not properly located or fused | Manual/Visual |
| 112 | Number of holes incorrect | Visual |
| 113 | Metal defective | Visual |
| 114 | Protective finish inadequate or defective | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 115 | Burr | Visual |
| 116 | Foreign matter | Visual |

Minor

| | | |
|---|---|---|
| 201 | Pitch diameter of thread, max | Gage |
| 202 | Diameter of undercut | Gage |
| 203 | Diameter of body | Gage |
| 204 | Depth of slot, min | Gage |
| 205 | Total length | Gage |
| 206 | Length of body | Gage |
| 207 | Width of undercut, max | Gage |
| 208 | Width of slot | Gage |
| 209 | Location of slot | Gage |
| 210 | Marking missing, incorrect, or illegible | Visual |
| 211 | Chamfer missing or improper | Visual |
| 212 | Surface finish improper | Visual |

#### 4.5.2.5 Pin, Firing, Drawing 10520474, covering a detail of Drawing 10520556.

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Concentricity of striker with body | Gage |
| 102 | Concentricity of groove with body | Gage |
| 103 | Symmetry of pin hole with body | Gage |
| 104 | Diameter of striker | Gage |
| 105 | Diameter of body | Gage |
| 106 | Diameter of groove | Gage |
| 107 | Diameter of pin hole | Gage |
| 108 | Depth of pin hole | Gage |
| 109 | Length of striker, min | Gage |
| 110 | Location of pin hole | Gage |
| 111 | Metal defective | Visual |
| 112 | Protective finish inadequate or defective | Visual |
| 113 | Surface finish of body improper | Visual |
| 114 | Burr or sharp corner | Visual |
| 115 | Foreign matter | Visual |

Minor

| | | |
|---|---|---|
| 201 | Total length | Gage |
| 202 | Length of striker, max | Gage |
| 203 | Location of groove | Gage |
| 204 | Depth of slot | Measure |
| 205 | Width of slot | Measure |
| 206 | Width of groove | Measure |
| 207 | Location of slot | Measure |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 208 | Angle on striker end of body | Visual |
| 209 | Radius or chamfer missing or incorrect | Visual |
| 210 | Surface finish improper, except as otherwise classified | Visual |

**4.5.2.6 Assembly, Drawing 10520556, less all Drawings except 10520557, 10520474, and MS29513-9.**

Critical

| | | |
|---|---|---|
| 1 | Firing pin protrusion | Gage |
| 2 | O-ring missing | Visual |

Major

| | | |
|---|---|---|
| 101 | Burr | Visual |
| 102 | Foreign matter | Visual |

Minor
None defined

**4.5.2.7 Assembly, Drawing 10520556.**

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Any part missing, except as otherwise classified | Visual |
| 102 | Improper assembly | Visual |
| 103 | O-ring not lubricated | Visual |
| 104 | Marking missing, incorrect, or illegible | Visual |

Minor

| | | |
|---|---|---|
| 201 | Protective cap or plug missing | Visual |
| 202 | Protective finish inadequate or defective | Visual |

**4.5.2.8 Box, Fiberboard (Inner), Packing, Ammunition, Drawing 8830992.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Manual |
| 202 | Box damaged | Visual |
| 203 | Marking missing, incorrect, or illegible | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 204 | Cut, damaged, or improperly sealed bag | Visual |

**4.5.2.9 Box, Packing, Ammunition, Drawing 8830993.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Visual/Manual |
| 202 | Strapping missing, loose, broken, or improperly assembled | Visual/Manual |
| 203 | Contents of box exposed | Visual |
| 204 | Box damaged | Visual |
| 205 | Marking missing, incorrect, or illegible | Visual |
| 206 | Number of units incorrect | Visual |

**4.5.2.10 Box, Fiberboard (Outer), Alternative, Packing, Ammunition, Drawing 9216932.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Manual/Visual |
| 202 | Carton broken or damaged | Visual |
| 203 | Number of units contained incorrect | Visual |
| 204 | Marking missing, incorrect, or illegible | Visual |
| 205 | Tape incomplete | Visual |

**4.5.3 Inspection testing.** The following tests shall be performed in accordance with 4.6.

**4.5.3.1 Hardness.** Fifty units from each heat treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

**4.5.3.2 Hydrostatic pressure.** Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with 3.4 shall be cause for rejection of the subassembly.

**4.5.3.3 Shear pin strength.** Fifty pins from each lot of shear pins shall be tested for shear strength. Failure of any shear pin to comply with 3.5 shall be cause for rejection of the lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

**4.5.3.4 Protective finish.** The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

**4.5.3.5 Residual magnetism.** Each assembly shall be subjected to the test for excessive residual magnetism as specified in 4.6.5. Failure of any unit in the inspection sample to comply with 3.8 shall be cause for rejection of the assembly.

**4.6 Test methods and procedures.**

**4.6.1 Hardness.** Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

**4.6.2 Hydrostatic pressure.** Prior to application of protective finish the cap and chamber shall be mounted in the device, using a fixture for properly sealing all openings, and subjected to the internal hydrostatic pressure to determine compliance with 3.4.

**4.6.3 Shear pin strength.** After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.5. The test shall be performed in a fixture in conjunction with a tensile testing machine.

**4.6.4 Protective finish.** Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

**4.6.5 Residual magnetism.** The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

**4.7 Inspection of packaging.** The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

## 5. PACKAGING

**5.1 Packing and marking.** Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8830992 and 8830993. Level B shall be in accordance with Drawings 8830992 and 9216932.

**5.2 Air Force packaging.** Air Force packaging shall be in accordance with TPO 00-724-9886.

## 6. NOTES



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

**6.1 Intended use.** The initiator assembly is used in conjunction with other propellant actuated devices in Aircrew Emergency Escape Systems.

**6.2 Acquisition requirements.** Acquisition documents must specify the following:

a. Title, number, and date of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. If first article inspection is required (see 3.1 and 6.3)

d. The responsible inspection activity (see 4.1)

e. Any special instruction requirements (see 4.3)

f. Level of packing and marking (see 5.1)

**6.3 First article.** When a first article inspection is required, the contracting officer should provide specific guidance to offerors that the items should be a first article sample. The first article should consist of 5 metal parts assemblies, 9 sets of unassembled parts, 1 set of unassembled parts without plating or final protective finish, and 50 shear pins. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

**6.4 Definition.**

**6.4.1 Mechanical failure.** Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

**6.5 Subject term (keyword) listing.**

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

**6.6 Changes from previous issue.** Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:

Preparing activity
Navy - OS

Navy - OS

Air Force - 99

(Project 1377-0D85)

Review activity:
Air Force - 70



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.