INCH-POUND

MIL-DTL-3628/149B
13 May 2019
SUPERSEDING
MIL-DTL-3628/149A
14 July 2014

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, OUTDOOR RECREATION SERVICE U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-210) or Nickel Silver 65/35 (UNS Alloy No C-752)

FINISH: Nickel Plated, (Red Brass only) Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match The Institute of Heraldry Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall): 2 inches (REF)
WIDTH (Overall): 1-3/4 inches (REF)
THICKNESS: (Edge): 0.100 inch $\pm$ 0.010 inch

ATTACHING DEVICE:
1. Attaching device shall be prong and wing type clutch.

2. One prong shall be located on the vertical center line 1/4 inch $\pm$ 1/16 inch above the bottom. Two prongs shall be located on a horizontal line 3/4 inch $\pm$ 1/16 inch below the top, equidistant from each end and 1-7/8 inch $\pm$ 1/16 inch apart.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:49Z
Check the source to verify that this is the current version before use.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2019-207)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:49Z
Check the source to verify that this is the current version before use.