MILITARY SPECIFICATION

CASES, MERCHANDISE DISPLAY, GENERAL SPECIFICATION FOR

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers the general requirements for display cases, merchandise. Specific requirements for a particular display case are covered by the applicable detailed specification sheet (see 6.3).

1.2 Classification.-

1.2.1 Types and styles.- Display cases covered by this specification shall be of the following types and styles as specified (see 6.2).

Type I - Case, merchandise display, exhibit.
Type II - Case, merchandise display, counter.

Style A - Floor mounted, full glass display.
Style B - Floor mounted, glass display, with storage base.

Type III - Case, merchandise display, wall.

Style A - Two section display area.
Style B - Four section display area.
Style C - Two section vertical display area.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

DD-G-451 - Glass, Flat and Corrugated, For Glazing, Mirrors, and Other Uses.
QQ-A-200/9 - Aluminum Alloy Bar, Rod, Shapes and Tubes, Extruded, 6063.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

UU-P-271 - Paper, Wrapping, Waterproofed Kraft.
MMM-A-260 - Adhesive, Water-Resistant (For Sealing Waterproof Paper).
PPP-B-601 - Boxes, Wood, Cleated - Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-F-320 - Fiberboard, Corrugated and Solid Sheet Stock (Container Grade) and Cut Shapes.

MILITARY

MIL-W-6110 - Wood, Determination of Moisture Content Of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL FIRE PROTECTION ASSOCIATION

Standard No. 70

National Electrical Code

(Copies of publications of the National Electrical Code may be obtained from the National Fire Protection Association, 60 Batterymarch Street, Boston, Mass., 02110.)

UNITED STATES DEPARTMENT OF COMMERCE

Product Standard PS 1-66 - Softwood Plywood, Construction and Industrial.

Commercial Standard CS 236-66 - Mat-Formed Wood Particleboard.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402)

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the current version before use.

(Copies may be obtained from the National Electrical Manufacturer's Association, 155 East 44th Street, New York 17, N.Y.)

3. REQUIREMENTS

3.1 Preproduction sample.- When specified (see 6.2), before production is commenced, a sample display case covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product.- Display cases furnished under this specification shall be the manufacturer's current standard models except for changes necessary to comply with this specification and applicable detailed specification. All accessories and components normally furnished commercially shall be furnished with the display cases covered under this specification and applicable detailed specification.

3.3 Materials.- The materials shall conform to referenced specifications and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice, according to accepted industry standards.

3.3.1 Aluminum alloy.- The aluminum used in the fabrication of display cases shall be alloy 6063, temper T5 in accordance with QQ-A-200/9.

3.3.2 Lumber, hardwood.- Hardwood lumber used in the fabrication of the cases shall be uniformly dried without case hardening or honey-combing. Moisture content at time of fabrication shall be 8 to 12 percent when tested as specified in 4.3.1.1. Lumber shall be free from decay, holes, loose knots, sound tight knots over 1/2 inch in diameter, larvae channels, shake, split, wrap, or brashness.

3.3.3 Particleboard.- Particleboard shall be type I, density B, class 1, in accordance with CS 236-66.

3.3.4 Softwood plywood.- Softwood plywood shall be Group 1 plywood, exterior type, grade B-c, sanded two sides, in accordance with Product Standard PS 1-66.

3.3.5 Laminated plastic sheets.- Plastic sheets shall be nominal 1/16 inch thick, melamine surfaced, high pressure laminated, thermosetting,

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the current version before use.

decorative plastic, conforming to general purpose type, furniture finish, of NEMA Publication No. LD1-1964. Plastic shall closely match exposed wood parts in grain and finish color.

3.3.6 Glass, polished plate.- The polished plate glass shall be type I, glazing quality, in accordance with DD-G-451.

3.4 Construction.- Unless otherwise specified in the specification sheets, construction details shall be as specified herein. Display cases shall be constructed of aluminum alloy specified in 3.3.1, hardwood specified in 3.3.2, particleboard specified in 3.3.3, or plywood specified in 3.3.4. Laminated plastic sheets specified in 3.3.5 shall be bonded to the surface of plywood or particleboard panel in accordance with manufacturers' commercial practice. Aluminum alloy or wooden frames shall have glass inserts, and glass hinged lid or removable horizontal sliding wooden or aluminum framed glass doors. All display cases shall conform to the additional requirements of the specification sheets. Completely assembled display cases shall be placed on flat surface and shall not rock more than 1/16 inch and shall show no evidence of binding of sliding doors or top hinged lid when tested as specified in 4.4.1.

3.4.1 Display cases, types and styles.-

3.4.1.1 Type I, exhibit cases.- The type I exhibit cases shall conform to the requirements specified herein and in the detailed specification sheet. The case shall be constructed on a leg base consisting of four (4) independent legs. The base shall be fabricated of hardwood specified in 3.2.2. The deck of the base shall be made up of slats not over 3-inches wide, with a wood binder. The slat frame shall be not less than 13/16 inch thick with a composition panel placed over the frame, making the deck not less than 1-1/4 inches thick. The aprons shall be not less than 13/16-inch thick by not less than 4-inches wide, fastened to the deck with screws from the inside. The legs shall be fastened to the aprons by means of a corner iron and flange fastened with screws to the apron. Two (2) machine screws shall pass through the steel corner and screw bushings inserted in each, allowing the legs to be removable for shipping and moving purposes. The legs shall be finished on all four sides, tapered from not less than 2-15/16 inches at the top to not less than 1-1/2 inches at the bottom. Legs shall be rounded at the outside corner to not less than 1-inch radius; all other edges rounded to not less than 3/16 inch radius. Fluorescent lighting shall conform to the requirements specified in 3.4.2.

3.4.1.2 Type II, case, merchandise display, counter.-

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:33Z
Check the source to verify that this is the current version before use.

3.4.1.2.1 Style A, floor mounted, full glass display.- Style A counter case shall be floor mounted with glassed top, front and sides conforming to the requirements specified herein and in the detailed specification sheet. The back of the case shall consist of two (2) full height sliding doors of all glass with ground-in door pulls or metal or wood frame glass doors. The display section shall be fabricated of metal with hardwood recessed base. Fluorescent lighting shall conform to the requirements specified in 3.4.2.

3.4.1.2.2 Style B, floor mounted, glass display and base, storage.- Style B counter case shall be floor mounted, glassed on four (4) sides, conforming to the requirements specified herein and in the detailed specification sheet. The back frame shall be fabricated of hardwood with a center rail. The rear of the display section shall have four (4) removable sliding glass doors with ground-in door pulls. The floor shall be made up of not less than 3/8-inch fir plywood panel covered with 1/8-inch hardboard. The lower section of the case shall be of hardwood exterior front and ends with the rear storage area of not less than 12 inches high with a 5-inch recessed high base. Fluorescent lighting shall conform to the requirements specified in 3.4.2.

3.4.1.3 Type III, case, merchandise display, wall.-

3.4.1.3.1 Style A, two section display area.- The style A, two section display area case may be floor mounted against a wall with a closed back of plywood or particleboard, with a glass front conforming to the requirements specified herein and in the detailed specification sheet. The sides may be of glass, plywood or particleboard. When plywood or particleboard is used, they shall be covered with plastic sheets specified in 3.3.5. Glass used in sliding doors or sides shall conform to the requirements specified in 3.4.3. Fluorescent lighting shall conform to the requirements specified in 3.4.2.

3.4.1.3.2 Style B, four section display area.- The style B, four section display area case shall conform to the detailed specification sheets and shall meet the requirements specified in 3.4.1.3.1.

3.4.1.3.3 Style C, two section display area.- The style C, two section display area case shall conform to the detailed specification sheets and shall meet the requirements specified in 3.4.1.3.1.

3.4.2 Electrical equipment.- All electrical equipment shall conform to the National Fire Protection association (NFPA) Standard No. 70, National Electric Code. The supplier shall furnish fluorescent light fixtures (complete with full length reflectors, necessary conduit, fittings, tubes, switch, and remote ballast) in all display cases as indicated and shall be completely wired through the switch to a junction box in the base of

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

the display cases. Fluorescent fixtures to be installed in cornice segments of each display case shall be as continuous as possible using single 40 watt-48 inch fluorescent fixture to the greatest extent possible. Shorter lengths down to 15 watt-18 inch fixtures may be used if space availability can be better accommodated. Fixtures shall be butted end-to end. Fluorescent fixtures shall be grounded to prevent electrical shock through the metal display case rail. All ballasts, sockets, lamps and other fixture components shall be of the type normally furnished in commercial practice. Acceptable evidence of meeting the requirements of NFPA Standard No. 70 shall be the manufacturer's certified statement that the electrical equipment conforms to the applicable requirements.

3.4.3 Glass.- All glass used in constructing display cases and sliding doors, shall be not less than 7/32 inch thick as specified in 3.3.6. All shelf glass shall be not less than 1/4-inch thick. All edges of glass used in the construction of display cases that are exposed shall be ground flat and finished with a beveled polished edge.

3.4.4 Hardware.- Hardware shall be of the type normally furnished in commercial practice.

3.5 Finish.- All wood surfaces shall be finished with a sealer coat and sanded. Filler shall be applied to open-grained wood prior to application of the sealer coat. One coat of undercoating of a light oak color shall be applied and finished with a final coat of clear lacquer. The base shall be finished in accordance with the detailed specification. When aluminum is used for construction of frame, the finish shall be natural color. All finish shall be accomplished in accordance with the manufacturer's standard practice.

3.6 Marking for identification.- Display cases shall be marked legibly with the manufacturer's identification in a location that will not effect the appearance of the case.

3.7 Workmanship.- The finished display cases shall be free of burrs, sharp edges, slivers or tacky finish, and glass shall not be cracked, chipped or loosely assembled. All welds or brazed areas shall be ground and polished smooth.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection.- When a preproduction sample is required, it shall be examined for defects in table I, dimensions specified, and tested in accordance with 4.4.1.

4.3 Sampling for inspection.- Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.1.1 Moisture content of wood.- Tests shall be performed on each lot of lumber offered for inspection at time of fabrication for moisture content in accordance with MIL-W-6110. Three determinations shall be taken on each sample unit and results shall be the average of the three determinations. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5 defects, expressed in terms of defects per hundred units. The sample unit shall be one piece of lumber.

4.3.2 Inspection of the end item.- The lot shall consist of all display cases of one type, style, and size submitted for inspection at one time. The sample unit shall be one completely fabricated display case.

4.3.2.1 Visual examination.- Examination shall be made of the end item for defects as set forth in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. - Classification of defects

Examine	Defect	Classification Major	Minor
Construction and workmanship	Frame not of hardwood or metal (as applicable)	X	
	Inserts not of plate glass	X	
Types II & III	Shelves not adjustable	X	

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the current version before use.

TABLE I. - Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Type III	Door not furnished with roller bearings	X	
	Sliding doors bind or do not move freely	X	
Type II	Door not furnished with ground in door pulls when specified	X	
	Hinged doors do not close properly	X	
	Access opening not as specified	X	
	Not furnished with lock and two keys	X	
	Sharp edges, burrs or slivers not removed	X	
Wiring and electrical	Wiring not as specified	X	
	Not wired through switches to junction box	X	
	Lighting fixtures not as specified	X	
	Lighting fixtures not butted end to end when applicable; not properly installed		X
Finish	Open-grained wood not filled	X	
	Not sanded as specified		X
	Not color specified		X
	Aluminum components not natural color		X
	Glass not polished quality	X	
	Exposed edges not ground flat and with beveled edge	X	
Marking for identification	Not legible, in location exposed to eye		X

4.3.2.2 Dimensional examination.- Examination shall be made for compliance with dimensions specified herein. Any noncompliance therefrom shall constitute a defect. The inspection level shall be S-2 with an AQL of 6.5, expressed in terms of defects per hundred units.

4.3.3 End item test.- When a preproduction sample is not required, the initial production unit shall be tested in accordance with 4.4.1.

4.3.4 Examination of preparation for delivery.- An examination shall be made to determine that packaging, packing and marking as required by

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

section 5 of this specification are complied with. Defects shall be scored as specified in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 6.5 defects, expressed in terms of defects per hundred units. Examination for closure and strapping shall be in accordance with the applicable container specification.

4.4 Tests.-

4.4.1 Level test.- Assembled cases shall be set on a flat level surface and alternately rocked at diagonally opposite corners. The case shall then be examined to determine compliance with 3.4.

TABLE II. - Examination of preparation for delivery

Examine	Defect
Marking	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Component missing or damaged.
Contents	Number per container is more or less than required.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Disassembly.- Detachable glass or wood shelves, glass doors, and legs shall be detached from each case to prevent damage while in transit.

5.1.1.2 Packaging.- (see 6.4).

5.1.1.2.1 Display cases.- Lacquered wood surfaces in contact with packing materials shall be covered with 30-pound basis weight per ream (24- by 36-500) machine-glazed kraft paper, highly calendered kraft paper, or waxed paper. The paper shall then be covered with cushioning material fabricated in the form of pads or blankets and shall be any one of the following materials or combination of these materials to provide built-up cushioning of not less than 1/2-inch thick:

Macerated paper, plain Cellulose wadding

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the current version before use.

Macerated paper, cellulose-faced	Excelsior (sealed ends)
Shredded paper	Cotton wadding
Wood wool	Moulded pulpwood
Wood fiber felt	Laminated cellulose wadding backed with corrugated fiberboard

When cellulose wadding, cotton wadding, laminated cellulose wadding backed with corrugated fiberboard, or macerated paper cellulose faced are used, the initial sheet of machine-glazed kraft paper, highly calendered kraft paper, or waxed paper may be omitted. Cushioning material shall be secured in place with tape, cord or twine. Fluorescent light bulbs shall be secured in place with pressure-sensitive adhesive tape.

5.1.1.2.2 Detached components.- Detached components shall be packaged in a fiberboard box or wood box or crate. Items shall be cushioned in such a manner as to prevent damage while in transit.

5.1.2 Level C.- Display cases shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Each display case, packaged as specified in 5.1, shall be packed in a cleated plywood or nailed wood shipping container conforming to overseas type, type 3 load of PPP-B-601; or class 2, style 2 or 4, type 3 load of PPP-B-621, respectively. Each shipping container, regardless of gross weight, shall be provided with skids in accordance with the applicable container specification. The boxed, detached components shall be secured in an unused portion of the shipping container. The contents shall be secured in such a manner as to prevent movement while in transit and provide a minimum 1 inch clearance between the display case and the interior surfaces of the top, sides, and ends of the shipping container. When fiberboard forms are used to secure the contents, forms shall be fabricated from fiberboard conforming to W5c or W5s of PPP-F-320, and the overwrap of cushioning material specified in 5.1.1.2.1 shall not be required. The contents shall be covered with a full-height shroud made of waterproof barrier material conforming to class E-2, H-1, H-5, or M of UU-P-271. All seams of the shroud shall be sealed with a 3/4-inch minimum width continuous of water-resistant adhesive conforming to MMM-A-260. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.- Each display case, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except shipping containers shall conform to domestic type, style A or B or PPP-B-601; or class 1, style 2 or 4, type 3 load of PPP-B-621; fiberboard used for blocking shall conform to type CF or SF, class domestic, grade 275 of PPP-F-320; and the waterproof shroud shall not be required.

5.2.3 Level C.- Display cases, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Special handling marking requirements applicable to fragile items shall apply.

6. NOTES

6.1 Intended use.- The merchandise display cases are intended for use in Government clothing sales stores, Post Exchanges, commissaries, warehouses, and similar locations for the display of merchandise.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, date and number of this specification.
(b) Type and style required (see 1.2.1).
(c) When preproduction sample is required (see 3.1).
(d) Selection of the applicable levels of packaging and packing (see 5.1).

6.3 The following specification sheets have been issued for type I, II and III display cases:

MIL-C- /1 - Case, Merchandise, Display, Exhibit, Type I
MIL-C- /2 - Case, Merchandise, Display, Counter, Type II
MIL-C- /3 - Case, Merchandise, Dispaly, Wall, Type III

6.4 Packaging.- The method of packaging referred to in 5.1.1.2 is similar to method III of MIL-P-116.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Preparing activity:

Army - GL

Project No. 7195-0049

Code "C"

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the currentversion before use.

Review activities:

Navy - YD
Air Force - 84, 85

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.

"to detach this form, cut along this line"

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

Cases, Merchandise Display, General Specification for - MIL-C-43495

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:33Z
Check the source to verify that this is the current version before use.

OLD

EPARTMENT OF THE ARMY
. S. Army Natick Laboratories
atick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-QS
Natick, Massachusetts 01760

"to detach this form, cut along this line"

OLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:33Z
Check the source to verify that this is the current version before use.