21 June 1971
SUPERSEDING
MIL-P-43478(GL)
17 January 1967

MILITARY SPECIFICATION

PRINTING PLANT ANNEX, SPECIAL WARFARE,

SEMI-TRAILER MOUNTED

1. SCOPE

1.1 This specification covers one type and size fabric covered, metal framed, annex for use with a semi-trailer mounted mobile printing plant (see 6.1).

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-F-106	-	Fasteners, Slide, Interlocking
V-T-285	-	Thread, Polyester
QQ-A-200/8	-	Aluminum Alloy Bar, Rod, Shapes, and Tube, Extruded 6061 and 6062
QQ-A-225/8	-	Aluminum Alloy Bar, Rod, Wire, and Special Shapes, Rolled, Drawn, or Cold Finished, 6061
QQ-A-250/11	-	Aluminum Alloy 6061, Plate and Sheet
AA-A-596	-	Aluminum Alloy Permanent and Semi Permanent Mold Casting
QQ-A-601	-	Aluminum Alloy Sand Casting
QQ-S-763	-	Steel Bars, Shapes, and Forgings, Corrosion-Resisting

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

RR-C-271 - Chains and Attachments, Welded, Weldless and Roller Chain
TT-E-529 - Enamel, Alkyd, Semi-Gloss
TT-P-666 - Primer Coating, Zinc, Yellow, for Aluminum and Magnesium Surfaces
WW-T-700/8 - Tube, Aluminum Alloy, Round, Square, Rectangular, and Other Shapes, Drawn, Seamless, 6061 and 6062
DDD-L-20 - Label; for Clothing, Equipage, and Tentage, (General Purpose)

MILITARY

MIL-C-104 - Crates, Wood, Lumber and Plywood Sheathed, Nailed and Belted
MIL-P-116 - Preservation, Methods of
MIL-W-530 - Webbing and Tape, Textile, Cotton, General Purpose, Natural or in Colors
MIL-R-1670 - Rope, Tent-Lay
MIL-L-1709 - Lines, Tent
MIL-C-5541 - Chemicals Films and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-F-10884 - Fasteners, Snap
MIL-G-16491 - Grommet, Metallic
MIL-A-25994 - Aluminum Alloy Angles, Channels, I and Z Beams, Extruded or Rolled, Structural Shapes
MIL-P-25995 - Pipe, Aluminum Alloy, Drawn or Extruded
MIL-R-30500 - Rope, Polyester
MIL-T-43566 - Tape Textile, Cotton, General Purpose, Natural or in Colors.
MIL-C-43627 - Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Lightdry Finish.

STANDARDS

FEDERAL

FED-STD-595 - Colors
FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:30Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY NATICK LABORATORIES

5-4-369	-	Tent Cover, for General Purpose Use
5-4-824	-	Printing Plant Annex, Special Warfare, Semi-Trailer Mounted; Assembly and Details
5-4-825	-	Wall Details
5-4-826	-	Sections
5-4-827	-	Cover Erection Instruction
6-1-1704	-	Printing Plant Annex, Special Warfare, Semi-Trailer Mounted; Annex Assembly, Complete
6-1-1760	-	Frame Assembly
6-1-1768	-	Frame Details
6-1-1770	-	Floor Section Assemblies
6-1-1771	-	Roof Support Bracket Detail
6-1-1772	-	Floor Beam Cradle Detail
6-1-1773	-	Body, Coupling
6-1-1774	-	Floor "C" and Pin, Support Detail
6-1-1775	-	Jack Screw Assembly
6-1-1776	-	Center Flooring Detail
6-1-1777	-	Ridge Pole Assembly and Details
6-1-1778	-	Post Assembly and Details
6-1-1779	-	Supporting Beam Assemblies and Details
6-1-1780	-	End Floor Beam Assembly
6-1-1781	-	Corner Support Assembly and Details
6-1-1782	-	12 Ft. Gable Assembly
6-1-1783	-	Beam Support Assembly
6-1-1784	-	Ridge Coupling Assembly
6-1-1786	-	13 Ft. Gable Assembly
6-1-1787	-	Cap Support
6-1-1793	-	12 and 13 Ft. Gable Details
6-1-1795	-	Center Beam Assembly
6-1-1798	-	Ridge Coupling Details
6-1-1810	-	Plate, Ground
6-1-1811	-	Bracket Details
6-1-1812	-	End Floor Beam Details

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

3. REQUIREMENTS

* 3.1 First article.- When specified (see 6.2) the supplier shall furnish a sample for first article inspection and approval (see 4.2, 6.2 and 6.3).

* 3.2 Alternative components.- Components offered as equivalent to components specified on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal to the manufacturer's part number identified and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article or if none, the initial production unit, the supplier shall submit for the contracting officer's approval a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of proposed substitution. Approval of the submitted listing, together with necessary supporting data, authorizes the commencement of manufacture of the first article or initial production unit, as applicable, and does not relieve the supplier of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3 Materials and components.- Materials and components shall conform to the referenced specifications, drawings and requirements specified hereinafter.

3.3.1 Frame, flooring and supports, connecting annex.-

3.3.1.1 Aluminum alloys.- Aluminum, of the alloys and tempers specified on the drawings, shall conform to the specifications indicated in table I for the forms noted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

* TABLE I.- Aluminum alloys

Form	Alloy and temper	Specification
Bar	6061-T6	QQ-A-200/8
Plate	6061-T651	QQ-A-250/11
Sheet	6061-T6	QQ-A-250/11
Pipe	6061-T6	MIL-P-25995
Wire	6061-T6	QQ-A-225/8
Structural shapes	6061-T6	MIL-A-25994
Tubing	6061-T6	WW-T-700/8
Sand castings	355-T6	QQ-A-601
Castings	356-T6	QQ-A-596

3.3.1.2 Fasteners, set screws, nuts, bolts and washers.- Fasteners, set screws, nuts, bolts and washers shall be commercially available items of the type, size, material classification and finish specified on the drawings.

3.3.1.3 Chain, sash, No.35.- No. 35 sash chain shall be type 302 corrosion resisting steel and shall conform to type II, class 3 weldless sash chain of RR-C-271.

3.3.1.4 Steel, corrosion resisting.- Corrosion resisting steel shall conform to class 303 of QQ-S-763.

3.3.1.5 Paint.-

3.3.1.5.1 Primer.- Primer shall conform to TT-P-666.

3.3.1.5.2 Enamel.- Enamel shall conform to class A or B of TT-E-529. Enamel color shall be olive drab color No. 24087 of FED-STD-595.

3.3.2 Cover, connecting annex and tent cover for general purpose use.-

3.3.2.1 Cloth, duck, cotton.- Cloth for the connecting annex cover and tent cover shall conform to MIL-C-43627 dyed shade olive drab No. 7.

3.3.2.2 Tape, textile, cotton.- Tape shall conform to type I, class 4, 1-inch width of MIL-T-43566, dyed shade olive drab No. 7.

3.3.2.3 Webbing, textile, cotton.- Webbing shall conform to type IIb, class 4, of MIL-W-530 in the width shown on applicable drawings and dyed shade olive drab No. 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

3.3.2.4 Thread, polyester.- The thread shall conform to type I class 1, subclass B of V-T-285 in the sizes indicated in table II, for the applications noted.

TABLE II.- Thread size

Application	Thread size
For all stitching, except stitching indicated by "Z" on drawings.	Size FF for needle and bobbin.
For all stitching indicated by "Z" on drawings.	Size FF for needle, size F for looper.

3.3.2.4.1 Color.- The thread for all stitching SS-1 (Cable No. 66022). The dyed thread shall show fastness to weathering equal to or better than the standard shade sample (see 6.4). If no standard sample is available, the thread shall show good fastness to weathering.

3.3.2.5 Rope, manila.-

3.3.2.5.1 Tie-down.- The tie down rope shall conform to type XV of MIL-L-1709 except that the length shall be 4 feet.

3.3.2.5.2 Hem.- The hem rope shall conform to size 3/4-inch circumference (1/4-inch diameter), type I, class 2 of MIL-R-1670.

3.3.2.6 Rope, polyester.- The polyester rope shall conform to size 3/4-inch circumference (1/4-inch diameter) of MIL-R-30500 and shall be dyed to match an approved standard shade of olive drab No. 7 (see 6.4).

3.3.2.7 Lines, tent.- The cover tent lines shall conform to type XXI of MIL-L-1709.

3.3.2.8 Fasteners, slide, interlocking.- The slide fasteners shall conform to type III or IV, as applicable, style I, size H of V-F-106. Slide fastener chains shall be fabricated of natural finish brass or aluminum and sliders shall be made only of brass.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

3.3.2.8.1 Tape, slide fastener.- The slide fastener tape shall be dyed to match olive drab shade S (Cable No. 66519) and shall be water repellent and mildew resistant treated. The color of the tape after treatment will be considered acceptable. The tape shall show good fastness to weathering.

3.3.2.9 Grommet, metallic.- Grommets shall be type III, class 3, size No. 2 and 4 of MIL-G-16491.

3.3.2.10 Fasteners, snap.- Snap fasteners shall conform to style 1, finish 2, regular pronged female socket; and size 1, stud eyelet base, male component of MIL-F-10884.

3.3.2.11 Buckle and strap tip.- The buckle and strap tip shall be equivalent to requirements shown on Drawing 5-4-824.

3.4 Design and construction.- The connecting annex frame (including flooring and supports), the connecting annex cover and the tent cover (see 6.1), shall conform to the design details and dimensions shown on the drawings referenced in 2.1, and requirements hereinafter specified.

3.4.1 Welding.- Welded connections of the types and sizes shown on the drawings shall be accomplished using the inert gas shielded process and filler rod recommended by the aluminum manufacturers. The surfaces of parts to be formed shall be thoroughly clean and free from oxidation prior to welding.

3.4.2 Threaded connections.- Except where otherwise shown on the drawings, threaded connections shall not be peened, staked or otherwise deformed to prevent disassembly.

3.4.3 Metal components.- In addition to forming and machining as required all metal components of the frame shall be processed to remove all extraneous metal including burrs and rough or sharp edges.

3.4.4 Cementing of rubber gaskets and anti-skid floor surfacing.- Cementing shall be accomplished in accordance with the adhesive manufacturer's recommendation after the applied paint finish has thoroughly dried.

3.4.5 Stitching machine.-

3.4.5.1 Types of stitches.- Stitching shall conform to FED-STD-751 and shall be of the types shown in table III for the applications shown.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:30Z
Check the source to verify that this is the currentversion before use.

TABLE III.- Types of stitches

Application	Stitch type
For all stitching except stitching indicated by "Z" on drawings.	Type 301, 5 to 7 stitches per inch.
For all stitching indicated by "Z" on drawing.	Type 401, 5 to 7 stitches per inch. Chain portion of stitching shall not appear on outside of connecting annex cover or tent cover.

3.4.5.2 Thread breaks.- Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301 and not less than 1-1/2 inches at each break on stitch type 401.

3.4.5.3 Stitching ends.- Stitching ends shall be overstitched not less than 1 inch on stitch type 301, except where ends are turned under in a hem, held down by other stitching or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking are performed automatically, at least 3 or more typing, overlapping or backstitches shall be used to secure the ends of stitching.

3.4.5.4 Seam allowance.- Seam allowances shall be maintained with seams sewn so that no runoffs, twists, pleats, puckers or open seams result. All thread ends shall be trimmed. Thread tension shall be maintained so that there shall be no loose stitching.

3.4.5.5 The addition of any lubricant to the polyester thread prior to or during the sewing operation is prohibited.

3.4.6 Attachment of slide fasteners.- The length of slide fastener chains shall be such that after the fastener is sewed on, the tape shall not be puckered and the slider shall operate freely. Care shall be exercised to trim all thread ends and maintain specified distances between edges of fabric attached to slide-fastener tape so that there will be no interference with the operation of the slider.

3.4.7 Setting of snap fasteners.- If a hole is punched before inserting the male part of the style 1 snap fastener, it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fasteners shall be securely clinched.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:30Z
Check the source to verify that this is the current version before use.

3.4.8 Setting of grommets.- Holes punched to receive grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the materials.

3.5 Finish, frame components.- Except as otherwise specified herein, all surfaces of frame components, including supports and flooring, shall be prepared for painting and shall be painted in accordance with requirements hereinafter specified. Jack screws and other surfaces shall not be primed or enameled where the function may be adversely affected by paint films. Painting of interior surfaces of pipe and tubing is not intended but will be permitted. Top and bottom surfaces of flooring shall be painted prior to application of anti-skid floor surfacing. Also, all surfaces of the gable assemblies, requiring rubber gaskets, shall be painted prior to application of the rubber gaskets.

3.5.1 Surface preparation.- Aluminum surfaces requiring paint shall be prepared for painting in accordance with MIL-C-5541. All other metal surfaces requiring paint shall be thoroughly cleaned and dry prior to painting.

3.5.2 Painting.- A uniform coat of primer specified in 3.3.1.5.1 shall be applied to all prepared surfaces requiring paint. After thorough drying, a uniform coat of enamel specified in 3.3.1.5.2, shall be applied to the primed surfaces. The final applied finish shall show uniform coverage and shall be free of runs, sags and foreign inclusion.

3.6 Marking for identification.-

3.6.1 Marking of frame assembly.- Marking for identification of the frame assembly shall conform to the unit marking requirements of MIL-STD-130.

3.6.2 Marking of connecting annex cover and tent cover.- All markings and labels shall conform to DDD-L-20.

3.6.2.1 The letters "U.S." on the connecting annex cover and tent cover and special markings on the tent cover shall conform to type IV, class 9 in the size characters and the locations shown on the drawings. Class 9 markings shall be clearly legible after subjection to accelerated weathering.

3.6.2.2 Identification label.- Identification labels shall be applied to the connecting annex cover and tent cover in the location(s) shown on the drawing(s) and shall conform to type IV, class 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

3.6.2.3 Instruction label.- Labels of erection instructions shall conform to type II, class 7 and shall be stitched to the connecting annex cover wall and the tent cover in the locations shown on the drawings. The size of the label shall be borderline to borderline, 10 by 14 inches, plus or minus 1/4 inch, with a minimum 1/2-inch margin outside of the borderline on all sides. Information on the label shall be a proportionate copy of Drawing 5-4-827.

3.7 Workmanship.-

3.7.1 Metal components.- Metal components of the annex frame and covers, where applicable, shall be free of burrs, sharp edges, corrosion, and shall not be broken or malformed.

3.7.2 Welding.- All welds shall have a uniform bead contour throughout, and shall be free from irregularities, craters, undercut, surface oxidation, pipes and porosity. The metal in and adjacent to the welded area shall be free from cracks, holes and imperfections indicative of poor fusion.

3.7.3 Textile components.- Textile components shall be free of holes, cuts, tears or cloth defects such as smashes, weak places, broken or missing yarns. Webbing and tapes shall contain no frayed or scalloped edges and rope components shall be free of cuts and abrasions.

3.7.4 Assembly.- The complete end item shall be capable of assembly without further modification. All mating parts shall align as intended without the need for impact type tools or pry bars to align mating components.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article inspection.- When a first article is required, it shall be examined in accordance with 4.3.2.1 and dimensions specified. The presence of any visual defect, any dimension not within specified requirements, shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:30Z
Check the source to verify that this is the current version before use.

4.3 Inspection of materials and components.- In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the specified requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.3.1 Process examination.- Examination shall be made to determine that the operations in table IV are accomplished in accordance with specified requirements. Whenever nonconformance is noted correction shall be made to affected items and lot in process.

TABLE IV.- Process examination

Operation	Requirement	Requirement paragraph
Welding	Inert gas shielded process and surface cleaning	3.4.1
Cementing of gaskets and anti-skid flooring	After paint is thoroughly dry	3.4.4
Stitching	No lubrication of polyester thread	3.4.5.5
Punching of holes for fasteners	Smaller than O.D. of fastener	3.4.7
Punching of holes for grommets	Smaller than O.D. of grommet barrel	3.4.8
Painting	Prior to cementing of gaskets and anti-skid flooring	3.5
	Surface preparation	3.5.1
	Drying of primer before enameling	3.5.2

4.3.2 End product inspection.- A lot shall consist of the number of annexes submitted for acceptance at one time. The sample unit for this inspection shall be one complete assembled annex.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:30Z
Check the source to verify that this is the current version before use.

4.3.2.1 Visual examination.- Examination shall be made of the end item for the defects listed in table V. The inspection level shall be level I, and the acceptable quality level (AQL), shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE V.- Classification of defects

Examine	Defect	Classification Major	Minor
Assembly	Part missing	X	
	Parts not assembled properly	X	
	Parts do not fit	X	
	Tubing dented, bent	X	
	Assembly instructions missing	X	
Flooring	Mismatched	X	
	Nonskid not cemented	X	
Zipper	Teeth missing	X	
Jack	Burrs, nicks, rust		X
Assembly markings	Omitted, illegible, incomplete, incorrect, incomplete, or not as specified	X	
Identification marking	Omitted, illegible, incorrect, incomplete, or not as specified		X

4.3.2.2 Dimensional examination.- Inspection shall be made of the end item to determine compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery.- An examination shall be made to determine that preservation, packaging, packing and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified in table VI. The sample unit shall be one shipping container fully prepared for delivery except that it need not be sealed. The lot shall be the

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:30Z
Check the source to verify that this is the current version before use.

number of containers offered for delivery at one time. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The inspection level shall be II with an AQL of 4.0 expressed in terms of defects per hundred units.

TABLE VI.- Preparation for delivery inspection

Examination	Defect
Preservation	Exposed, uncoated, ferrous metal surfaces, not coated with preservative.
Markings (exterior container)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of container, or loose wiring or strapping, bracing or blocking or anchoring inadequate, improper or missing; components improperly secured; bulging or distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified.

5.1.1 Level A.- Each annex shall be disassembled in such a manner as to minimize cubage and the attaching hardware shall be secured to the mating parts. All exposed, uncoated, ferrous metal surfaces shall be coated with type P-7 or P-9 preservative of MIL-P-116. The annex cover shall be compactly folded, with the erection instruction label exposed, placed within the cover provided and the cover secured with the rope ties.

5.1.2 Level C.- The annex shall be preserved and packaged to afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A.- Each annex, preserved and packaged as specified in 5.1, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104. Anchoring of contents and closure and strapping shall be in accordance with the crate specification and appendix thereto.

5.2.2 Level B.- Each annex, preserved and packaged as specified in 5.1, shall be packed in a sheathed, nailed wood crate as specified in 5.2.1, except that the waterproofing shall not be required.

5.2.3 Level C.- Each annex, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The annex covered by this specification is intended to be used as a sheltered passageway between the 3 semi-trailer vans of the Printing Plant, Special Warfare, Semi-Trailer Mounted. The tent cover is used as a protective wrap for the annex cover during storage and transportation of the annex.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required (see 3.1, 4.2 and 6.3).
(c) Selection of the applicable levels of preservation, packaging and packing (see 5.1 and 5.2).

* 6.3 First article.- When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be an initial production item. The first article should consist of one completely assembled and finished Printing Plant Annex. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 For access to a standard shade of the polyester rope and polyester thread, address the procuring officer issuing the invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.

6.5 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 3610-A208

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-433-699/9680

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:30Z
Check the source to verify that this is the current version before use.