MIL-P-43484A (GL)
AMENDMENT-2
13 September 1977
SUPERSEDING
Amendment-1
21 July 1975

MILITARY SPECIFICATION

PRINTING PLANT, SPECIAL WARFARE, SEMITRAILER MOUNTED

This amendment forms a part of Military Specification MIL-P-43484A (GL) dated 24 June 1971.

PAGE 2

2.1, under FEDERAL SPECIFICATIONS, title of PPP-T-60. Delete and substitute "Tape: Packaging, Waterproof."

Title of PPP-B-621. Delete "Box" and substitute "Boxes".

Under MILITARY SPECIFICATIONS, title of MIL-P-116. Delete "Preservation" and substitute "Preservation-Packaging".

Title of MIL-B-131, after "Flexible". Insert ", Heat Sealable"

Delete "MIL-W-6110 - Wood, Determination of Moisture Content of"

Add "MIL-S-62049" - Semitrailer, Van, For Installation of Special Equipment, Military Design.

PAGE 3

2.1, under MILITARY STANDARDS. Delete MS Standards in their entirety and substitute the following:

MS 3057 - Clamp, Cable, Electrical Connector
MS 3106 - Connector, Plug, Electric, Straight
MS 15795 - Washer, Flat Metal, Round, General Purpose
MS 20257 - Hinge, Continuous
MS 20426 - Rivet, Solid, Countersunk 100 Degrees, Precision Head, Aluminum and Aluminum Alloy
MS 20470 - Rivet, Solid-Universal Head, Aluminum and Aluminum Alloy
MS 20600 - Rivet, Blind, Structural Pull Stem, Self-Plugging, Protruding Head Type
MS 20601 - Rivet, Blind, Structural Pull Stem Self-Plugging, 100 Degree Flush Head, Type II, Class 2
MS 21919 - Clamp, Cushioned Support Loop-Type, Aircraft
MS 24628 - Screw, Tapping, Thread Cutting, Types D, F, G or T, Flat Countersunk Head, Cross-Recessed, Steel, Corrosion Resisting

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

PAGE 3 (Cont'd)

MS 27183 - Washer, Flat-Round, Steel, Cadmium Plated, General Purpose
MS 35058 - Switch, Toggle One Pole, Sealed Toggle
MS 35190 - Screw, Machine 82 Degree Flat Countersunk Head, Cross-recessed, Carbon Steel, Cadmium Plated, UNC-2
MS 35206 - Screw, Machine Pan Head, Cross-recessed, Carbon Steel, Cadmium Plated, UNC-2A
MS 35307 - Screw, Cap, Hexagon Steel, Corrosion-Resisting, Passivated, UNC-2A
MS 35333 - Washer, Lock, Flat Internal Tooth
MS 35338 - Washer, Lock-Spring, Helical, Regular (Medium) Series
MS 35649 - Nut, Plain, Hexagon, Machine Screw, UNC-2B
MS 35650 - Nut, Plain, Hexagon, Machine Screw, UNF-2B
MS 51861 - Screw, Tapping, Thread Forming, Type Ab, Pan Head, Cross-Recessed
MS 51922 - Nut, Self-Locking, Hexagon Prevailing Torque, General Purpose, 250 Deg. F, UNC-2B and UNF-2B
MS 51957 - Screw, Machine Pan Head, Cross-Recessed, Corrosion-Resisting Steel, Passivated, UNC-2A
MS 51958 - Screw, Machine Pan Head, Cross-Recessed, Corrosion-Resisting Steel, UNF-2A
MS 51959 - Screw, Machine Flat Countersunk Head, 82 Deg., Cross-Recessed, Corrosion Steel, UNC-2A
MS 90725 - Screw, Cap, Hexagon Head, Steel, Grade 5, Cadmium Plated, UNC-2A

PAGE 4

2.2, line 2. Delete "otherwise indicated" and substitute "a special issue is identified."

Line 11. After "Testing" insert "AND"

Line 13. Delete "D 2016-65" and substitute "D2016."

PAGE 8

* TABLE II, Bulletin board, description. Delete and substitute:

"Bulletin Board, 18 x 24 inches, cork composition surface and oak frame, Arthur Brown No. 163946."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

PAGE 9

* TABLE II, Composing Machine, item and description. Delete and substitute:

"Phototypesetting machine	Machine, phototypesetting: direct-entry, keyboard input, equipped with magnetic diskette playback module. Varityper Corp., Comp./Set Model 560 with 504 playback module, including phototypesetting paper table top processor."

* TABLE II, Safelight, darkroom description. Delete and substitute:

"Safelight, darkroom, photographic, double swivel bracket for wall, ceiling or bench mounting, for use with 5 1/2 inch dia. filters; equipped with in-line switch and plug cap, and the following:

a. 15-watt frosted, medium screw, 115v incandescent lamp

b. Wratten OA greenish-yellow filter

c. Wratten series/red filter

Eastman Kodak Co., Kodak adjustable safelight model B"

PAGE 11

* TABLE II, under item, description and location. Delete Mixer in its entirety.

Duplicating machine, description, last line: Delete "LW" and substitute "L".

PAGE 13

* TABLE II, under item, description and location. Delete Scale dial indicating in its entirety.

Typewriter, description, line 1. Delete "13" and substitute "15".

PAGE 14

* TABLE II, Water pump and tank, description. Delete and substitute: "Pump and tank, 5 GPH shallow well type, Sears Roebuck 42H2925N"

* TABLE II, Platemaker, description. Delete and substitute: "Platemaker flip-top Nu Arc Model No. FT 18V-1".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

PAGE 15

Table III, under "Nomenclature", line 2. Delete "MIL-S-45311" and substitute "MIL-S-62049".

PAGE 19

4.2, line 1. Delete "it" and substitute "the printing plant".

Line 5. Delete "preproduction sample" and substitute "first article".

4.3.2 Delete and substitute:

"4.3.2 Testing for moisture content of wood. Wood components shall be tested for moisture content in accordance with ASTM D2016 to determine compliance with 3.6.12. The lot shall consist of all components ready for assembly and submitted for inspection at one time. The sample unit shall be one component. When testing is performed by the electronic moisture meter method, three determinations shall be made on each sample unit and the result shall be the average of the three determinations. The inspection level shall be S-1 with an AQL of 4.0, expressed in terms of defects per hundred units. Failure to comply with the moisture content requirement of 3.6.12 shall be cause for rejection of the lot."

PAGE 20

Table IV, under "Requirement", line 1. Delete "cleaning" and substitute "precleaning."

4.3.4, title. Delete "product" and substitute "item".

4.3.5. Delete and substitute:

"4.3.5 End item testing. Each printing plant shall be tested in accordance with 4.4.1 through 4.4.5 and failure to pass any test shall be cause for rejection of the item. The test specified in 4.4.6 shall be performed on one production unit (see 6.5), and failure to pass this test shall be cause for rejection of the item."

4.4.1, lines 3 and 4. Delete second sentence and substitute: "The vans shall be towed at a sustained speed of 50 miles per hour (mph) over improved roads and at an average speed of 20 mph over unimproved roads."

Line 10. Delete "Any nonconformance with water tightness or"

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

PAGE 21

4.4.2, line 1. Delete "the printing plant" and substitute "Each van"; also after "to" insert "a".

4.4.3, line 2. Delete "A.C." and substitute "hertz"

PAGE 24

5.1.1.5.1, line 2, before "class 1". Insert "type IV".

5.1.1.6, (c), before "grade A". Insert "type II,".

5.1.1.7, line 2, before "MIL-B-131". Insert "class 1 of". Before "class 1", insert "type IV".

PAGE 25

* 6.2, (c). Delete in its entirety.

PAGE 26

Add, new para. 6.5 as follows:

"6.5 End item tests. Performance of test 4.4.6 should be limited to one successful demonstration of compliance with the requirements of this specification for each contract."

* The margins of this amendment are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - GL

Review activities:

Army - MD

DLA - GS

Preparing activity:

Army - GL

Project No. 3610-A281

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.