MIL-S-43483A(GL)
28 January 1986
SUPERSEDING
MIL-S-43483(GL)
15 March 1967

MILITARY SPECIFICATION

STENCIL DUPLICATING PRINT KIT, HAND STAMP: MAN-PACKED

This specification is approved for use within the Natick Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size portable duplicator kit for field use (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

H-B-643	-	Brush, Acid Swabbing
L-P-375	-	Plastic Film, Flexible, Vinyl Chloride
L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
L-T-90	-	Tape, Pressure Sensitive, Adhesive, (Cellophane and Cellulose Acetate)
L-P-390	-	Plastic, Molding and Extrusion Material, Polyethelene and Copolymers (Low, Medium and High Density)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Center, Natick MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 7520

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimitd.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:31Z
Check the source to verify that this is the currentversion before use.

V-T-285	-	Thread, Polyester
GG-D-458	-	Dispenser, Pressure Sensitive Adhesive Tape
GG-S-792	-	Stylus, Duplicating Stencil
TT-C-621	-	Correction Fluid, Duplicating Machine Stencil
TT-E-527	-	Enamel, Alkyd, Lusterless
TT-I-564	-	Ink, Stencil, Duplicating Machine, Black
UU-S-1205	-	Stencil, Duplicating Machine
MMM-A-121	-	Adhesive, Bonding Vulcanized Synthetic Rubber to Steel
MMM-A-1617	-	Adhesive, Rubber Base, General Purpose
PPP-B-636	-	Box, Shipping Fiberboard

MILITARY

MIL-R-6855	-	Rubber, Synthetic, Sheets, Strips, Molded or Extruded Shapes
MIL-S-8802	-	Sealing Compound, Temperature-Resistant, Integral Fuel Tanks and Fuel Cell Cavities, High-Adhesion
MIL-A-8625	-	Anodic Coatings, For Aluminum and Aluminum Alloys
DOD-P-15328	-	Primer, (Wash), Pretreatment (Formula No. 117 for Metals) (Metric)

STANDARDS

FEDERAL

FED-STD-595	-	Colors
FED-STD-751	-	Stitches, Seams and Stitching

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of US Military Property
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-810	-	Environmental Test Methods and Engineering Guidelines

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

5-7-104	-	Stencil Duplicating Print Kit; Hand Stamp; Man-Packed; Illustration
5-7-105	-	Stencil Duplicating Print Kit; Hand Stamp; Man-Packed; Carrying Case Assembly
5-7-106	-	Stencil Duplicating Kit; Hand Stamp; Man-Packed; Shell, Body, Case

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

5-7-107 - Stencil Duplicating Kit; Hand Stamp; Man-Packed; Shell, Lid, Case
5-7-108 - Stencil Duplicating Kit; Hand Stamp; Man-Packed; Pads, Cushion, Case
5-7-109 - Stencil Duplicating Kit; Hand Stamp; Man-Packed; Details

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

OTHER GOVERNMENT DOCUMENTS

JOINT COMMITTEE ON PRINTING (JCP) PUBLICATIONS

JCP-G-20 - Government Paper Specification Standards

(Copies may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 256 - Impact Resistance of Plastics and Electrical Insulating Materials

D 543 - Resistance of Plastics to Chemical Reagents

D 638 - Tensile Properties of Plastics

D 648 - Deflection Temperature of Plastics Under Flexural Load

D 785 - Rockwell Hardness of Plastics and Electrical Insulating Materials

D 792 - Specific Gravity and Density of Plastics by Displacement

D 1623 - Tensile and Tensile Adhesion Properties of Rigid Cellular Plastics

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings. Material and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed end item complies with all the provisions of this document.

3.3 Alternate materials and components. Components offered as equivalent to components specified herein and on the reference drawings as a specific manufacturer's part number or equal, shall be functionally equal to the specified component. The incorporation of such a component in design of the specified end product shall not require modification to any other components, unless such modification is specifically approved by the contracting officer. Prior to commencing production the contractor shall submit for the contracting officer's approval, a list identifying each alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data, does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3.1 Pressed laminated sheets (ABS plastic). Pressed laminated sheets shall be formed of polymers or blends of polymers, produced from acrylonitrile butadienestyrene. The polymer material shall not be adulterated, extended, or in any way modified other than by pigments. Pigments used shall not exceed 5 percent by weight of the volume of the polymer material. All materials used for processing into pressed laminated sheets shall be virgin stock. Virgin stock shall be material that has not been processed into a finished product prior to use in fabrication of the case. The physical requirements shall be as indicated in table I when tested in accordance with the ASTM test methods indicated.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:31Z
Check the source to verify that this is the currentversion before use.

TABLE I. Physical requirements for pressed laminated sheets

Characteristic	ASTM method	Physical requirement
Tensile strength, minimum, p.s.i	D 638	3500
Modulus of elasticity in tension, minimum, p.s.i	D 638	160,000
Rockwell Hardness, "R" scale, minimum	D 785	80
Heat deflection, temperature under load, minimum (264 p.s.i., fiber stress)	D 648	180°F
Impact strength (Izod), minimum foot pounds per inch of notch, at:		
23°±2°C (73.4°± 3.6°F)	D 256	5.5
-40°± 2°C (-40° ± 3.6°F)	(Method A)	2.0
Specific gravity:		
Minimum	D 792	1.0
Maximum	(Method A)	1.2
Chemical resistance, 40-hour immersion in heptane at 32° ± 2°C, weight change, maximum percent	D 543	5.0

3.3.1.1 Color. Unless otherwise specified (see 6.2), color of the laminated press sheets shall match olive drab color No. 24087 of FED-STD-595.

3.3.2 Polyethylene pads. The polyethylene used in the fabrication of the cushion pads shall conform to type I, class L, grades 1, 2 or 3 of L-P-390. The pads shall be a cellular material with closed cell structure, made by an extrusion process. Color shall be within a range from charcoal gray to black. The physical requirements shall be as indicated in table II, when tested in accordance with the methods indicated.

TABLE II. Physical requirements for polyethylene cushion pads

Characteristic	Test method	Physical requirement
Density, lbs. per cubic ft.	Measurement	1.8 to 2.6
Tensile strength, lbs. per sq. in.	ASTM D 1623 (1/4 by 1/4 in. sample)	20 to 30

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

TABLE II. Physical requirements for polyethylene cushion pads (cont'd)

Characteristic	Test method	Physical requirement
Volume change, on heat aging 140°F for 7 days	Measurement	Less than 1 percent

3.3.3 Plastic film.

3.3.3.1 Polyethylene plastic film. Polyethylene plastic film shall be type I, grade A, B or C, finish 1 of L-P-378.

3.3.3.2 Vinyl plastic film. Vinyl plastic film shall be type I, class 1 of L-P-375.

3.3.4 Adhesive.

3.3.4.1 Synthetic rubber to metal. Synthetic rubber to metal adhesive shall be in accordance with MMM-A-121.

3.3.4.2 Rubber, synthetic and reclaimed rubber base. Synthetic and reclaimed rubber base adhesive shall be type I or II as applicable of MMM-A-1617.

3.3.5 Sealing compound. Sealing compound shall be class B-2 of MIL-S-8802.

3.3.6 Gasket material. Gasket material shall be synthetic rubber conforming to class 2, grade 40 of MIL-R-6855.

3.3.7 Thread, polyester. The thread used for all stitching shall conform to type I or II, class 1, size FF of V-T-285. The color shall match shade S-1, cable no. 66022 (see 6.5).

3.4 Design and construction. The design and construction of all components and the complete assembly thereof shall conform to the requirements specified herein and to the design, details and dimensions shown on the drawings referenced in 2.1. The major components of the kit shall be as specified in table III.

TABLE III. Kit, major components

Quantity	Nomenclature	Requirement paragraph
1 each	Case, carrying	3.5.1
See 3.5.1.9	Instruction cards	3.5.1.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

TABLE III. Kit, major components (cont'd)

Quantity	Nomenclature	Requirement paragraph
1 each	Stencil duplicator (rocker type) with metal base	3.5.2
1 each	Brush, acid swabbing	3.5.2.1
2 each	Pen, stylus, double ends	3.5.2.2
4 quires	Stencils (24 stencils per quire)	3.5.3.1
15 pads	Paper, 5-1/4 by 8 inches (100 sheets to pad)	3.5.3.2
2 each	Ink, duplicating, black (1/2 pound can, unit pack)	3.5.3.3
1 each	Correction fluid (1-ounce can)	3.5.3.4
1 each	Tape, cellophane, transparent, 3/4-inch width	3.5.3.5

3.4.1 Welding. Welding shall be accomplished by the inert-gas-shielded arc welding process. Finished welds shall present a uniform bead contour and shall be free of undercut, surface cavities, and cracks in weld metal or heat affected zones.

3.4.2 Metal forming. Aluminum extrusions shall be formed to the contour of the carrying case shells in such a manner as to be free from chatter marks, wrinkles, blemishes, burrs, and visible distortion in cross section. The carrying case handle clips shall be free of cracks, burrs, and sharp edges.

3.4.3 Laminated sheet forming. Both shells of the carrying case shall be formed in such a manner to be free from wrinkles, blisters, blemishes, or other visible defects. The thickness of the formed shells shall not be reduced by more than 1/16 inch at any point on the formed shells.

3.4.4 Sealing and cementing. Sealing and cementing shall be accomplished in accordance with the adhesive manufacturer's recommendations without evidence of excess adhesive or contamination of surrounding surfaces.

3.4.5 Stitching, machine. Machine stitching shall be done with thread specified in 3.3.7. The stitching shall be five to seven stitches per inch conforming to type 301 of FED-STD-751. Thread breaks in stitch ends shall be secured by stitching back of breaks not less than 1 inch. There shall be no loose stitching and thread ends shall be trimmed. The stitched items shall be free from needle chews, puckers or open seams.

3.4.6 Riveting. Riveting shall be accomplished using blind rivets shown on the drawings. Riveted components shall be drawn tight with the rivet head in full contact with the mating surface and free of sharp or rough edges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

3.5 Details of components. All component parts of the duplicator kit furnished under this document shall be interchangeable with like parts of all duplicator kits furnished under any one contract or purchase order.

3.5.1 Carrying case. The carrying case shall consist of a lid and body hinged together to house all the expendable and nonexpendable components required.

3.5.1.1 Body and lid. The body and lid shells shall be vacuum formed from material specified in 3.3.1 and to dimensions shown on Drawings 5-7-106 and 5-7-107 respectively, without addition radius corner reinforcement, to meet the impact requirement in 3.7.2.

3.5.1.2 Extrusions. The body and lid extrusions shall be as shown on Drawing 5-7-109. The extrusions shall be fitted together in such a manner that when hinged together, the lip of the lid extrusion is centered within the channel of the body extrusion and with the welded joint located as shown on Drawing 5-7-105. Each extrusion shall be secured to the appropriate case shell by proper application of the sealing compound specified in 3.3.5, and by staking shown on Drawing 5-7-105.

3.5.1.3 Hinge. The body and lid extrusion shall be joined by a nonmagnetic, continuous, corrosion resisting steel piano hinge; 0.050 inch thick; 1-3/4 inch open; 0.125 inch nonmagnetic, corrosion resisting steel pin, and 5/8 inch joint (see 6.4).

3.5.1.4 Catches and mounting plate. The catches shown on Drawing 5-7-105 shall be concealed spring loaded, draw pull type with a hook link to engage the lid extrusion. The catch mounting plate shall be designed for retention between the body extrusion and body shell by means of serrations in the mounting plate engaging serrations in the body extrusion. The catch and mounting plate shall be joined by means of a hinge pin. All parts of the catches and mounting plate shall be made from nonmagnetic corrosion-resisting steel (see 6.4).

3.5.1.5 Handle. The handle shown on Drawing 5-7-105 shall have not less than a 4-1/2 inch by 1-7/8 inch grip opening and an olive drab colored vinyl grip over a solid aluminum handle, free to pivot within aluminum mounting flanges (see 6.4). The configuration shall be as shown on Drawing 5-7-105.

3.5.1.6 Cushion pad. The cushion pad shall be as shown on Drawing 5-7-108 and shall be made from material specified in 3.3.2. The finished pad shall be one piece construction or an assembly of pieces bonded together, using reclaimed rubber cement applied as directed by the cement manufacturer, thereby forming a one piece unit. The top face surface and the stencil duplicator cavity surfaces of the finished pad shall be sealed to close surface pores by the heat sealing method. All dimensions of the assembled pad shall be such as to insure a snug fit within the carrying case, and a snug fit between stored components and the pad cavities.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

3.5.1.7 Gasket. The gasket shown on Drawing 5-7-105 shall consist of a single piece of tubular rubber, 7/32 inch O.D. by 1/8 inch I.D., with the ends joined by a 1/8 inch diameter by 2 inches long solid rubber connector inserted 1 inch deep into each end of the tube. The tubular rubber and connector shall each be made from material specified in 3.3.6. The tubing and connector shall be secured together with type II adhesive specified in 3.3.4.2, with the cemented joint located as shown on Drawing 5-7-105. The assembled gasket shall lay within the groove of the body extrusion without visible stretch or bulge and shall be retained in position with either adhesive specified in 3.3.4.2.

3.5.1.8 Stencil retainer. The stencil retaining assembly shown on Drawing 5-7-105 shall be cemented to the inside of the lid shell using methyl-ethyl-ketone or acetone. The strap assembly shall consist of a hook and pile fastener tape sewn to cotton tape (see 6.5) and secured to the stencil retainer by staples as shown on Drawing 5-7-109.

3.5.1.9 Instructions cards. The contractor shall submit for the contracting officer's approval, written, typewritten, or printed instruction sheets relating to the proper use and maintenance of the furnished stencil duplicator. The approval sample shall be in the English language, and may include line illustrations to compliment the text. The instructions shall include all information required for the preparation and attachment of stencils; the replacement of ink pads, and inking of the ink pad. Upon approval by the contracting officer, the approved instruction sheet shall be reproduced by the supplier on white bond paper in English, French, Spanish, and Arabic, with each language on a separate sheet. The English language instructions shall be printed on one side of the sheet only. The foreign language instructions may be printed on both sides of the sheet and shall be of a size to fit in the space indicated on Drawing 5-7-104, after laminating within plastic film.

3.5.1.9.1 Lamination of instruction sheets. The English language instructions shall be laminated between two sheets of 2 mil vinyl plastic film specified in 3.3.3.2. The foreign language instructions shall be laminated within two sheets of 6 mil polyethylene film specified in 3.3.3.1. The text, and line illustrations when applicable, shall be clearly legible to normal vision at a distance of 16 to 18 inches in daylight, after the instruction sheets have been laminated in the plastic film.

3.5.1.9.2 Attachment of English language instructions. The English language instruction sheet, laminated within vinyl-plastic film, shall be cemented to the case lid using methyl-ethyl-ketone or acetone. Location shall be as shown on Drawing 5-7-104.

3.5.2 Stencil duplicator. The stencil duplicator shall be manually operated rocker type, capable of printing an area up to 5-1/4 by 7-1/8 inches. A neoprene cork gasket shall be incorporated in the stencil retainer frame, to

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

aid in maintaining stencils in proper alignment. The neoprene cork gasket shall be secured in location by adhesive specified in 3.3.4.1. The duplicator shall be furnished without ink in the reservoir or ink pad, and with a nonmagnetic metal storage base or tray. The tray mounted duplicator assembly shall have maximum overall dimensions of 8-3/4 inches long, 6-1/4 inches wide, and 5-3/4 inches high, including a minimum 2-3/4 inches high by 1-1/2 inches diameter contoured handle. The tray mounted duplicator shall be a snug fit in the cushion pad recess provided in the carrying case.

3.5.2.1 Brush, acid swabbing. The acid swabbing brush shall conform to type II, class 2, size 2 of H-B-643. The brush shall be furnished in a tooth brush type plastic container having a slip-type shouldered joint around its transverse axis at the middle of the container. The container, with brush, shall be stored as shown on Drawing 5-7-104.

3.5.2.2 Pen, stylus, double ends. Duplicating stencil stylus shall be double end style conforming to type II, style A of GG-S-792. Each stylus shall be furnished in a clear plastic cylinder with press on cap and shall be stored in the locations shown on Drawing 5-7-104.

3.5.3 Expendable supplies. The expendable supplies specified hereinafter shall be furnished and stored within the spaces provided in the carrying case as shown on Drawing 5-7-104, in the quantity indicated in 3.1 for each item.

3.5.3.1 Stencils. Stencils shall be in accordance with UU-S-1205, modified as to size and scale number, for use with the duplicator specified in 3.5.2. Each quire shall be packaged as specified in UU-S-1205 a folded box and then heat sealed in 2-mil plastic film specified in 3.3.3.2. Excess air shall be expelled prior to final closure, except that vacuum packaging shall not be permitted.

3.5.3.2 Writing pads. Paper for writing pads shall be chemical-wood, bond, white, translucent, substance 12 in accordance with Commercial Standard JCP-G-20. The paper, furnished in pads of 100 5-1/4 by 8 inch sheets, shall be cemented on one of the 5-1/4 inch sides with padding cement without padding cloth or strawboard backing. Each pad shall be heat sealed in 2 mil plastic film specified in 3.3.3.1. Excess air shall be expelled prior to final closure.

3.5.3.3 Ink. Ink shall be type IV, class 2 of TT-I-564, Color No. 37038 of FED-STD-595. Ink shall be furnished in 1/2 pound cans with screw caps. The can configuration shall be similar to that shown on Drawing 5-7-104.

3.5.3.4 Correction fluid. Correction fluid and the 1-ounce unit package shall conform to TT-C-621 except that the container shall be of metal in lieu of glass and shall be labelled to indicate contents.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

3.5.3.5 Tape, cellophane, transparent. Cellophane tape shall be pressure sensitive transparent tape of L-T-90, furnished in 3/4-inch width by 1296 inch length, coiled on a 1-inch core, mounted in a dispensing frame conforming to type VI, class 1 of G-D-458.

3.6 Finish.

3.6.1 Pressed laminated sheets. The carrying case body and lid shall have a uniform haircell exterior surface finish and a uniformly smooth interior surface finish.

3.6.2 Metal surface. Metal surfaces of the carrying case shall be finished in accordance with the applicable requirements hereinafter specified, so that all visible surfaces, after assembly, shall have a lusterless olive drab color, approximating the color of the case body and lid shells, or a lusterless black color.

3.6.2.1 Aluminum surfaces. Aluminum component shall be finished in accordance with either of the following options:

Option A. Render the surface lusterless by chemical or mechanical treatment, followed by anodizing in accordance with type II, class 2 of MIL-A-8625, except that rivet heads may be spot coated, after setting, with enamel conforming to TT-E-527.

Option B. Thoroughly clean surfaces and wash coat with primer in accordance with MIL-P-15328, followed by a coat of enamel conforming to TT-E-527, except that rivet heads may be spot coated, after setting, with enamel conforming to TT-E-527.

3.6.2.2 Corrosion resisting steel surfaces. Corrosion resisting steel surfaces shall be finished in accordance with either of the following options:

Option A. Render the surface lusterless by chemical treatment or grit abrading followed by a chemical or fused salt bath treatment, to produce a lusterless finish.

Option B. Render the surface lusterless by chemical treatment or grit abrading and then wash coat with primer in accordance with MIL-P-15328, followed by a coat of enamel conforming to TT-E-527.

3.7 Performance.

3.7.1 Lid closure. The lid closure shall be such that when tested in accordance with 4.5.1, the lid shall remain partially open (1/2 to 1-1/4 inches) under its own weight, until additional force is applied to effect complete closure. The engagement of the catches shall be such that there is no evidence of lid spring back when the catches are fully engaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

3.7.2 Extreme temperature and impact. The complete duplicator kit, fully assembled with all components, shall withstand exposure to extreme temperatures ranging from plus 160°F to minus 40°F (see 4.5.2.1 and 4.5.2.2), and the impact test specified in 4.5.3, without evidence of deterioration or fracturing, and without adversely affecting the watertightness requirement in 3.7.3.

3.7.3 Watertightness. The carrying case shall be watertight to the extent that no more than 1 ounce of water is visible inside the carrying case when submerged in water (see 4.5.4).

3.8. Marking. The duplicator kit shall be marked, on the inside surface of the case lid, with the manufacturer's identification in accordance with MIL-STD-130.

3.9 Workmanship. The finished duplicator kits shall be free from dents, nicks, burrs, slivers and punctures.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the perfomance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3.1 and 4.4.3.2 and tested as specified in 4.5.1 thru 4.5.4. The presence of any defect or failure of any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of the referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Examination shall be made at appropriate stages of manufacture to determine that the operations in table IV are accomplished by the process indicated. Whenever nonconformance is noted, correction shall be made to the applicable process and all affected items shall be brought into compliance.

TABLE IV. In-process examination

Operation	Process	Requirement paragraph
Welding	Inert-gas-shielded arc welding process	3.4.1
Forming of case body and lid	Vacuum formed	3.5.1.1
Sealing of cushion pads	Heat sealing	3.5.1.6
Metal finishing	Pretreatment and priming (as applicable)	3.6.2.1 and 3.6.2.2

4.4.3 End item inspection.

4.4.3.1 Visual examination. The end item shall be examined for the defects listed in table V. The lot size shall be expressed in units of kits. The sample unit shall be one complete duplicating kit. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE V. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Body and lid not specified color		X
	Any wrinkle, blister, or blemish on body or lid		X
	Body and lid not haircell finish on exterior surfaces or not smooth finish on interior surfaces		X
	Not specified color		X
Design, construction, and workmanship	Component missing or not as specified	X	
	Component malformed, buckled, or bent	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Design, construction, and workmanship (cont'd)	Functioning component inoperable or requires excess pressure to operate	X	
	Body and lid extrusion not centered one within the other	X	
	Body and lid extrusions not staked to shells	X	
	Body and lid extrusions staked at less than specified intervals		X
	Any split, fracture, puncture, or dent	X	
	Sharp edge or burr	X	
Cushion pad	Not one piece construction or not a bonded assembly	X	
	Not a snug fit in carrying case	X	
	Stored components free to shift in pad cavities	X	
	Not heat sealed where specified		X
Instruction cards	Not individually laminated within plastic film		X
	Any card missing, illegible, or incorrect	X	
	English language card not cemented to case lid		X
Stencil	Any quire of stencils not individually sealed within plastic film		X
	Vacuum sealed	X	
	Excess air not expelled		X
Writing pads	Any writing pad not individually sealed within plastic film		X
	Excess air not expelled		X
Gasket	Bulged or stretched	X	
	Not cemented to extrusion	X	
	Joint not properly located	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Metal forming	Chatter marks, wrinkles, blemishes		X
	Cross sectional deformation (formed aluminum extrusions)		X
Sealing and cementing	Excess adhesive on surrounding surfaces		X
Welding	Not uniform bead contour		X
	Weld in wrong location	X	
	Undercut, or surface cavities	X	
	Cracks in weld metal or in heat affected zones	X	
Riveting	Component loose	X	
	Rivet head not seated	X	
	Rough or sharp edge		X
Stitching	Not type specified		X
	Loose stitching	X	
	Thread ends not trimmed		X
	Needle chews, puckers, or open seams	X	
Marking	Missing, illegible, or incomplete		X

4.4.3.2 End item dimensional examination. The end item shall be examined for compliance with the specified dimensions, including body and lid shell thickness. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of kits. The sample unit shall be one kit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing.

4.4.4.1 Initial production item testing. When a first article is not required, the initial production unit shall be tested as specified in 4.5.1 through 4.5.4 in sequence. Any test failure shall be cause for rejection of the lot.

4.4.4.2 Leakage testing. The end items shall be tested for leakage as specified in 4.5.4. The lot size shall be expressed in units of kits.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

The sample unit shall be one kit. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5 for test failures.

4.4.4.3 Operational testing. Every end item shall be tested as specified in 4.5.1. Any end item exhibiting one or more test failures shall be rejected.

4.4.5 Packaging inspection. An inspection shall be made to determine that preservation, packing, and marking comply with section 5. Defects shall be scored in accordance with table VI. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE VI. Packaging defects

Examine	Defect
Markings, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Rubber gasket not coated with talcum powder (level A packaging). Component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, inadequate stapling, loose strapping or tape banding. Bulged or distorted container.
Contents, interior and exterior container	Contents per container more or less than required.

4.4.6 Palletization inspection. An inspection shall be made to determine that palletization complies with the section 5 requirements. Defects shall be scored in accordance with table VII. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

TABLE VII. Palletization defects

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Lid closure tests. The complete kit, with the lid open, and with all components stored as shown on Drawing 5-7-104, shall be placed flat, in the horizontal position, on a table or bench. The following tests shall then be conducted and repeated at least once in sequence:

a. Close the lid and allow the lid to remain at rest under its own weight without latching. The at rest position of the lid shall then be observed for compliance with 3.7.1.

b. Secure the lid in the closed position by engaging the four latches. Then apply and release a downward manual force to the top side of the lid opposite the hinge. The force shall be applied and released at least four times. Any nonconformance with the "no spring back" requirement in 3.7.1 shall constitute failure of this test.

4.5.2 Extreme temperature storage tests.

4.5.2.1 High temperature. The fully assembled kit, with all components properly housed therein, shall be stored in an ambient temperature of 160°F, plus or minus 5°F, for not less than 4 hours. After returning to room temperature (65° to 75°F), the carrying case, all adhesive bonded connections, and the components within the carrying case shall be examined. Any nonconformance with the requirements of 3.7.2 shall constitute failure of this test.

4.5.2.2 Low temperature. Following the high temperature test and examination specified above, the same unit shall be stored in an ambient temperature of minus 40°F, plus or minus 5°F, for 72 hours. After returning

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:31Z
Check the source to verify that this is the currentversion before use.

to room temperature (65° to 75°F), the carrying case, all adhesive bonded connections, and the components within the carrying case shall again be examined. Any nonconformance with the requirements of 3.7.2 shall constitute failure of this test .

4.5.3 Impact test. After testing in accordance with 4.5.1 and 4.5.2, and at room temperature (65° to 75°F), elevate the carrying case 30 inches, plus or minus 2 inches, above a concrete surface so that the three center lines of the carrying case are diagonal to the concrete surface, and allow the carrying case to fall free. This drop shall be repeated until each of the eight corners of the carrying case has been subjected to the impact test. Each of the three latch surfaces shall then be subjected to the free fall, with the latch surface striking parallel with the concrete surface. Any nonconformance with the requirements of 3.7.2 shall constitute failure of this test.

4.5.4 Watertightness test. The fully assembled kit, with all removable components properly housed therein, shall be tested as specified in procedure I of Method 512 of MIL-STD-810. Nonconformance with the watertightness requirements of 3.7.3 shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Prior to securing the carrying case latches, the gasket shall be lightly coated with commercial grade talcum powder. The carrying case of each complete duplicator kit shall then be secured by the catches provided. Each kit shall then be unit packed in a snug-fitting fiberboard box conforming to style RSC, type CF or SF, class domestic of PPP-B-636. Closure shall be in accordance with the appendix of PPP-B-636.

5.1.2 Commercial. The duplicator kits shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Three duplicator kits, preserved as specified in 5.1, shall be packed in a snug fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2 Level B. Unless otherwise specified (see 5.2.2.1), three duplicator kits, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, of PPP-B-636. Each shipping container shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with method III as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Duplicator kits, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), stencil duplicating print kit, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L or film bonding means O and P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the patterns of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The kit is intended to be air dropped with using personnel. The kit is to be used for the preparation, printing, and distribution of PSYOP leaflets.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1).
c. When a special color is required (see 3.3.1.1).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant fiberboard shipping containers are required for level B pack (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample consisting of one kit. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

6.4 Part numbers, manufacturers. The following manufacturers' part numbers have satisfactorily met the requirements for the items indicated below:

Item	Paragraph	Manufacturer	Manufacturer's Part No.
Hinge	3.5.1.3	Homer D. Bronson Co.	SS-8653
Catches	3.5.1.4	Nielsen Hardware Co.	C-83314-9900CE
Handle	3.5.1.5	Nielsen Hardware Co.	5371 - Vinyl Grip - Olive Drab

6.5 Standard shade samples. For access to a standard shade sample of cotton tape, fastener tape, and polyester thread, address the procuring officer issuing the invitation for bids.

6.6 Instruction sheets. The contracting officer should arrange for examination of instruction sheets for recommended changes or approval (see 3.5.1.9).

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - GL

Review activity:

Army - MD

Preparing activity:

Army - GL

Project No. 7520-A108

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:31Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-43483A(GL)	STENCIL DUPLICATING PRINT KIT, HAND STAMP: MAN-PACKED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK/OP 20 NOV 84

Source: https://assist.dla.mil -- Downloaded: 2024-10-21T21:31Z
Check the source to verify that this is the current version before use.