MIL-T-43463B

1 August 1974
SUPERSEDING
MIL-T-43463A
31 August 1971

MILITARY SPECIFICATION

TABLE, DINING, PEDESTAL BASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers laminated or solid plastic top, pedestal base dining tables (see 6.1).

* 1.2 Classification. The tables shall be of the following types and sizes as specified (see 6.2).

Type I - Square

Size 1 - 36 by 36 inches
Size 2 - 40 by 40 inches

Type II - Rectangular

Size 1 - 24 by 36 inches
Size 2 - 36 by 48 inches
Size 3 - 36 by 54 inches

Type III - Round

Size 1 - 32 inches diameter
Size 2 - 42 inches diameter

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-508	-	Plastic Sheet, Laminated, Decorative and Nondecorative
MMM-A-130	-	Adhesive, Contact
* MMM-A-188	-	Adhesive, Urea-resin-type (Liquid and Powder)
MMM-S-193	-	Adhesive, Vinyl Acetate Resin Emulsion
PPP-B-601	-	Boxes, Wood, Cleated, Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

STANDARDS

FED-STD-175	-	Adhesives; Methods of Testing

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

(Copies of specifications, standards and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM)

Standard D 2016-65 - Standard Methods of Test for Moisture Content of Wood

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

United States Department of Commerce

Commercial Standard CS236 - Mat Formed Wood Particleboard

PS 1 - Softwood/Plywood
PS 51 - Hardwood and Decorative Plywood

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

* Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.2, 6.2, and 6.3).

* 3.2 Standard product. The table covered by this specification shall be the manufacturer's current commercial product except for any changes necessary to comply with this specification. All like items furnished on any one contract, including parts or subassemblies thereof, shall be new and interchangeable.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for pedestal base tables provided the completed item complies with all provisions of this specification. All materials shall be unused in their present state and free from defects which effect serviceability or appearance of the finished product.

* 3.3.1 Plywood panels. Plywood panels shall be constructed of either hardwood veneers, a combination of softwood and hardwood veneers, or a combination of hardwood veneers and lumber core, as specified in 3.3.1.1, 3.3.1.2, and 3.3.1.3, respectively. Face and back veneers for all constructions shall be close grained hardwood conforming to grade 1 or 2 veneers of PS51. The veneers shall produce a balanced panel to prevent warping.

* 3.3.1.1 Hardwood plywood panels. Hardwood plywood panels fabricated of all hardwood veneers shall be 9-ply minimum and shall be constructed in accordance with type II, exterior plys of grade 1 or 2 veneers of PS51 or better.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

* 3.3.1.2 Combination softwood and hardwood veneer plywood panels. Combination softwood and hardwood veneer plywood panels shall be 9-ply minimum and shall have inner plies of softwood conforming to interior type, grade A-B or better of PS 1. Hardwood face and back veneers shall be as specified in 3.3.1 and shall have an interior or better type bond.

3.3.1.3 Combination hardwood veneers and lumber core. Combination hardwood veneers and lumber core plywood panels shall be 5-ply minimum and shall be constructed with a lumber core of medium or low density hardwood, Idaho or Ponderosa Pine, Spruce, or similar low density softwood. Construction of the lumber core shall be in accordance with regular grade of PS51. After lumber core has been glued, and prior to surfacing, the moisture content shall be stabilized to not less than 5 and not more than 9 percent when tested as specified in 4.3.1.1. Hardwood face and back veneers shall be as specified in 3.3.1. The plywood shall have an interior or better type bond.

* 3.3.1.4 Particleboard. Particleboard shall be in accordance with any of the following types, grades and classes in Commercial Standard CS236:

Type 1, grade A (High Density), class 1
Type 2, grade B (Medium Density), class 2, except that panels less than one inch thick shall have a minimum average screw holding capacity of 235 pounds on the edges and 285 pounds on the faces
Type 2, grade A (High Density), class 2

* 3.3.2 Plastic sheet.

* 3.3.2.1 Decorative laminated sheet. For table tops with squared edges and self-edging, the surfacing and self-edging sheet shall have a nominal thickness of 1/16-inch (.050" minimum) conforming to style D, type I, grade HP, class 1 of L-P-508. Alternatively, decorative laminated plastic sheet conforming to style D, type II, grade HP, class 1 of L-P-508, nominal 0.031-inch thick may be used for self-edging only. For tables that are designed and constructed with rounded or rolled edges, plastic sheet shall be of post-forming style D, type III, grade HP, class 1, 0.051 inch minimum nominal thickness of L-P-508. Color, finish and pattern shall be selected from suppliers standard samples and as specified (see 6.2).

* 3.3.2.2 Backing sheet. The backing sheet shall conform to style ND, grade HP, type V of L-P-508 with minimum nominal thickness of 0.030 inch.

* 3.3.3 Solid molded plastic. The solid plastic table top shall be molded from nylon class thermoplastic material capable of meeting the performance characteristic requirements and tests applicable to style D, type I, grade HP, class 1, in L-P-508. Color and pattern shall be selected from suppliers standard samples and as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

* 3.3.4 Adhesive. The adhesive for bonding types I and II laminates shall conform to the block shear strength requirements and tests in MMM-A-188, for bonding type III laminates, the adhesives shall conform to the same requirements as above or MMM-A-139, at the option of the supplier.

* 3.3.5 Glides. Glides shall be adjustable, over a 3/4 inch range, rubber-cushioned, with the dome fabricated of corrosion-resisting steel, or case hardened steel with a nickel or chromium protective coating.

* 3.3.6 Screws, bolts, nuts, and washers. The miscellaneous hardware shall be steel with zinc or cadmium plating. Bolts or nuts shall be of self-locking type. Unless otherwise specified herein the screws, washers and other fastening devices shall be of the type, style and size used commercially for purpose intended.

3.4 Construction. Unless otherwise specified (see 6.2), the table tops shall be either laminated or solid plastic construction specified herein. All tables of the same top and size furnished on any one contract shall be identical. The table top shall be parallel with the test surface, within 1/8 inch, when tested as specified in 4.4.1. The table top sizes (see 1.2) shall be within a tolerance of plus or minus 3/8 inch. Table tops shall be mounted on a single pedestal column with spider leg base except for the 36 X 48 and 36 X 54 inch table tops which shall be mounted on two pedestal columns, each with a two prong base. The completed table height shall be 30 inches, plus or minus 1/2 inch. The table top requirements shall be as specified under 3.5.1.1 or 3.5.1.2, as applicable.

3.5 Component details.

3.5.1 Table top.

* 3.5.1.1 Laminated plastic sheet top.

3.5.1.1.1 Table top with square edges. The table top shall be fabricated with a core of plywood as specified in 3.1.1 or particleboard as specified in 3.3.1.4 having a minimum thickness of 3/4 inch. As a minimum, the edge thickness of the table shall be 1-1/8 inch, and may be obtained by wood back-up strips around the perimeter. The entire thickness of the edge shall be self-edged of the same color, finish and pattern as the top. The top shall be covered with plastic sheet specified in 3.3.2.1 while the entire bottom shall be covered with backing sheet specified in 3.3.2.2. The top plastic sheet shall overlap the self-edging to prevent any dirt or food collecting in the joint. All edges shall be eased to remove sharp corners.

* 3.5.1.1.2 Table top with round edges. Table tops with round, contoured or rolled edges shall be fabricated of core material and backing sheet as specified in 3.5.1.1.1 except that the top underside perimeter edges shall be faced with 3/4 inch half round wood back-up strips to provide additional edge thickness and the top including the edges, shall be covered with the type III post forming laminate in 3.3.2.1. Corners shall be formed in such a manner as to preclude gaps and crevices that would collect dirt or cause personnel injury. No delaminations shall occur.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

3.5.1.1.3 Bonding. The laminated plastic sheets shall be bonded with adhesives specified in 3.3.4 as applicable. The adhesive shall be applied to surfaces in an adequate and uniform manner as recommended by the adhesive manufacturer. Open and closed assembly time clamping or pressing time and pressure shall be in accordance with the adhesive manufacturer's recommendations.

* 3.5.1.2 Solid molded plastic top. The table top shall be fabricated from solid plastic specified in 3.3.3. The surface of the top shall be free from mars, patches, blistered or rough areas, cracks, scratches, extrusions or mold marks, and when viewed from 5 feet no discoloration, streaking, staining, surface waviness, swells, and depression. There shall be no warp greater than 1/4-inch in length or width of the top. The molded top shall have inserts molded into the underside to receive the bolts for attaching the pedestal legs, stiffening ribs and stiffening edges. Exterior edge thickness shall be 1-1/8 inch minimum.

* 3.5.2 Pedestal base.

* 3.5.2.1 Single pedestal table. The base shall be constructed of cast steel in a four leg spider shape in accordance with the manufacturer's standard practice. Glides as specified in 3.3.5 shall be provided at each end of the spider leg to eliminate any table wobble. The spread (center to center of glides) of the base leg of a center pedestal table shall not be less than half of the table top size. The column shall be steel tube, nominal 3-inches in diameter with 0.095 inch nominal wall thickness. The top of the column shall have either a steel mounting plate 11-inches square minimum with 0.0747 inch thickness minimum, ribbed and reinforced or a steel casting spider not less than 3/16-inch thick. Not less than eight threaded fasteners shall secure the top mounting to the bottom of wood table top. Minimum of four threaded fasteners shall secure the pedestal to the inserts in the plastic molded top. The column, base and attachment plate shall be mechanically assembled into a single unit which shall permit subsequent disassembly.

* 3.5.2.2 Double pedestal. The bases for the table shall be made of cast steel, be rectangular (two prong legs) approximately 21-inches long and between 2 to 4 inches wide and weigh not less than 7-1/2 pounds. Glides specified in 3.3.5 shall be fastened to bottom at end of each leg. The columns shall be steel tube, nominal 3-inches in diameter with 0.049 inch nominal wall thickness. The top of each column shall have a steel mounting plate that shall be secured to the table top by no less than four threaded fasteners. The column, base and attachment plate shall be mechanically assembled into a single unit which shall permit subsequent disassembly.

3.6 Performance.

* 3.6.1 Stability. The pedestal tables shall withstand the tipping test specified in 4.4.2 and the impact test specified in 4.4.3 without loosening any hardware or damage to legs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

* 3.6.2 Static load. The table shall be capable of supporting a 160 pound load, plus or minus 2 pounds, without any evidence of permanent deformation of top or failure at any interface or any fasteners when tested in accordance with 4.4.4.

3.7 Finish. The bases shall be painted with black paint in accordance with the manufacturer's standard practice. The columns shall be chromium plated and polished to a satin finish in accordance with the manufacturer's standard practice. The mounting plate shall be electrodeposited zinc or cadmium plated, or painted in accordance with the manufacturer's standard practice.

3.8 Marking for identification. The identification marking shall be permanently stamped or stenciled legibly on the underside of the table top and shall include the manufacturer's identification contract No., year of manufacture, and National Stock No. (NSN) all in characters 1/4-inch high minimum.

3.9 Assembly instructions. A detailed assembly instruction sheet shall be furnished with each table describing recommended assembly procedures to follow.

* 3.10 Workmanship. Exposed steel parts shall be free from sharp or rough edges, burrs and slivers. Paint shall be free from grit or foreign matter, areas of no film, drip, drops or sags. The table top surface shall be free from mars, chips, rough areas, scratches and surface waviness. When viewed at a distance of 5 feet, discoloration, spotting, streaking, staining, surface waviness, swells, laps on printed surface, depression, mold marks, plywood imperfections and grain imperfections shall not be visible. Corners and edges of table top shall be smooth so as not to snag clothing or cause injury to personnel or have gaps or open joints which would collect dirt. There shall be no warp greater than 1/4-inch across diagonal corners of the table top. All bolts and screws shall be drawn up snug against the bearing surface.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article inspection. When a first article is required, it shall be examined for defects in table I, dimensions specified, and tested in accordance with 4.4.1 through 4.4.4. The presence of any visual defects, dimensions not within specified requirements or failure to pass the tests shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.1.1 Moisture content. Tests shall be performed on each lot of lumber cores specified in 3.3.1.3 offered for inspection at one time for moisture content in accordance with ASTM D 2016-65. The sample unit shall be one lumber core. Three determinations shall be taken on each sample unit and the results shall be the average of the determinations. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units.

* 4.3.2 Process examination. An examination shall be made during fabrication to determine that the laminating of the table top is in accordance with the specified bonding requirements in 3.5.1.1.3. Whenever nonconformance is noted, correction shall be made to affected items and process.

4.3.3 Inspection of the end item. The lot shall consist of all completely finished tables of one type and size offered for inspection at one time. The sample unit shall be one assembled table.

* 4.3.3.1 Visual examination. The tables shall be examined for defects classified in table I. The inspection level shall be II, and the acceptable quality levels (AQL's) shall be 2.5 for major and 6.5 for total, defects, expressed in terms of defects per hundred units.

* TABLE I. Visual classification of defects

Examine	Defect	Classification Major	Minor
Painted surfaces	Not specified color		X
	Not smooth; not uniform in color; hard sags, runs		X
	Areas of no film on exposed surfaces	X	
	Dirt, grit, or other foreign matter imbedded in finish		X
	Deep scratches, gouges, or mars, through to metal	X	
Plated surfaces	Center column not plated as specified, not free from scratches, gouges or dents	X	
	Mounting plate not plated or painted as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

* TABLE I. Visual classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Laminated, decorative sheet table top	Not specified finish, color or pattern	X	
	Marred, patched, cracked, pinholes, chipped out, blistered, unbonded to core, pitted or rough areas	X	
	Open joints at edges between top and sides	X	
	Plywood imperfections, or wood veneer grain visible in plastic top	X	
	Edges or corners not smooth	X	
Solid molded plastic table top	Not one piece	X	
	Not free of mold mark or extrusions or exposed surfaces, mars, patches, blistered or rough areas, cracks or when viewed from 5 feet discoloration, streaking, stains, waviness, swells or depressions		X
	Edges or corners not smooth	X	
Backing sheet	Torn or scuffed surface; dirt, grit or other foreign matter imbedded in face of backing sheet		X
	Cracked, chipped out, gouged, or split, exposing core, any portion unbonded to core, or blistered	X	
Construction, workmanship and material	Not type, size, or construction required	X	
	Sharp or burred edges or projections	X	
	Component not of specified design	X	
	Component missing, malformed, dented, bent, or fractured	X	
	Component loose, not properly assembled, out of alignment or mispositioned (unless otherwise classified)	X	
Table top edge construction	Not as specified	X	
Table top corners and edges	Corners and edges not eased	X	
Glides	Not adjustable or rubber cushioned	X	
	Missing	X	
Identification marking	Missing, illegible, incorrect, incomplete or wrong size		X
Assembly instructions	Missing, illegible or incorrect		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

4.3.3.2 Dimensional examination. The tables shall be examined for defects in dimensions, including warpage. For warpage, check using straight edge placed across diagonals. Any dimension that is not within specified tolerances shall be classified a defect. The inspection level shall be S-2 and the AQL shall be 4.0, expressed in terms of defects per hundred units.

* 4.3.3.3 End item testing. When a first article is not required, the first produced table shall be tested as specified in 4.4.1 through 4.4.4. Production tables shall be tested as specified in 4.4.1 and 4.4.3 as applicable. Failure of a test shall be recorded as a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.3.4 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking comply with section 5. Defects shall be as set forth in table II. The sample unit shall be one shipping container fully packed, except that it need not be sealed. The lot shall be all shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0, expressed in terms of defects per hundred units.

TABLE II. Examination of preparation for delivery

Examine	Defect
Marking (exterior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as immobilization of legs and drawstring bag. Closure not in accordance with PPP-B-636.
Content	Number per container more than required.

4.4 Tests.

4.4.1 Levelness test. Levelness of the assembled table shall be determined by adjusting each glide the same distance from the base. The table shall then be set on a flat test plate. Measurements shall be taken at all four corners of the table top to determine compliance with 3.4. Any nonconformance shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

* 4.4.2 Stability resistance to tipping. On a level floor, a load of 95 pounds, ± one pound shall be secured adjacent to one top edge of the assembled table, over an area not exceeding one square foot, centered at the midpoint of the longest dimension between base glides. Tipping of the table beyond the equilibrium point shall constitute failure of the test.

* 4.4.3 Interface evaluation impact test. An assembled table shall be tipped to its equilibrium point and allowed to free-fall five times from that point to impact upon an asphalt tile over concrete floor of the type used in dining halls. The support assembly and hardware shall be inspected. Any looseness of bolts or damage to support shall be considered as failing this test.

* 4.4.4 Static load. For not less than 10 minutes, a load of 160 pounds, ± two pound, shall be placed adjacent to one top edge of the assembled table, over an area not exceeding one square foot. The load shall be centered at the mid-point of the longest dimension between base glides. The table base may be restrained to prevent tipping. Any evidence of noncompliance with 3.6.2 shall constitute failure to pass this test.

5. PREPARATION FOR DELIVERY

5.1 Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Each table shall be disassembled. Screws, nuts, bolts and washers removed during disassembly of table shall be packaged in a cotton cloth drawstring bag or sealed paper envelope and secured to a component of the table.

5.1.2 Level C. Tables shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Each table, packaged as specified in 5.1, together with assembly instructions, shall be packed in a snug-fitting fiberboard or cleated plywood shipping container conforming to grade V2s, style RSC of PPP-B-636, or overseas type of PPP-B-601, respectively. The finished surfaces of the table top shall be covered with 30-pound basis weight per ream (24 by 36 - 500) machine-glazed kraft paper, highly calendered kraft paper, or waxed paper, and then covered with a fiberboard cap tray. Fiberboard inserts or other cushioning material shall be used to isolate and immobilize the contents and to fill voids within the container. Closure and strapping shall be in accordance with the appendix of the applicable container specification. Each fiberboard shipping container shall be waterproofed in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Each table, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard or cleated plywood shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 350 of PPP-B-636; or domestic type, style A or B of PPP-B-601, respectively. The table top shall be protected and contents immobilized as specified in 5.2.1. Each fiberboard shipping container shall be closed in accordance with method II of PPP-B-636.

5.2.3 Level C. Tables, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The tables covered by this specification are to be used in military dining facilities.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Style and size table required (see 1.2).
(c) When a first article is required (see 3.1, 4.2 and 6.3).
(d) Color, pattern, and surface finish required (see 3.3.2.1, 3.3.3 and 3.4).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample of the specified table and shall consist of one unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangement for inspection and approval of the first article.

6.4 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - MC
Air Force - 84

Review activities:

Army - MD
Navy - YD, MS

Preparing activity:

Army - GL

Project No. 7105-0214

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-T-43463B TABLE, DINING, PEDESTAL BASE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.

FOLD

U.S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STSNL-TD

Commanding General
U.S. Army Natick Laboratories
ATTN: STSNL-TD
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:28Z
Check the source to verify that this is the current version before use.