MIL-C-70491(AR)
AMENDMENT 2
12 MARCH 1990

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, DISPLAY/PROCESSOR

This Amendment forms a part of Military Specification MIL-C-70491(AR), dated 8 May 1983, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

*1. Delete existing 3.2.1.

Add: 3.2.1. Functional. The display/processor circuit card assembly shall be tested using AN\USM-465 Genrad Tester or equivalent in accordance with Test Station Software-Display/Processor CCA: 9379253.

3.2.1.2, line 1: Delete the word “either”.

3.2.1.2, line 2: Delete “or” and substitute “and”.

PAGE 14

4.6.1, line 8. Delete the fourth sentence starting with “Upon” and substitute:

“Upon completion of the 20 minute exposure, the temperature of the chamber shall be raised at the rate of 10°C (18°F) per minute plus or minus 1°C (1.8°F) to -40°C (-40°F). At -40°C, operating power shall be applied to the unit under test and shall continue to be applied until the end of each cycle. The chamber temperature shall then be raised at the rate of 10°C (18°F) per minute Plus Or minus l°c (1.8°F) to +71°C (+160°F).“

4.6.1, line 17: Delete “test in 4.6.3” and substitute “tests in 4.6.3 through 4.6.7”.

4.6.1. line 18: Delete 3.2.1 and substitute “3.2.1.1 through 3.2.1.5 inclusively"

4.6.2, line 10: Delete “4.6.3” and substitute “4.6.3. through 4.6.7”.

4.6.2, line 11: Delete 13.2.1.1" and substitute “3.2.1.1. through 3.2.1.5, inclusively”.

AMSC N/A FSC 1220

DISTRIBUTION STATEMENT A. Approved for public release; distributicn is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:34Z
Check the source to verify that this is the current version before use.

4. Change 4.6.3.

a. Delete the existing 4.6.3. and Table IV.

b. Add the following:

4.6.3 Performance. The performance of the CCA, Displayl Processor shall be tested using aAN\USM-465 Genrad Tester or equivalent in accordance with Test Station Software-Display/Processor CCA:9379253.

PAGE 18

4.6.4: Add new last sentence:

"The last inspection/test performed prior to acceptance and delivery shall be the memory read cycle test on the EPROM (reference EPROM Program Cycle Test paragraph number 4.6.6)."

PAGE 19

4.6.6, line 2: Delete "Figure 3.4" and substitute "Figure 4".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220- A371)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.