INCH-POUND

MIL-C-70492(AR)
AMENDMENT 2
12 Mar 1990

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, MODEM

This Amendment forms a part of Military Specification MIL-C-70492(AR), dated 8 May 1989, and is approved for use within the U.S. Army Armament Munition and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

*1. Delete existing 3.2.1.

Add: 3.2.1 Functional. The modem circuit card assembly shall be tested using AN/USM-465aGenrad Tester or equivalent in accordance with Test Station Software-Modem CCA: 9379254.

PAGE 9

4.6.1, line 7: Delete the fourth sentence starting with "Upon" and substitute:

"Upon completion of the 20 minute exposure, the temperature Of the chamber shall be raised at the rate 01 10°C (18°F) per minute plus or minus 1°C (1.8°F) to -40°C (-40°C). At -40°C, operating power shall be applied to the unit under test and shall continue to be applied until the end of each cycle. The chamber temperature shall then be raised at the rate of 10°C (18°F) per minute plus or minus 1°C (1.8°F) to +71°C (+160°F).

PAGE 10

4.6.2, line 10: Delete "3.2.1.1. and. 3.2.1.7 inclusive." and substitute "3.3.3" .

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

*2 Change

a. Delete existing 4.. 6.3 and Table IV

b. Add the following:

4.6.3 Performance. The performance of the CCA/Modem shall be tested using AN/USM-465AGenrad Tester or equivalent in accordance With Test Station sOftware-Modern CCA: 9279254.

Custodian:
Army–AR

Preparing activity:
Army-AR

(Protect 1220-A372)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.