MIL-C-70494(AR)
AMENDMENT 1
21 March 1986

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, AUDIO INTERFACE

This Amendment forms a part of Military specification MIL-c-70494(AR), dated 4 April 1985, and is approved for use within the U.S. Army Armament, Munition and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.3.2, line 2: Delete “and” and substitute ‘through”.

3.3.3, line 2: Delete “and” and substitute “through”.

PAGE 9

4.6.1, line 7: Delete the fourth sentence starting with “Upon and substitute:

Upon completeion of the 20 minute exposure, the temperature of the chamber shall be raised at the rate of 10°C (18°F) per minute plus or minus 1°C (1.8°F) to -40° (-40°F). AT-40°, operating power shall be applied to the unit under test and shall continue to be applied until the end of each cycle. The chamber temperature shall then be raised at the rate of 100C (18°F) per minute plus or minus l°C (1.8°F) to +71°C (+160°F).”

4.6.1, lines 17 and 18: Delete “and” and substitute ‘through”.

PAGE 10

4.6.2, lines 10 and 11: Delete “and” and substitute “through”.

CustOdian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-A3L8)

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.