MIL-C-70496(AR)
AMENDMENT 1
21 March 1986

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, LOGIC POWER SUPPLY

This Amendment forms a part of Military Specification MIL-C-70496(AR), dated 4 April 1985, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defenses

PAGE 5

3.3.2, line 2: Delete “and” and substitute ‘through”.

PAGE 6

3.3.3, line 2: Delete “and” and substitute “through”.

PAGE 10

4.6.1, line 7: Delete the fourth sentence starting with "Upon" and substitute:

“Upon completion of the 20 minute exposure, the temperature of the chamber shall beraised at eh note of 100C (180F) per minute plus or minus 1°C(1.8°F) to -40W (-400F). At -40°C, operating power shall be applied to the unit under test and shall contiune to be applied until the end of each cycle.the rate of 10°C temperature shall then be raised at (18°F) per minute plus or minus l°C (1.8°F) to +71°C (+160°F).”

4.6.1, lines 17 and 18: Delete "and" and substitute through"-

4.6.2. line 9 and 10: Delete “and” and substitute "through".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Protect 1220-A320)

AMSC N/A

FSC 1220

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.