MIL-C-70497 (AR)
AMENDMENT 1
21 March 1986

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, CASE INTERCONNECT

This Amendment forms a part of Military Specification MIL-C-70497(AR), dated 4 April 1985, and IS approved for use within the U.S.Army Armament, Muntions amd Chemicsl Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 9

4.6.1, line 8: Delete the fourth sentence starting with "Upon" and substitute:

"Upon Completeion of the 20 minute exposure, the temperatureof the chmber shall be raised at the rate of 10° (18°F) per minute plus or minus l°c (1.8°F) to -40° (-40°F). At -40°, operating power shall be applied to the unit under test and shall conutine to be applied until the end of each cycle. The chamber temperature shall then be raised at the rate of 10°C (18°F) per minute plusor minus 1°C (1.8°F) to 71°C (+160°F). "

Custodian:
Army-AR

Preparing activity:
Army-AR

(Protect 1220-A321)

AMSC N/A

FSC 1220

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.Text

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.