MIL-C-70498(AR)
AMENDMENT 1
21 March 1986

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, INTERCONNECT

This Amendment forms a part of Military Specification MIL-C-70498(AR), dated 4 April 1985, and is approved for use within the U.S. Army Armament, Munition and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

4.6.1, line 8: Delete the fourth sentence starting with "Upon" and substitute:

"Upon completion of the 20 minute exposure? the temperature of the chamber shall be raised at the rate of 10°(18°F] per minute plus or minus l°C (1.8°F) to -40°(-40°F). At- 40°C, operating power shall be applied to the unit under test and shall continue to be applied until the end of each cycle. The chamber temperature shall then be raised at the rate of 10°C (18°F) per minute plus or minus 1°C (1.8°F) to +71°C (+160°F)."

4.6.1, line 10: Delete "+71°F (+160°C)." and substitute "+71°C (+160°F)""

Custodian:
Army-AR

"Preparing activity:
Army-AR

(Protect 1220-A322)

AMSC N/A

FSC 1220

DISTRIBUTION STATEMENT A. Approved forpublic release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.