MIL-K-70493(AR)
AMENDMENT 1
21 March 1986

MILITARY SPECIFICATION

KEYBOARD, DATA ENTRY

This Amendment forms a part of Military specification MIL-K-70493(AR), dated 4 April 1985, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies Of the Department of Defense.

PAGE 5

3.3.2, line 2: Delete “and” and substitute “through”.

3.3.3, line 2: Delete “and” and substitute “through”.

PAGE 9

4.6.1, line 7: Delete The Fourth sentence starting with “Upon” and substitute:

"Upon completion of the 20 minute exposure, the temperature of the chamber shall be raised at the rate of 10°C {18°F) per minute plus or minus 1°C (1.8°F) to -40°C (-40°F). At -40°C, operating power shall be applied to the unit under test and shall continue to be applied until the end of each cycles The chamber temperature shall then be raised at the rate of 10°c (18°F) per minute plus or minus l°C (1.8°F) to +7l°C (+160°F) . “

4.6.1, lines 17 and 18: Delete "and" substitue "through".

PAGE 10

4.6.2, line 10: Delete "4.6.4 and" and substitute "4.6.3 through".

4.6.2, line 11: Delete “and” and substitute "through".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-A317)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.