INCH-POUND
MIL-S-64045/124 (AR)
16 October 2001

MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1/M825A1, W/ICM, LOW ANGLE, (155-AN-2) CHGS 5W & 6W, (P/N 11785434-145)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described here in shall consist of this document and the latest issue of Specification MIL-S-64045.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	Drift (mils)	TF/FS (seconds)	FS/1 Om HOB (seconds)
5 W	3000	125.5 ± 1	2.1 ± 1	9.1 ± .1	0.23
	4500	204.5 ± 1	3.6 ± 1	14.3 ± .1	0.15
	5500	263.6 ± 1	4.7 ± 1	18.1 ± .1	0.12
	7000	366.0 ± 1	6.9 ± 1	24.4 ± .1	0.09
	8500	499.8 ± 1	10.2 ± 1	32.3 ± .1	0.07
6W	4500	149.1 ± 1	2.8 ± 1	12.4 ± .1	0.17
	6000	220.2 ± 1	4.2 ± 1	17.6 ± .1	0.12
	7000	273.8 ± 1	5.3 ± 1	21.3 ± .1	0.10
	9000	399.7 ± 1	8.1 ± 1	29.7 ± .1	0.07
	10000	478.1 ± 1	9.9 ± 1	34.6 ± .1	0.06

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	FS (seconds)	Elevation (mils)	FS (seconds)
		M825A1		ICM 483A1	
5 W	5000	246 ± 1	15.6 ± .1	259 ± 1	15.0 ± .1
	6000	306 ± 1	19.7 ± .1	316 ± 1	18.9 ± .1
	8000	460 ± 1	29.2 ± .1	465 ± 1	28.3 ± .1
		ICM 692/731		ICM 718/741	
	5000	350 ± 1	15.4 ± .1	245 ± 1	14.5 ± .1
	7500	480 ± 1	26.4 ± .1	410 ± 1	25.0 ± .1
	8500	560 ± 1	32.3 ± .1	504 ± 1	30.5 ± .1
		M825A1		ICM 483Al	
6W	6000	231 ± 1	17.1 ± .1	240 ± 1	16.4 ± .1
	8000	341 ± 1	25.0 ± .1	346 ± 1	24.2 ± .1
	9000	408 ± 1	29.5 ± .1	412 ± 1	28.5 ± .1
		ICM 692/731		ICM 718/741	
	6000	315 ± 1	16.8 ± .1	227 ± 1	16.0 ± .1
	8000	400 ± 1	24.5 ± .1	338 ± 1	23.8 ± .1
	10000	532 ± 1	34.2 ± .1	480 ± 1	32.9 ± .1

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-0025)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.