INCH-POUND

MIL-S-64045/125 (AR)
16 October 2001

MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1/M825A1, W/ICM,
LOW ANGLE, (155-AN-2) CHGS 7W & 7R, (P/N 11785434-146)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described here in shall consist of this document and the latest issue of Specification MIL-S-64045.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	Drift (mils)	TF/FS (seconds)	FS/1 Om HOB (seconds)
7W	6000	150.3 ± 1	3.2 ± 1	14.1 ± .1	0.15
	7500	210.6 ± 1	4.6 ± 1	19.8 ± .1	0.11
	9000	281.6 ± 1	6.2 ± 1	25.3 ± .1	0.08
	10500	364.7 ± 1	8.2 ± 1	31.3 ± .1	0.07
	12500	503.2 ± 1	12.2 ± 1	40.8 ± .1	0.05
7R	8000	147.1 ± 1	3.6 ± 1	17.2 ± .1	0.13
	10000	213.9 ± 1	5.3 ± 1	23.7 ± .1	0.09
	13000	346.9 ± 1	8.8 ± 1	35.1 ± .1	0.06
	15000	463.0 ± 1	12.1 ± 1	44.0 ± .1	0.05
	17000	624.7 ± 1	17.5 ± 1	55.8 ± .1	0.04

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	FS (seconds)	Elevation (mils)	FS (seconds)
		M825A1		ICM 483Al	
7 w	7500	213 ± 1	19.3 ± .1	225 ± 1	18.5 ± .1
	8500	264 ± 1	25.0 ± .1	269 ± 1	22.3 ± .1
	12000	423 ± 1	38.2 ± .1	473 ± 1	37.0 ± .1
		ICM 692/731		ICM 718/741	
	7500	285 ± 1	18.9 ± .1	215 ± 1	18.3 ± .1
	8500	320 ± 1	22.6 ± .1	260 ± 1	21.9 ± .1
	12000	505 ± 1	37.6 ± .1	465 ± 1	36.6 ± .1
		M825A1		ICM 483Al	
7R	9500	202 ± 1	21.6 ± .1	206 ± 1	20.9 ± .1
	11000	260 ± 1	26.9 ± .1	262 ± 1	26.2 ± .1
	15000	472 ± 1	44.0 ± .1	470 ± 1	42.9 ± .1
		ICM 692/731		ICM 718/741	
	9500	252 ± 1	21.1 ± .1	197 ± 1	20.7 ± .1
	11000	299 ± 1	26.4 ± .1	252 ± 1	25.9 ± .1
	15000	490 ± 1	43.1 ± .1	460 ± 1	42.5 ± .1

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-0026)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.