MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1/M825A1, W/ICM, HIGH ANGLE, (155-AN-2), CHGS 3W-4W-5W-6W-7W-7R (P/N 11785434-148)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described here in shall consist of this document and the latest issue of Specification MIL-S-64045.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	TF (seconds)	FS/M577 (seconds)	Drift (mils)
3W	3800	1287.2 ± 1	53.4 ± .1	50.6 ± .1	128.6 ± 1
	4500	1227.3 ± 1	52.0 ± .1	49.2 ± .1	75.5 ± 1
	6000	1050.2 ± 1	47.6 ± .1	44.4 ± .1	37.6 ± 1
4 w	4500	1295.1 ± 1	59.2 ± .1	56.8 ± .1	132.6 ± 1
	5500	1223.9 ± 1	57.4 ± .1	54.9 ± .1	72.3 ± 1
	7000	1081.0 ± 1	53.6 ± .1	51.0 ± .1	41.1 ± 1
5W	7000	1194.0 ± 1	62.4 ± .1	60.4 ± .1	65.4 ± 1
	8000	1114.1 ± 1	60.0 ± .1	57.9 ± .1	48.0 ± 1
	9000	1006.8 ± 1	56.4 ± .1	54.0 ± .1	35.0 ± 1

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	TF (seconds)	FS/M577 (seconds)	Drift (mils)
6W	7000	1275.4 ± 1	72.1 ± .1	69.8 ± .1	116.62 1
	8000	1224.9 ± 1	70.5 ± .1	68.3 ± .1	79.1 ± 1
	10000	1094.4 ± 1	66.0 ± .1	64.8 ± .1	46.2 ± 1
7 w	10000	1215.8 ± 1	78.8 ± .1	76.5 ± .1	82.0 ± 1
	11000	1166.8 ± 1	76.9 ± .1	74.6 ± .1	64.3 ± 1
	12000	1109.0 ± 1	74.6 ± .1	72.3 ± .1	52.0 ± 1
7R	11000	1268.6 ± 1	93.3 ± .1	90.4 ± .1	150.2 ± 1
	14000	1162.5 ± 1	88.3 ± .1	85.5 ± .1	68.9 ± 1
	16000	1060.2 ± 1	83.2 ± .1	80.3 ± .1	48.2 ± 1

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-0028)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.