The documentation and process conversion measures necessary to comply with this document shall be completed by 4 May 2022.

INCH-POUND

MIL-PRF-19500/515F
w/AMENDMENT 1
4 February 2022
SUPERSEDING
MIL-PRF-19500/515F
16 September 2016

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, PNP, SILICON, POWER,
THROUGH HOLE, TYPES 2N6378 AND 2N6379,
QUALITY LEVELS JAN, JANTX, JANTXV, AND JANHC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNP silicon, through hole power transistors for power applications. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each encapsulated device type as specified in MIL-PRF-19500. One level of product assurance (JANHC) is provided for each unencapsulated device.

1.2 Package outlines. The device package outlines are as follows: TO-3 in accordance with figure 1 for all encapsulated device types. See figure 2 for unencapsulated devices.

1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Types	P_T T_C = +25°C (1)	P_T T_C = +100°C (1)	$R_{\theta JC}$	V_{CBO}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	°C
2N6378	250	143	0.7	-120	-100	-6	-20	-50	-65 to +200
2N6379	250	143	0.7	-140	-120	-6	-20	-50	-65 to +200

(1) Between T_C = +25°C and T_C = +200°C, linear derating factor (average) = 1.43 W/°C.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Unless otherwise specified, T_C = +25°C.

	h_{FE3}	h_{FE3}	h_{FE2}	h_{FE2}	$V_{BE(sat)}$	$V_{BE(sat)}$	$V_{CE(sat)}$	$V_{CE(sat)}$
Type	V_{CE} = -4 V dc I_C = -50 A dc (1)	V_{CE} = -4 V dc I_C = -50 A dc (1)	V_{CE} = -4 V dc I_C = -20 A dc (1)	V_{CE} = -4 V dc I_C = -20 A dc (1)	I_C = -20 A dc I_B = -2 A dc	I_C = -20 A dc I_B = -2 A dc	I_C = -20 A dc I_B = -2 A dc	I_C = -20 A dc I_B = -2 A dc
	Min	Max	Min	Max	V dc	V dc	V dc	V dc
					Min	Max	Min	Max
2N6378	10		30	120		1.8		1.0
2N6379	10		30	120		1.8		1.0

	C_{obo}	C_{obo}	$\|h_{fe}\|$	Pulse response	
Type	V_{CB} = -10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1 MHz	V_{CB} = -10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1 MHz	V_{CE} = -10 V dc I_C = -1 A dc f = 10 MHz	t_{on}	t_{off}
	pF	pF		µs	µs
	Min	Max	Min	Max	Max
2N6378		1500	3	0.5	1.05
2N6379		1500	3	0.5	1.05

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JAN”, “JANTX”, and “JANTXV”.

1.5.2 JAN certification mark and quality level for unencapsulated devices (die). The quality level designators for unencapsulated devices (die) that are applicable for this specification sheet is: "JANHC".

1.5.3 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.3.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".


1.5.3.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "6378" and "6379".

1.5.4 Die identifiers for unencapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifiers that are applicable for this specification sheet is "A" (see figure 2 and 6.5.2).

* 1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.


Ltr	Inch	Inch	mm	mm	Notes
	Min	Max	Min	Max	
CD		.875		22.23	3
CH	.270	.380	6.86	9.65	
HR	.495	.525	12.57	13.34	
HR1	.131	.188	3.33	4.78	
HT	.060	.135	1.52	3.43	
L1		.050		1.27	5, 9
LD	.057	.063	1.45	1.60	5, 9
LL	.312	.500	7.92	12.70	5
MHD	.151	.161	3.84	4.09	7
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	4
PS1	.205	.225	5.21	5.72	4, 5
S1	.655	.675	16.64	17.15	4



NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Body contour is optional within zone defined by CD
4. These dimensions shall be measured at points .050 (1.27 mm) to .055 (1.40 mm) below seating plane. When gauge is not used, measurement shall be made at seating plane.
5. Both terminals.
6. At both ends.
7. Two holes.
8. Terminal 1 is the emitter, terminal 2 is base. The collector shall be electrically connected to the case.
9. LD applies between L1 and LL. Lead diameter shall not exceed twice LD within L_1.
* 10. In accordance with ASME Y14.5, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (TO-3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.



Ltr	Inch	Inch	mm	mm
	Min	Max	Min	Max
A	.231	.235	5.87	5.97
C	.231	.235	5.87	5.97

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 inches (0.13 mm).
4. The physical characteristics of the die are:
   Thickness: .008 inch (0.20 mm) to .012 inch (0.30 mm).
   Top metal: Aluminum 40,000 Å minimum, 50,000 Å nominal.
   Back metal: Gold 2,500 Å minimum, 3,000 Å nominal.
   Back side: Collector.
   Bonding pad: B = .016 inch (0.41 mm) x .060 inch (1.52 mm).
   E = .016 inch (0.41 mm) x .070 inch (1.78 mm).

FIGURE 2 Physical dimensions JANHC die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML-19500) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The Interface and physical dimensions shall be as specified in MIL-PRF-19500, figure 1 (TO-3); and figure 2 (JANHC) herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500 and herein. Where a choice of finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table II herein).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

* 4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements JANTX, JANTXV levels
(1) 3c	Thermal impedance (see 4.3.3).
11	I_{CEX1} and h_{FE2}
12	See 4.3.2, method 1039 of MIL-STD-750, test condition B.
13	Subgroup 2 of table I herein; ΔI_{CEX1} = 100 percent of initial value or -2 μA dc, whichever is greater. Δh_{FE2} = ± 25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Screening (JANHC) die. Screening of JANHC die shall be in accordance with appendix G of MIL-PRF-19500. As a minimum, die shall be 100 percent probed to insure the assembled chips will meet the requirements of table I, subgroup 2.

4.3.2 Power burn-in conditions. Power burn-in conditions are T_J = + 187.5 °C, ± 12.5 °C; $V_{CB} \geq$ -20 V dc; $T_A \leq$ +35°C. T_J measurement shall be in accordance with method 3100 of MIL-STD-750.

4.3.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). See table III, group E, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein. Electrical measurements (end-points) shall be in accordance with subgroup 2 of table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500, and as follows. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
B3	1037	For solder die attach: $V_{CE} \geq$ -20 V dc.
B3	1027	For eutectic die attach: $V_{CE} \geq$ -20 V dc adjust P_T to achieve T_J = +175°C minimum.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Test condition A, weight = 10 pounds; time = 15 s.
C5	3131	See 4.3.3, $R_{\theta JC}$ = 0.7°C/W.
C6	1037	For solder die attach: $V_{CE} \geq$ -20 V dc.
C6	1026	For eutectic die attach: $V_{CE} \geq$ -20 V dc adjust P_T to achieve T_J = +175°C minimum.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table III herein. Delta measurements shall be in accordance with table II herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1 Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.3	$Z_{\theta JX}$			°C/W
Collector to emitter breakdown voltage 2N6378 2N6379	3011	Bias condition D, I_C = -50 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	 -100 -120		 V dc V dc
Collector to emitter cutoff current 2N6378 2N6379	3041	Bias condition D V_{CE} = -50 V dc V_{CE} = -70 V dc	I_{CEO}		-50	µA dc
Collector to emitter cutoff current 2N6378 2N6379	3041	Bias condition A; V_{BE} = +1.5 V dc V_{CE} = -120 V dc V_{CE} = -140 V dc	I_{CEX1}		-10	µA dc
Emitter-base cutoff current	3061	Bias condition D, V_{EB} = -6 V dc	I_{EBO}		-100	µA dc
Collector to base cutoff current 2N6378 2N6379	3036	Bias condition D, V_{CB} = -120 V dc V_{CB} = -140 V dc	I_{CBO}		-10	µA dc
Forward-current transfer ratio	3076	V_{CE} = -4 V dc; I_C = -1 A dc; pulsed (see 4.5.1)	h_{FE1}	50		
Forward-current transfer ratio	3076	V_{CE} = -4 V dc; I_C = -20 A dc; pulsed (see 4.5.1)	h_{FE2}	30	120	
Forward-current transfer ratio	3076	V_{CE} = -4 V dc; I_C = -50 A dc; pulsed (see 4.5.1)	h_{FE3}	10		
Collector to emitter saturated voltage	3071	I_C = -20 A dc; pulsed (see 4.5.1) I_B = -2.0 A dc	$V_{CE(sat)1}$		1.0	V dc
Collector to emitter saturated voltage	3071	I_C = -50 A dc; I_B = -10 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		3.0	V dc
Base -emitter saturated voltage	3066	Test condition A; I_C = -20 A dc; I_B = -2.0 A dc; pulsed (see 4.5.1)	$V_{BE(sat)}$		1.8	V dc

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High-temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = +1.5 V dc	I_{CEX2}		1.0	mA dc
2N6378		V_{CE} = -120 V dc				
2N6379		V_{CE} = -140 V dc				
Low-temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = -4.0 V dc I_C = -20 A dc; pulsed (see 4.5.1)	h_{FE4}	10		
Subgroup 4						
Pulse response:	3251	Test condition A, except test circuit and pulse requirements in accordance with figure 3 herein.				
Turn-on time		V_{CC} = approximately -80 V dc; I_C = -20 A dc; I_B = -2.0 A dc;	t_{on}		0.5	µs
Turn-off time		V_{CC} = approximately 80 V dc; I_C = 20 A dc; I_{B1} = I_{B2} = 2.0 A dc	t_{off}		1.05	µs
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = -10 V dc; I_C = -1 A dc; f = 10 MHz	$\|h_{fe}\|$	3	12	
Open capacitance (open circuit)	3236	V_{CB} = -10 V dc; I_E = 0; 0.1 MHz ≤ f ≤ 1.0 MHz	C_{obo}		1500	pF
Subgroup 5						
Safe operating area (dc operation)	3051	T_C = +25°C t = 1 s; 1 cycle; (See figure 4)				
Test 1		V_{CE} = -5 V dc; I_C = -50 A dc				
(Both device types)						
* Test 2						
(Both device types)		V_{CE} = -8.6 V dc; I_C = -29 A dc				

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 5 - Continued						
Test 3						
2N6378 2N6379		V_{CE} = -80 V dc; I_C = 165 mA dc V_{CE} = -100 V dc; I_C = 130 mA dc				
Safe operating area (switching)	3053	Load condition C, (unclamped inductive load) (see figure 5) T_C = + 25°C; duty cycle ≤ 10 percent; R_s = 0.1 ohms; $t_r = t_f \leq 500$ ns				
Test 1		t_p approximately 5 ms (vary to obtain I_C); R_{BB1} = 2 ohms; V_{BB1} =-12 V dc; R_{BB2} = ∞; V_{BB2} = 0 V; I_C = 40 A dc; V_{CC} = -50 V dc; L = 100 µH; (4 each Miller type 7827 in parallel, 40 A), 0.04 ohm, or equivalent)				
Test 2		t_p approximately 5 ms (vary to obtain I_C;) R_{BB1} = 120ohms; V_{BB1} =12 V dc; R_{BB2} = ∞; V_{BB2} = 0 V; V_{CC} = -50 V dc; I_C = 850 mA dc; L = 100 µH; (- 80 + 20 mH 2 each Triad Transformer C-48u, in series), 0.713 ohm, or equivalent.				
Safe operating area (switching)	3053	Clamped inductive load T_A = + 25°C; condition B, duty cycle ≤ 5 percent; t_p approximately 1.5 ms (vary to obtain I_C) V_{CC} = -50 V dc; I_C = 50 A dc; V_{BB1} =-12 V dc; V_{BB2} = -1.5 V; R_{BB1} = 2 ohms; R_{BB2} = 100 ohms; $R_s \leq 0.1$ ohms; L = 370 µH (Miller 7827 or equivalent)				
2N6378		Clamp voltage = -100 V dc				
2N6379		Clamp voltage = -120 V dc				
Electrical measurements		Table I, subgroup 2 herein.				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF 19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

* TABLE II. Groups B, C, and E delta measurements. 1/ 2/ 3/ 4/ 5/

Steps	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector to emitter cutoff current 2N6378 2N6379	3041	Bias condition A; V_{BE} = +1.5 V dc V_{CE} = -120 V dc V_{CE} = -140 V dc	ΔI_{CEX1}		100 percent of initial value or 2 µA, whichever is greater.	
2.	Forward - current transfer ratio	3076	V_{CE} = -4 V dc; I_C = -20 A dc; pulsed (see 4.5.1)	Δh_{FE2}		± 25 percent change from initial reading.	
3.	Collector to emitter voltage (saturated)	3071	I_C = -2.0 A dc; I_B = -20 A dc, pulsed (see 4.5.1)	$\Delta V_{CE(sat)1}$		± 50 mV change from previously measured value.	


1/ See MIL-PRF-19500 for sampling plan.
2/ Devices which exceed the group A limits for this test shall not be acceptable.
3/ The delta measurements for table E-VIB (JAN, JANTX and JANTXV) of MIL-PRF-19500 are subgroup 6, see able II herein, steps 1 and 2.
4/ The delta measurements for table E-VII of MIL-PRF-19500 are as follows:
   a. Subgroup 2 and 3, see table II herein, step 1.
   b. Subgroup 6, see table II herein, steps 2 and 3.
5/ The delta measurements for table E-IX of MIL-PRF-19500 are subgroups 1 and 2, see table II herein, all steps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.


TABLE III. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	-55°C to +150°C, 500 cycles	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		Table I, subgroup 2 and table II herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated; T = 1,000 hours.	
Electrical measurements		Table I, subgroup 2 and table II herein.	
Subgroup 4			N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.



TURN-ON (t_{on}) TIME TEST CIRCUIT



TURN-OFF (t_{off}) TIME TEST CIRCUIT

FIGURE 3. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.




FIGURE 4. Maximum safe operating graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.




FIGURE 5. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).


d. The complete PIN, see 1.5 and 6.4.

e. For die acquisition, the letter version shall be specified (see figure 2 and 6.5.2).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.


6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

6.4.2 Unencapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level
JAN2N6378	JANTX2N6378	JANTXV2N6378
JAN2N6379	JANTX2N6379	JANTXV2N6379

6.5.2 List of PINs for unencapsulated devices. The following is a list of possible PINs available on this specification sheet. The qualified die suppliers with the applicable letter version (e.g., JANHCA2N6378) will be identified on the QML.

Base PIN	PINs for cage code 33178
2N6378 2N6379	JANHCA2N6378 JANHCA2N6379

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 693-1642 or DSN 850-6939.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
DLA - CC
* NASA - NA

Review activities:
Army - MI, SM
* Navy - AS, MC
* Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2021-107)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:40Z
Check the source to verify that this is the current version before use.