DETAIL SPECIFICATION SHEET

POWER PLANT (PP), TRAILER MOUNTED, TACTICAL

ADVANCED MEDIUM-SIZED MOBILE POWER SOURCES (AMMPS)

SIZE 30, 30 kW, MODE I (50/60 HERTZ)

PP-30 kW, 50/60 HERTZ on two 2.5 M200A1

This specification is approved for use within US Army Research Development and Engineering Command, Communications and Electronics Research and Development Center, Product Realization Directorate, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32496.

1. SCOPE

1.1 Scope. This specification sheet covers the detail requirements for a PP, size 30, 30 kW, mode I, PP-3105, NSN-6115-01-562-4009.

2. APPLICABLE DOCUMENTS

DRAWINGS

8358998 - Chassis, Trailer.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from: PROJECT MANAGER – MOBILE ELECTRIC POWER, 10205 BURBECK ROAD, SUITE 105, FT BELVOIR VA 22060-5863).

MILITARY

MIL-DTL-32496 ADVANCED MEDIUM-SIZED MOBILE POWER SOURCES

(Copies of these documents are available online at http://quicksearch.dla.mil/or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, Pa. 19111-5094).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:46Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be IAW TA-04-3105 and as specified herein.

3.2 Description. The PP shall consist of the following equipment:

a. Two each, generator sets, 30 kW, 50/60 hertz
b. Two each, modified trailer chassis, 2 1/2 ton, Family of Medium Tactical Vehicles
c. Trailer interface kit
d. Switchbox and cables
e. Ancillary equipment:

1. Fire extinguisher
2. Ground rods
3. Ground rod driver
4. Refueling accessories

3.3 Weight. The maximum weight of the PP shall not exceed 12,000 pounds (each trailer configuration not to exceed 6,000 pounds).

3.3.1 User equipment weight. The user equipment weight allowance shall be determined by subtracting the operational weight from the maximum weight. The user equipment weight for each trailer configuration shall not exceed 400 pounds.

3.3.2 Lunette eye weight. The maximum and minimum lunette eye weights of the PP (each trailer configuration) shall be:

a. Maximum: 600 pounds
b. Minimum: 200 pounds

3.4 Towing vehicle. The PP (each trailer configuration) shall be towed by 2 1/2 and 5 ton military vehicles.

3.5 PP identification. In PP configurations where the generator sets are located on separate trailers, Identification/Transportation Data Plate drawing 13229E5666 shall be the reference for data plate development, used to identify the following PP configurations:

a. 13229E5666A: trailer + generator set + switchbox
b. 13229E5666B: trailer + generator set + PP inter-connect cable with connector

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:46Z
Check the source to verify that this is the current version before use.

Concluding Material

Custodian:

Army - CR4

Preparing Activity:

Army - CR4
(Project 6115-2014-025)

Review Activities:

DLA – GS

Note: The activities listed above were interested in this document as of the date of this document. Since organization and responsibilities can change, you should verify the currency of the information above using ASSIST Online at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:46Z
Check the source to verify that this is the current version before use.