
INCH-POUND
MIL-PRF-32535/1
w/AMENDMENT 1
30 November 2017
SUPERSEDING
MIL-PRF-32535/1
28 September 2015

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, CHIP, FIXED, CERAMIC DIELECTRIC (GENERAL PURPOSE), EXTENDED RANGE, HIGH RELIABILITY AND STANDARD RELIABILITY, SIZE 0201

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-32535.



Dimensions			
L ± .003	W ± .001	T Max.	Y Min.
.024	.011	.013	.004

inches	mm
.001	0.03
.003	0.08
.004	0.10
.011	0.28
.013	0.33
.024	0.61

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Dimensions and tolerances are for terminated chips.
4. Minimum spacing between metalized end terminals is .008 inch (0.20 mm).

FIGURE 1. Size 0201 capacitors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Capacitance value: See table I.

Capacitance tolerance: See table I.

Voltage-temperature limit or temperature characteristic (VTL/TC): X7R as specified in MIL-PRF-32535.

Rated voltage (V_{dc}): V = 4; W = 6.3; X = 10. See table I for maximum rated voltage available for each capacitance value.

Operating temperature range: -55°C to +125°C.

Termination finish: G, H, M, and Z as specified in MIL-PRF-32535.

Electrode: P as specified in MIL-PRF-32535.

Product level designator: Standard reliability – M and high reliability - T.

Marking: Package marking only in accordance with MIL-PRF-32535.

TABLE I. Size 0201 capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance (pF)	Capacitance tolerance	VTL/TC	Rated voltage 2/ (V_{dc})
M3253501E2 - 102 - - - P	1,000	K, M	X7R	10
M3253501E2 - 122 - - - P	1,200	K, M	X7R	10
M3253501E2 - 152 - - - P	1,500	K, M	X7R	10
M3253501E2 - 182 - - - P	1,800	K, M	X7R	10
M3253501E2 - 222 - - - P	2,200	K, M	X7R	10
M3253501E2 - 272 - - - P	2,700	K, M	X7R	10
M3253501E2 - 332 - - - P	3,300	K, M	X7R	10
M3253501E2 - 392 - - - P	3,900	K, M	X7R	10
M3253501E2 - 472 - - - P	4,700	K, M	X7R	10
M3253501E2 - 562 - - - P	5,600	K, M	X7R	10
M3253501E2 - 682 - - - P	6,800	K, M	X7R	10
M3253501E2 - 822 - - - P	8,200	K, M	X7R	10
M3253501E2 - 103 - - - P	10,000	K, M	X7R	10

1/ The complete PIN shall include additional symbols to indicate voltage, capacitance tolerance, termination finish, and product level.
2/ This is the maximum rated voltage available. All lower voltage ratings are also available.

Amendment notations: The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:53Z
Check the source to verify that this is the current version before use.

Custodians:
Army – CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2017-046)

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
Other – MDA, NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:53Z
Check the source to verify that this is the current version before use.