The documentation and process conversion measures necessary to comply with this revision shall be completed by 10 January 2003.

INCH-POUND

MIL-PRF-19500/603D
10 October 2002
SUPERSEDING
MIL-PRF-19500/603C
15 November 1997

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED
(TOTAL DOSE ONLY) TRANSISTORS, N-CHANNEL, SILICON
TYPES 2N7268, 2N7269, 2N7270, 2N7394, 2N7268U, 2N7269U, 2N7270U, AND 2N7394U
JANTXVR, F, G, AND H; AND JANSR, F, G, AND H

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for an N-channel, enhancement-mode, MOSFET, radiation hardened (total dose only), power. Two levels of product assurance are provided for each device type specified in MIL-PRF-19500, with avalanche energy maximum rating (E_{AS}) and maximum avalanche current (I_{AS}).

1.2 Physical dimensions. See figure 1 (TO-254AA) and figure 2 (surface mount, T0-267AB).

* 1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Type	P_T (1)	P_T T_A = +25°C	V_{DS}	V_{DG}	V_{GS}	I_{D1} (2) (3)	I_{D2} T_C = +100°C	I_S (2)	I_{DM} (4)	T_{op} and T_{STG}	V_{ISO} 70,000 ft altitude
	W	W	V dc	V dc	V dc	A dc	A dc	A dc	A(pk)	°C	V dc
2N7394, 2N7394U	150	4	60	60	±20	35.0	30.0	35.0	200	-55	N/A
2N7268, 2N7268U	150	4	100	100	±20	34.0	21.0	34.0	136	to	N/A
2N7269, 2N7269U	150	4	200	200	±20	26.0	16.0	26.0	104		N/A
2N7270, 2N7270U	150	4	500	500	±20	11.0	7.0	11.0	44	+150	500

(1) Derate linearly 1.2 W/°C for T_C > +25°C;

(2) $$I_D = \sqrt{\frac{T_J \max - T_C}{(R_{\theta JC}) x (r_{DSon} \text{ at } T_J \max)}}$$

(3) I_{D1} may be limited by pin diameter.

(4) I_{DM} + 4 X I_{D1}; as calculated by footnote (2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 1.4 Primary electrical characteristics at T_C = +25°C.

Type	Min $V_{(BR)DSS}$ V_{GS} = 0 I_D = 1.0 mA dc	$V_{GS(TH)1}$ $V_{DS} \geq V_{GS}$ I_D = 1.0 mA dc		Max I_{DSS1} V_{GS} = 0 V_{DS} = 80 percent of rated V_{DS}	Max $r_{DS(ON)}$ (1) V_{GS} = 12 V dc		$R_{\theta JC}$ max	E_{AS} at I_{D1}	I_{AS}
					T_J = +25°C at I_{D2}	T_J = +150°C at I_{D2}			
	V dc	V dc		µA dc	ohm	ohm	°C/W	mJ	A
		Min	Max						
2N7394, 2N7394U	60	2.0	4.0	25	0.027	0.030	0.83	500	35.0
2N7268, 2N7268U	100	2.0	4.0	25	0.065	0.132	0.83	500	34.0
2N7269, 2N7269U	200	2.0	4.0	25	0.100	0.230	0.83	500	26.0
2N7270, 2N7270U	500	2.0	4.0	50	0.450	1.260	0.83	500	11.0

(1) Pulsed (see 4.5.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE


MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Services (DAPS), Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BL	.535	.545	13.59	13.89
CH	.249	.260	6.32	6.60
LD	.035	.045	0.89	1.14
LL	.510	.570	12.95	14.48
LO	.150 BSC		3.81 BSC	
LS	.150 BSC		3.81 BSC	
MHD	.139	.149	1.53	3.78
MHO	.665	.685	16.89	17.40
TL	.790	.800	20.07	20.32
TT	.040	.050	1.02	1.27
TW	.535	.545	13.59	13.89
Term 1	Drain			
Term 2	Source			
Term 3	Gate			



NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Refer to applicable symbol list.
4. Dimensioning and tolerating are in accordance with ASME Y14.5M.
5. All terminals are isolated from case.

* FIGURE 1. Physical dimensions for TO-254AA (2N7268, 2N7269, 2N7270, and 2N7394).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 2. Dimensions and configuration of surface mount package outline (T0-267AB) 2N7268U, 2N7269U, 2N7270U, AND 2N7394U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

Dimensions				
Symbol	SMD-1			
	Inches		Millimeters	
	Min	Max	Min	Max
BL	.620	.630	15.75	16.00
BW	.445	.455	11.30	11.56
CH		.142		3.60
LH	.010	.020	0.26	0.50
LL_1	.410	.420	10.41	10.67
LL_2	.152	.162	3.86	4.11
LS_1	.210 BSC		5.33 BSC	
LS_2	.105 BSC		2.67 BSC	
LW_1	.370	.380	9.40	9.65
LW_2	.135	.145	3.43	3.68
Q_1	.030		0.76	
Q_2	.035		0.89	
Term 1	Drain			
Term 2	Gate			
Term 3	Source			

NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. The lid shall be electrically isolated from the drain, gate and source.
4. Dimensioning and tolerancing shall be in accordance with ASME Y14.5M 1982.

* FIGURE 2. Dimensions and configuration of surface mount package outline (T0-267AB) 2N7268U, 2N7269U, 2N7270U, AND 2N7394U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

* 3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

* 3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows.

I_{AS} - Rated avalanche current, nonrepetitive.

* 3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figures 1 and 2 herein. Methods used for electrical isolation of the terminal feedthroughs shall employ materials that contain a minimum of 90 percent AL_2O_3 (ceramic). Examples of such construction techniques are metallized ceramic eyelets or ceramic walled packages.

3.4.1 Lead material and finish. Lead material shall be Kovar or Alloy 52; a copper core or plated core is permitted. Lead finish shall be solderable in accordance with MIL-PRF-19500 and herein. Where a choice of lead material or finish is desired, it shall be specified in the contract or order (see 6.5).

* 3.4.2 Internal construction. Multiple chip construction is not permitted.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrostatic discharge protection. The devices covered by this specification require electrostatic discharge protection.

3.6.1 Handling. MOS devices must be handled with certain precautions to avoid damage due to the accumulation of static charge. However, the following handling practices are recommended (see 3.6).

a. Devices should be handled on benches with conductive handling devices.

b. Ground test equipment, tools, and personnel handling devices.

c. Do not handle devices by the leads.

d. Store devices in conductive foam or carriers.

e. Avoid use of plastic, rubber, or silk in MOS areas.

f. Maintain relative humidity above 50 percent if practical.

g. Care should be exercised during test and troubleshooting to apply not more than maximum rated voltage to any lead.

h. Gate must be terminated to source, $R \leq 100$ k, whenever bias voltage is to be applied drain to source.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4 and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 3.8 Electrical test requirements. The electrical test requirements shall be table I, group A as specified herein.

* 3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

* 4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I, II, and III).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the associated specification that did not request the performance of table III tests, the tests specified in table III herein shall be performed by the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (JANTXV and JANS levels only). Screening shall be in accordance with appendix E, table IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTXV levels
(1)	Method 3470 of MIL-STD-750 (see 4.5.4)	Method 3470 of MIL-STD-750 (see 4.5.4)
(1)	Method 3161 of MIL-STD-750 (see 4.5.3)	Method 3161 of MIL-STD-750 (see 4.5.3)
(1)	Gate stress test (see 4.5.5)	Gate stress test (see 4.5.5)
(1) 9	Subgroup 2 of table II herein. I_{GSS}, I_{DSS1}	Subgroup 2 of table I herein
10	Method 1042 of MIL-STD-750 , test condition B	Method 1042 of MIL-STD-750 , test condition B
11	I_{GSSF1}, I_{GSSR1}, I_{DSS1}, $r_{DS(on)}$, $V_{GS(TH)}$ Subgroup 2 of table I herein ΔI_{GSSF1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{DSS1} = ± 10 μA dc or ± 100 percent of initial value, whichever is greater.	I_{GSSF1}, I_{GSSR1}, I_{DSS1}, $r_{DS(on)}$, $V_{GS(TH)}$ Subgroup 2 of table I herein
12	Method 1042 of MIL-STD-750, test condition A	Method 1042 of MIL-STD-750, test condition A
13	Subgroups 2 and 3 of table I herein ΔI_{GSSF1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{DSS1} = ± 10 μA dc or ± 100 percent of initial value, whichever is greater. $\Delta r_{DS(on)1}$ = ± 20 percent of initial value $\Delta V_{GS(th)1}$ = ± 20 percent of initial value	Subgroups 2 and 3 of table I herein ΔI_{GSSF1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ± 20 nA dc or ± 100 percent of initial value, whichever is greater. ΔI_{DSS1} = ± 10 μA dc or ± 100 percent of initial value, whichever is greater. $\Delta r_{DS(on)1}$ = ± 20 percent of initial value $\Delta V_{GS(th)1}$ = ± 20 percent of initial value

(1) Shall be performed anytime before screen 10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein. Alternate flow is allowed for conformance inspection in accordance with appendix E, of MIL-PRF-19500.

* 4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with appendix E, table V of MIL-PRF-19500 and table I herein. End-point electrical measurements shall be in accordance with table I, group A, subgroup 2 herein.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table VIa (JANS) and table VIb (JANTX and JANTXV) of MIL-PRF-19500, and herein. Electrical measurements (end-points) and delta requirements shall be in accordance with table I, group A, subgroup 2 herein.

* 4.4.2.1 Group B inspection, appendix E, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1051	Test condition G, 100 cycles.
B3	2075	See 3.4.2.
B3	2077	SEM qualification may be performed anytime prior to lot formation.
B4	1042	The heating cycle shall be 30 seconds minimum.
B5	1042	Accelerated steady-state reverse bias, condition B, V_{GS} = rated, T_A = +175°C, t = 24 hours minimum; or, T_A = +150°C, t = 48 hours minimum.
B5	1042	Accelerated steady-state reverse bias, condition A, V_{DS} = rated, T_A = +175°C, t = 120 hours minimum; or, T_A = +150°C, t = 240 hours minimum.
B5	2037	Bond strength (Al-Au die interconnects only); test condition A.
B6	3161	See 4.5.2.

4.4.2.2 Group B inspection, appendix E, table VIb (JANTX and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B2	1051	Test condition G, 25 cycles.
B3	1042	The heating cycle shall be 30 seconds minimum.
B4	2075	See 3.4.2.
B4	2037	Test condition A. All internal bond wires for each device shall be pulled separately.
B5 and B6		Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table VII of MIL-PRF-19500 and as follows. Electrical measurements (end-points) and delta requirements shall be in accordance with table I, group A, subgroup 2 herein.

Subgroup	Method	Condition
C2	2036	Test condition A; weight = 10 pounds; t = 15 s (applicable to TO-254AA only).
C5	1001	Test condition C. For device type 2N7270, 2N7270U: V_{DS} = 500 V; $I_{(ISO)}$ < 0.25 mA.
C6	1042	The heating cycle shall be 30 seconds minimum.

* 4.4.4 Group D Inspection. Group D inspection shall be conducted in accordance with appendix E, table VIII of MIL-PRF-19500 and table II herein.

* 4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table IX of MIL-PRF-19500 and as specified herein. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in MIL-STD-750.

4.5.2 Thermal resistance. Thermal resistance measurements shall be performed in accordance with method 3161 of MIL-STD-750. The maximum limit of $R_{\theta JC(max)}$ = 0.83°C/W. The following parameter measurements shall apply:

a. Measuring current (I_M) ..... 10 mA.

b. Drain heating current (I_H) ..... 4 A minimum.

c. Heating time (t_H) ..... Steady-state (see method 3161 of MIL-STD-750 for definition).

d. Drain-source heating voltage (V_H)..... 25 V (20 V for “U” suffix devices).

e. Measurement time delay (t_{MD}) ..... 30 to 60 μs.

f. Sample window time (t_{SW}) ..... 10 μs maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* 4.5.3 Thermal impedance ($Z_{\theta JC}$ measurements). The $Z_{\theta JC}$ measurements shall be performed in accordance with method 3161 of MIL-STD-750. The maximum limit (not to exceed figure 3, thermal impedance curves and the table I, group A, subgroup 2 limits) for $Z_{\theta JC}$ in screening (appendix E, table VI of MIL-PRF-19500) shall be derived by each vendor by means of statistical process control. When the process has exhibited control and capability, the capability data shall be used to establish the fixed screening limit. In addition to screening, once a fixed limit has been established, monitor all future sealing lots using a random five piece sample from each lot to be plotted on the applicable X, R chart. If a lot exhibits an out of control condition, the entire lot shall be removed from the line and held for engineering evaluation and disposition. This procedure may be used in lieu of an in-line monitor.

a. Measuring current (I_M) ..... 10 mA.

b. Drain heating current (I_H) ..... 4 A minimum.

c. Heating time (t_H) ..... 100 ms (30 ms for “U” suffix devices).

d. Drain-source heating voltage (V_H)..... 25 V (20 V for “U” suffix devices).

e. Measurement time delay (t_{MD}) ..... 30 to 60 μs.

f. Sample window time (t_{SW})..... 10 μs maximum.

* 4.5.4 Single pulse avalanche energy E_{AS}.

a. Peak current (I_{AS}) ..... $I_{AS(max)}$.

b. Peak gate voltage (V_{GS}) ..... 12 V.

c. Gate to source resistor (R_{GS})..... $25\Omega \leq R_{GS} \leq 200\Omega$.

d. Initial case temperature (T_C) ..... +25°C +10°C, -5°C.

e. Inductance (L) ..... $L = (2*E_{AS}/(I_{D1})^2)*((V_{BR}-V_{DD})/V_{BR})$ mH minimum.

f. Number of pulses to be applied ..... 1 pulse minimum.

g. Supply voltage (V_{DD}) ..... 25 V for 2N7268, 2N7394, and 2N7268U; 50 V for 2N7269, 2N7269U, and 2N7270.

4.5.5 Gate stress test. Apply V_{GS} = 30 V minimum for t = 250 μs minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical inspection	2071					
Subgroup 2						
Thermal impedance 2/	3161	See 4.5.3 TO-254 surface mount devices	$Z_{\theta JC}$		0.60 0.45	°C/W °C/W
Breakdown voltage, drain to source	3407	V_{GS} = 0 V; I_D = 1 mA dc bias condition C	$V_{(BR)DSS}$			
2N7394, 2N7394U				60		V dc
2N7268, 2N7268U				100		V dc
2N7269, 2N7269U				200		V dc
2N7270, 2N7270U				500		V dc
Gate to source voltage threshold	3403	$V_{DS} \geq V_{GS}$ I_D = 1 mA dc	$V_{GS(TH)1}$	2.0	4.0	V dc
Gate current	3411	V_{GS} = +20 and -20 V dc V_{DS} = 80 percent of rated V_{DS}	I_{GSS1}		± 100	nA dc
Drain current	3413	V_{GS} = 0 V dc, bias condition C V_{DS} = 80 percent of rated V_{DS}	I_{DSS1}			
2N7394, 2N7394U					25	µA dc
2N7268, 2N7268U					25	µA dc
2N7269, 2N7269U					25	µA dc
2N7270, 2N7270U					50	µA dc
Static drain to source “ON”-state resistance	3421	V_{GS} = 12 V dc, condition A pulsed (see 4.5.1), $I_D = I_{D2}$	$r_{DS(on)1}$			
2N7394, 2N7394U					0.027	ohm
2N7268, 2N7268U					0.065	ohm
2N7269, 2N7269U					0.100	ohm
2N7270, 2N7270U					0.450	ohm
Static drain to source “ON”-state resistance	3421	V_{GS} = 12 V dc, condition A pulsed (see 4.5.1), $I_D = I_{D1}$	$r_{DS(on)2}$			
2N7394, 2N7394U					0.030	ohm
2N7268, 2N7268U					0.070	ohm
2N7269, 2N7269U					0.110	ohm
2N7270, 2N7270U					0.500	ohm
Forward voltage	4011	Pulsed (see 4.5.1), $I_D = I_{D1}$ V_{GS} = 0 V dc	V_{SD}			
2N7394, 2N7394U					1.4	V
2N7268, 2N7268U					1.4	V
2N7269, 2N7269U					1.4	V
2N7270, 2N7270U					1.6	V

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		$T_C = T_J = +125°C$				
Gate current	3411	V_{GS} = +20 and -20 V dc bias condition C, V_{DS} = 0	I_{GSS2}		± 200	nA dc
Drain current	3413	V_{GS} = 0 V; bias condition C				mA dc
		V_{DS} = 100 percent of rated V_{DS}	I_{DSS2}		1.0	
		V_{DS} = 80 percent of rated V_{DS}	I_{DSS3}		0.25	mA dc
Static drain to source "ON"-state resistance	3421	V_{GS} = 12 V dc pulsed (see 4.51), $I_D = I_{D2}$	$r_{DS(on)3}$			
2N7394, 2N7394U					0.060	ohm
2N7268, 2N7268U					0.132	ohm
2N7269, 2N7269U					0.200	ohm
2N7270, 2N7270U					1.000	ohm
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1 mA dc	$V_{GS(TH)2}$	1.0		V dc
Low temperature operation:		$T_C = T_J = +55°C$				
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1 mA dc	$V_{GS(TH)3}$		5.0	V dc
Subgroup 4						
Forward transconductance	3475	I_D = rated I_{D2}, V_{DD} = 15 V (see 4.5.1)	g_{FS}			
2N7394, 2N7394U				12		S
2N7268, 2N7268U				8		S
2N7269, 2N7269U				8		S
2N7270, 2N7270U				4		S
Switching time test	3472	$I_D = I_{D1}$, V_{GS} = 12 V dc R_G = 2.35Ω, V_{DD} = 50 percent of rated V_{DS}				
Turn-on delay time			$t_{d(on)}$			
2N7394, 2N7394U					27	ns
2N7268, 2N7268U					45	ns
2N7269, 2N7269U					33	ns
2N7270, 2N7270U					45	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Rise time			t_r			
2N7394, 2N7394U					100	ns
2N7268, 2N7268U					190	ns
2N7269, 2N7269U					140	ns
2N7270, 2N7270U					190	ns
Turn-off delay time			$t_{d(off)}$			
2N7394, 2N7394U					75	ns
2N7268, 2N7268U					170	ns
2N7269, 2N7269U					140	ns
2N7270, 2N7270U					190	ns
Fall time			t_f			
2N7394, 2N7394U					75	ns
2N7268, 2N7268U					130	ns
2N7269, 2N7269U					140	ns
2N7270, 2N7270U					130	ns
Subgroup 5	3474					
Safe operating area test (high voltage)		See figures 4, 5, 6 and 7 t_p = 10 ms minimum V_{DS} = 80 percent of maximum rated V_{DS}, ($V_{DS} \leq 200$)				
Electrical measurements		See table I, group A, subgroup 2				
Subgroup 6						
Not applicable						
Subgroup 7						
Gate charge	3471	Condition B				
On-state gate charge			$Q_{g(on)}$			
2N7394, 2N7394U					200	nC
2N7268, 2N7268U					160	nC
2N7269, 2N7269U					170	nC
2N7270, 2N7270U					150	nC

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 7 - Continued						
Gate to source charge			Q_{gs}			
2N7394, 2N7394U					60	nC
2N7268, 2N7268U					35	nC
2N7269, 2N7269U					30	nC
2N7270, 2N7270U					30	nC
Gate to drain charge			Q_{gd}			
2N7394, 2N7394U					75	nC
2N7268, 2N7268U					65	nC
2N7269, 2N7269U					60	nC
2N7270, 2N7270U					75	nC
Reverse recovery time	3473	di/dt ≤ 100 A/μs, V_{DD} ≤ 30 V, $I_D = I_{D1}$	t_{rr}			
2N7394, 2N7394U					280	ns
2N7268, 2N7268U					570	ns
2N7269, 2N7269U					820	ns
2N7270, 2N7270U					1,100	ns

1/ For sampling plan, see MIL-PRF-19500.
2/ This test is required for the following end-point measurements only (not intended for screen 13):
JANS - table VIa of MIL-PRF-19500, group B, subgroups 3 and 4;
JANTX and JANTXV - table VIb of MIL-PRF-19500, group B, subgroups 2 and 3;
table VII of MIL-PRF-19500, group C, subgroup 6;
table IX of MIL-PRF-19500, group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE II. Group D inspection.

Inspection 1/ 2/	MIL-STD-750		Symbol	Preirradiation limits				Postirradiation limits				Unit
	Method	Conditions		R		3/ F, G, and H		R		3/ F, G, and H		
				Min	Max	Min	Max	Min	Max	Min	Max	
Subgroup 1												
Not applicable												
Subgroup 2		T_C = +25°C										
Steady-state total dose irradiation (V_{GS} bias) 4/	1019	V_{GS} = 12 V V_{DS} = 0										
Steady-state total dose irradiation (V_{DS} bias) 4/	1019	V_{GS} = 0 V_{DS} = 80 percent of rated V_{DS} (pre-irradiation)										
End-point electricals												
Breakdown voltage, drain to source	3407	V_{GS} = 0; I_D = 1 mA bias cond. C	V_{BRDSS}									
2N7394, 2N7394U				60		60		60		60		V dc
2N7268, 2N7268U				100		100		100		100		V dc
2N7269, 2N7269U				200		200		200		200		V dc
2N7270, 2N7270U				500		500		500		500		V dc
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$ I_D = 1 mA	V_{GSth}									
2N7394, 2N7394U				2	4	2	4	2	4	1.25	4.50	V dc
2N7268, 2N7268U				2	4	2	4	2	4	1.25	4.50	V dc
2N7269, 2N7269U				2	4	2	4	2	4	1.25	4.50	V dc
2N7270, 2N7270U				2	4	2	4	2	4	1.25	4.50	V dc
Gate current	3411	V_{GS} = 20 V V_{DS} = 0 bias cond. C	I_{GSSF1}		100		100		100		100	nA dc
Gate current	3411	V_{GS} = 20 V V_{DS} = 0 bias cond. C	I_{GSSR1}		-100		-100		-100		-100	nA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

* TABLE II. Group D inspection - Continued.

Inspection 1/ 2/	MIL-STD-750		Symbol	Preirradiation limits				Postirradiation limits				Unit
	Method	Conditions		R		3/ F, G, and H		R		3/ F, G, and H		
				Min	Max	Min	Max	Min	Max	Min	Max	
Subgroup 2 - Continued												
Drain current	3413	V_{GS} = 0 Bias cond. C V_{DS} = 80 percent of rated V_{DS} (pre-irradiation)	I_{DSS}									
2N7394, 2N7394U					25		25		25		50	µA dc
2N7268, 2N7268U					25		25		25		50	µA dc
2N7269, 2N7269U					25		25		25		50	µA dc
2N7270, 2N7270U					50		50		50		100	µA dc
Static drain to source on-state voltage	3405	V_{GS} =12 V Condition A pulsed see 4.5.1 $I_D = I_{D2}$	V_{DSon1}									
2N7394, 2N7394U					0.81		0.81		0.81		1.2	Vdc
2N7268, 2N7268U					1.365		1.365		1.365		1.89	Vdc
2N7269, 2N7269U					1.6		1.6		1.6		2.48	Vdc
2N7270, 2N7270U					3.15		3.15		3.15		4.2	Vdc
Forward voltage source drain diode	4011	V_{GS} = 0 V $I_D = I_{D1}$	V_{SD}									
2N7394, 2N7394U					1.4		1.4		1.4		1.4	Vdc
2N7268, 2N7268U					1.4		1.4		1.4		1.4	Vdc
2N7269, 2N7269U					1.4		1.4		1.4		1.4	Vdc
2N7270, 2N7270U					1.6		1.6		1.6		1.6	Vdc

* 1/ For sampling plan, see MIL-PRF-19500. At the manufacturer's option, group D samples need not be subjected to the screening tests, and may be assembled in it's qualified package or in any qualified package that the manufacturer has data to correlate the performance to the designated package.

2/ Group D qualification may be performed anytime prior to lot formation. Wafers qualified to these group D QCI requirements may be used for any other detail specification utilizing the same die design.

3/ The F designation represent devices which pass end-points at both 100 k and 300 k rads (Si). The G designation represents devices which pass 100 k, 300 k, and 600 k rad (Si) end-points. H must meet end-points for 100 k, 300 k, 600 k and 1,000 k RAD (Si).

4/ Separate samples shall be pulled for each bias.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) for qualification only.

Inspection	MIL-STD-750		Qualification and large lot quality conformance inspection
	Method	Conditions	
Subgroup 1			12 devices c = 0
Thermal shock (temperature cycling)	1051	Test condition G.	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, group A, subgroup 2.	
Subgroup 2 1/			12 devices c = 0
Steady-state gate bias	1042	Condition B, 1,000 hours.	
Electrical measurements		See table I, group A, subgroup 2.	
Steady-state reverse bias	1042	Condition A, 1,000 hours.	
Electrical measurements		See table I, group A, subgroup 2.	
Subgroup 3			
Not applicable			
Subgroup 4			12 devices c = 0
Thermal resistance	3161	$R_{\theta JC}$ = 0.83 °C/W maximum. See 4.5.2.	

1/ A separate sample may be pulled for each test condition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 3. Thermal impedance curves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 4. Safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 5. Safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 6. Safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.




FIGURE 7. Safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

* 6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

* 6.2 Acquisition requirements. The acquisition requirements are as specified in MIL-PRF-19500.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers' List (QML) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43216-5000.

6.4 Substitution information. Devices covered by this specification are substitutable for the manufacturer's and user's Part or Identifying Number (PIN). This information in no way implies that manufacturer's PIN's are suitable for the military PIN.

Preferred types	Commercial types (1)	
	TO254-AA	“U”
2N7394	IRHM7054	IRHN 054
2N7268	IRH7150	IRHN 150
2N7269	1RH7250	IRHN 250
2N7270	1RH7450	IRHN 450

(1) IRH 7: 100k RAD (Si)
IRH 3: 300k RAD (Si)
IRH 4: 600k RAD (Si)
IRH 8: 1,000k RAD (Si)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

6.5 Ordering data. Acquisition documents may specify the material and finish (see 3.4.1).

* 6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - MI
Navy - TD
Air Force - 19, 70

Preparing activity:
DLA - CC

(Project 5961- 2648)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/603D	2. DOCUMENT DATE 10 October 2002

3. **DOCUMENT TITLE**
SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED (TOTAL DOSE ONLY) TRANSISTORS, N-CHANNEL, SILICON TYPES 2N7268, 2N7269, 2N7270, 2N7394, 2N7268U, 2N7269U, 2N7270U, AND 2N7394U JANTXVR, F, G, AND H; AND JANSR, F, G, AND H

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) COMMERCIAL DSN FAX EMAIL	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. Point of Contact Alan Barone	b. TELEPHONE Commercial 614-692-0510	DSN 850-0510	FAX 614-692-6939	EMAIL alan.barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus ATTN: DSCC-VAC P.O. Box 3990 Columbus, OH 43216-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533 Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888			

DD Form 1426, Feb 1999 (EG) Previous editions are obsolete WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:00Z
Check the source to verify that this is the current version before use.