MILITARY SPECIFICATION

BAKERY EQUIPMENT, INCLUDING UNIT ASSEMBLIES, REPAIR PARTS AND TOOLS, PREPARATION FOR DELIVERY OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the preservation, packaging, packing and marking for shipment of bakery equipment and related items designated for use in garrison bread bakeries.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-P-664	-	Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
PPP-B-591	-	Boxes, Fiberboard Wood-Cleated.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible.
PPP-B-1163	-	Box, Corrugated Fiberboard, High Compression Strength, Weather-Resistant, Wax-Resin Impregnated.
PPP-B-1364	-	Box, Corrugated Fiberboard, High Strength, Weather-Resistant, Double-Wall.
PPP-C-650	-	Crates, Wood, Open and Covered.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

PPP-F-320	-	Fiberboard; Corrugated and Solid Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-40	-	Packaging and Packing of Hand Tools.
PPP-T-60	-	Tape: Packaging, Waterproof.

MILITARY

MIL-V-3	-	Valves, Fittings, and Flanges (Except for Systems Indicated Herein); Packaging of.
MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation, Methods of.
MIL-P-551	-	Pipes and Elbows, Air Conditioning - Heating.
MIL-R-3593	-	Refrigeration and Cooling Equipment (Excluding Household Refrigerators), Packaging of.
MIL-C-3774	-	Crates, Wood; Open 12,000-and 16,000-Pound Capacity.
MIL-E-16298	-	Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1186	-	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; With Appropriate Test Methods.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of parts susceptible to damage during transit or storage and for the reduction in cubage. Attaching hardware shall be replaced on one of the mating parts or placed in a cloth drawstring bag and the bag attached to one of the mating parts. Parts removed shall be adequately identified or tagged. Where disassembly affects the operation of the equipment, warning tags or labels indicating the dissasembly shall be attached. Instructions for assembly shall be included either as a part of the warning tag, or label, or as a separate sheet or folder attached to the equipment. Disassembly shall not be such that special skills or special tools, other than those furnished, or both, are required to place the equipment in operation.

3.2 Draining. All water or fuel containing parts, such as water cooling systems, tanks, burners, and hoses, shall be completely drained and thoroughly dried.

3.3 Cleaning. All exposed, uncoated machined surfaces and critical operating surfaces shall be cleaned according to process C-5 and all other exposed, uncoated, ferrous metal surfaces shall be cleaned per process C-1, and thoroughly dried in accordance with MIL-P-116.

3.4 Repainting and recoating. Painted and permanently coated surfaces from which the paint and permanent coating have been removed or on which the finish is defective shall be repainted and recoated with material identical to the original.

3.5 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

3.5.1 Level A.

3.5.1.1 Lubrication. All bearings and fittings requiring lubrication shall be lubricated to capacity with the manufacturer's recommended lubricant containing a rust inhibitor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

* 3.5.1.2 Gasoline tanks. After draining and drying, the interior of the gasoline tanks shall be fogged with type P-10 preservative of MIL-P-116 and then pressure fogged with type P-18 preservative in accordance with MIL-P-116. The cap shall be replaced and the breather hole sealed with tape conforming to PPP-T-60.

3.5.1.3 Burners, combustion chamber, and radiators. Burners, combustion chamber, and radiators shall be coated with type P-7 preservative of MIL-P-116.

3.5.1.4 Pulleys. Drive belts shall be removed and exposed, uncoated ferrous metal surfaces of pulleys and shafts shall be coated with primer conforming to TT-P-664, and thoroughly dried. The belts shall then be replaced and tension relieved.

3.5.1.5 General preservation. Preservation of equipment and related parts not specified shall be as follows: All cleaned contacting surfaces (surfaces that contact other surfaces in operation), except food contacting surfaces, shall be coated with type P-2 preservative of MIL-P-116. All cleaned noncontacting surfaces (surfaces that do not contact other surfaces in operation), except food contacting surfaces, shall be coated with type P-1 preservative of MIL-P-116. All cleaned, uncoated ferrous metal surfaces which will be in contact with food ingredients shall be coated with type P-14 preservative of MIL-P-116.

3.5.1.6 Protection of preservative. Coated surfaces, from which preservative might be removed by contact with packaging and packing materials, shall be covered, wrapped, or bagged with greaseproof barrier material in accordance with method I of MIL-P-116.

3.5.1.7 Electrical motors. All open type motors not exceeding 40 pounds in weight, disassembled from the basic unit, shall be preserved in accordance with method II of MIL-P-116, with selection of the submethod at the option of the manufacturer. Totally enclosed motors shall not require any preservation other than that specified in 3.5.1.1.

3.5.1.8 Technical literature. Technical literature shall be packaged in accordance with method IC-1 of MIL-P-116, and secured to the parent unit.

* 3.5.1.9 Sealing. Lamps, electric cable connections, receptacles, switches, terminals, openings into motors, instruction and identification plates, control boxes, gages, meters, locks, key openings, and crevices formed by covers or lids shall be completely sealed with tape conforming to PPP-T-60. Remaining openings into the units shall also be sealed with the same type tape as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

3.5.1.10 Refrigeration and cooling systems. Refrigeration and cooling systems shall be processed in accordance with MIL-R-3593.

3.5.1.11 Miscellaneous items and accessories. Miscellaneous items and accessories shall be preserved and packaged in accordance with the applicable requirements of the following specifications:

Electrical equipment	MIL-E-16298
Hand tools	PPP-P-40
Pipe and elbows	MIL-P-551
Valves, fittings, and flanges	MIL-V-3

3.5.1.12 Securing. Parts of the equipment that are free to move shall be secured in a fixed position to prevent movement or vibration while in transit.

3.5.1.13 Disassembled components, tools, and accessories. Disassembled components, tools, and accessories shall be packaged in a fiberboard or nailed wood box conforming to style optional, type CF or SF class domestic of PPP-B-636, or class 1, style 2 or 4 of PPP-B-621, respectively. The weight of contents shall not exceed the weight limitations of the applicable box specification. Contents shall be cushioned, blocked, or braced within the box to prevent movement while in transit. Each box shall be securely closed in accordance with the appendix of the applicable box specification. A disassembled component considered too large or heavy to package may be packed directly into a shipping container or with its parent item.

3.5.2 Level C. Bakery equipment, units, assemblies, repair parts and tools shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from supply source to first receiving activity. The supplier may use his standard practice when it meets these requirements.

3.6 Packing. Packing shall be level A, B, or C as specified (see 6.2).

3.6.1 Level A.

* 3.6.1.1 Bakery equipment not exceeding 65 pounds. Bakery equipment, units, and assemblies not exceeding 65 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting fiberboard shipping container conforming to style optional, V2s of PPP-B-636. Fiberboard pads or forms conforming to PPP-F-320 shall be used, as required, to prevent movement or damage of the contents during transit. Each shipping container shall be closed, waterproofed, and reinforced with flat steel strapping or tape banding in accordance with PPP-B-636. Bakery equipment, units, and assemblies

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

weighing 40 pounds or less, preserved and packaged as specified in 3.5, shall be packed in containers conforming to style optional, V3s of PPP-B-636. Cushioning of contents, and closure, waterproofing, and reinforcing of shipping containers shall also be as specified in PPP-B-636.

* 3.6.1.2 Bakery equipment not exceeding 1000 pounds, except as specified in 3.6.1.4. Bakery equipment, units, and assemblies not exceeding 1000 pounds, preserved and packaged as specified in 3.5, shall be packed in wood-cleated plywood or nailed wood shipping containers conforming to overseas type of PPP-B-601 or class 2, style 2, 4, or 7, type 3 load of PPP-B-621, respectively. Alternatively, a shipping container as specified in 3.6.1.3 may be used at the option of the contractor for equipment, units, and assemblies weighing from 500 to 1000 pounds. Each shipping container exceeding 200 pounds gross weight shall be provided with skids as specified in the applicable container specification. Contents shall be secured as specified in 3.6.1.5. The top, sides, and ends of the nailed wood shipping container conforming to style 7 of PPP-B-621 shall be lined with waterproof barrier material conforming to PPP-B-1055, with all joints having a 4-inch minimum single lap. The contents of each shipping container conforming to style 2 or 4 of PPP-B-621 shall be waterproofed in accordance with the appendix of PPP-C-650. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

* 3.6.1.3 Bakery equipment exceeding 1000 pounds, except as specified in 3.6.1.4. Bakery equipment, units, and assemblies exceeding 1000 pounds, preserved and packaged as specified in 3.5, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104. Contents shall be secured as specified in 3.6.1.5.

3.6.1.4 Troughs, racks, cabinets, and stands.

(a) Weight not exceeding 200 pounds.
Troughs, racks, cabinets, and stands not exceeding 200 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting wood-cleated fiberboard shipping container conforming to class II of PPP-B-591. Equipment having nondetachable casters or wheels shall be blocked in such a manner as to have a minimum clearance of 1 inch between the interior base or end of the container and the casters or wheels.

(b) Weight not exceeding 2,500 pounds.
Troughs, racks, cabinets, and stands not exceeding 2,500 pounds, preserved and packaged as specified in 3.5, shall be packed in an open wood crate conforming to type I, II, IV, or V, style A of PPP-C-650. Each shipping container shall be closed, strapped, and waterproofed in accordance with the appendix of the container specification. Contents shall be secured as specified in 3.6.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

3.6.1.5 Securing. Equipment provided with bolt holes for anchoring shall be secured to the base of the shipping container by bolting through the skids. When bolt holes and the skids are not in alignment, additional skids, longitudinal sleepers, or interior load bearing members shall be provided. The minimum size of the sleepers, or interior load bearing members shall be nominal 2- by 4- inch lumber 2 feet long. Blocking and bracing shall be provided as required to prevent sway of topheavy items. When bolt holes in the equipment being packed are not available, the equipment shall be blocked and braced in a manner to prevent movement and damage while in transit. Equipment having nondetachable casters or wheels shall be blocked in such a manner as to have a minimum clearance of 1 inch between the interior base or end of the container and the casters or wheels. A clearance of not less than 1 inch shall be provided between the items and the closest member of the sides, ends, and top of the shipping container. Cushioning and padding shall be used where necessary to prevent damage between the lumber blocking and unprotected finished surfaces. Wood blocks and braces shall be securely nailed to floorboards, headers, or other frame members when present. The blocking and bracing shall not depend on end-grain nailing alone but supplemental supporting cleats shall be provided to reinforce and prevent splitting of the blocking and bracing.

3.6.1.6 Stowage of boxed components. Boxes containing items to be shipped with a unit or assembly shall be securely fastened in an unused portion within the shipping container of that unit or assembly.

3.6.2 Level B.

* 3.6.2.1 Bakery equipment not exceeding 160 pounds. Bakery equipment, units, and assemblies not exceeding 160 pounds, preserved and packaged as specified in 3.5, shall be packed, unless otherwise specified (see 6.2), in a snug-fitting fiberboard shipping container conforming to style optional, type CF or SF, class domestic of PPP-B-636. When specified (see 6.2) fiberboard shipping containers conforming to style optional, V3c, V3s, or V4s of PPP-B-636, class 2, style G of PPP-B-640, SW or DW of PPP-B-1163 or PPP-B-1364 shall be used. Each shipping container shall be closed in accordance with the appendix of the applicable container specification. The weight of contents shall not exceed the weight limitations for the applicable grade of the specification of the container used. The contents of each container shall be immobilized in accordance with MIL-STD-1186.

* 3.6.2.2 Bakery equipment not exceeding 400 pounds. Bakery equipment, units, and assemblies not exceeding 400 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting wood-cleated fiberboard shipping container conforming to class 1, style A or B of PPP-B-591. Each shipping container exceeding 200 pounds gross weight shall be provided with skids as specified in PPP-B-591 or provisions for handling with power equipment such

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

as fork lift trucks. Other provisions for handling shall be by wood strips bolted to the base of the appliance and secured to the inside face of the bottom of the shipping container. These internal members shall be positioned so as to assure protection to the container and contents when handling with power equipment. When internal strips are used, the container shall be marked to indicate two opposite sides intended for fork lift truck handling.

* 3.6.2.3 Bakery equipment not exceeding 1000 pounds. Bakery equipment, units, and assemblies not exceeding 1000 pounds, preserved and packaged as specified in 3.5, shall be packed in wood-cleated plywood or nailed wood shipping containers conforming to domestic type, style A or B of PPP-B-601 or class 1, style 2, 4, or 7, with diagonals as required, of PPP-B-621, respectively. Each shipping container shall be provided with skids as specified in the applicable container specification, and the contents secured as specified in 3.6.1.5.

* 3.6.2.4 Bakery equipment not exceeding 4,000 pounds. Bakery equipment, units, and assemblies not exceeding 4,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a wood crate conforming to style A, type IV or style B, type I, II, or V of PPP-C-650. Contents shall be secured as specified in 3.6.1.5.

* 3.6.2.5 Bakery equipment weighing from 4,000 to 12,000 pounds. Bakery equipment, units, and assemblies weighing from 4,000 to 12,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a wood crate conforming to type I, style A of MIL-C-3774. Contents shall be secured as specified in 3.6.1.5.

3.6.2.6 Bakery equipment exceeding 12,000 pounds. Bakery equipment, units and assemblies exceeding 12,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104, except that waterproof barrier material shall not be required. Contents shall be secured as specified in 3.6.1.5.

3.6.2.7 Stowage of boxed components. Stowage of boxed components shall be as specified in 3.6.1.6.

* 3.6.3 Level C. Bakery equipment, units, and assemblies, preserved and packaged as specified in 3.5, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

3.7 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Set marking requirements shall apply when accessories and parts are packed separate from the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

3.7.1 Precautionary marking. Special handling marking requirements in MIL-STD-129 applicable to fragile items, arrows, the words "UP", "THIS SIDE UP" and "CENTER OF BALANCE" shall apply.

3.8 Workmanship. Preservation, packaging, packing, and marking shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.3 Inspection of the end item.

4.3.1 Examination of end item for preparation for delivery of. The end item shall be examined for preservation, packaging, packing, and marking in accordance with the defects set forth in tables I through IV. The sample unit for these examinations shall be one disassembled, packaged or packed item of Bakery Equipment, as applicable, of the specified type, design, size and characteristic. The lot size shall be expressed in terms of the applicable sample unit. The inspection level for each examination shall be S-1 and the acceptable quality level (AQLs), expressed in defects per 100 units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

TABLE I. Visual examination of preparation for packaging

Examine	Defects
Disassembly (as applicable)	Detached parts or hardware not placed with mating parts as specified (see 3.1)
Matchmarking	Removed parts not identified or tagged Warning tags or labels indicating the disassembly not attached or missing Instructions for reassembly missing
Draining (as applicable)	All water or fuel not removed from fuel or water containing parts or systems
Repainting and recoating	Not repainted or recoated as needed (see 3.4)

TABLE II. Examination of preservation and packaging

Examine	Defects
Lubrication (where applicable)	Not lubricated to capacity
Gasoline tanks	Cap not replaced after fogging Breather hole not sealed with tape
Pulleys and drive belts	Pulleys not preserved as specified Drive belts not replaced with tension relaxed
Technical literature	Missing or not secured to parent unit
Sealing of units (as applicable)	Any openings or crevices not sealed with tape as specified (see 3.5.1.9)
Movable parts of equipment	Not secured in a fixed position
Disassembled components, tools and accessories	Not cushioned and securely immobilized within the box as specified (see 3.5.1.13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of packing

Examine	Defects
Container	Not as specified for weight limits of equipment being packed (see 3.6.1.1 through 3.6.2.6 as applicable) Less than 1 inch clearance between item and closest member of sides, ends and top, when required Top, sides, and ends of nailed wood box (PPP-B-621) not lined with barrier as specified (see 3.6.1.2)
Skids or handling means (when required)	Missing Strips not bolted to base of appliance Strips not secured to bottom of container Strips do not protect the unit or container from fork lift damage Markings not as required for boxes with internal handling means
Bakery equipment, units and assemblies	Not securely immobilized by bolting and blocking and bracing as specified Longitudinal sleepers or load bearing members missing when required Any wood member less than size specified Bolting not positioned through the skids as specified Cushioning and padding of finished surfaces not as specified Nailing application of blocking and bracing not as specified
Boxed components	Not secured within shipping container, when applicable

TABLE IV. Examination of the end item for marking

Examine	Defects
Marking interior packages and shipping container (as applicable)	Omitted; incorrect; illegible; or of improper size, location, sequence or method of application Set markings missing, when applicable Precautionary markings missing, or not as specified (see 3.7.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

* 4.3.2 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-636, PPP-B-640, PPP-B-1163, PPP-B-1364, PPP-C-650, MIL-C-104, or MIL-C-3774, examination for defects in closure, strapping, and waterproofing, when applicable, shall be in accordance with the applicable specification.

5. PREPARATION FOR DELIVERY
Not applicable.

6. NOTES

6.1 Intended use. The preservation, packaging, and packing and marking of bakery equipment and related items.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation and packaging and packing (see 3.5 and 3.6).
(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 3.6.2.1).

6.3 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 7310-0424

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973-714-546/5605

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-B-2316D BAKERY EQUIPMENT, INCLUDING UNIT ASSEMBLIES, REPAIR PARTS AND TOOLS, PREPARATION FOR DELIVERY OF

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.