MIL-B-2316D
AMENDMENT-2

10 June 1974
SUPERSEDING
~~Int. Amendment-1~~ (GL)
5 February 1974

MILITARY SPECIFICATION

BAKERY EQUIPMENT, INCLUDING UNIT ASSEMBLIES,

REPAIR PARTS AND TOOLS, PREPARATION FOR

DELIVERY OF

This amendment forms a part of Military Specification MIL-B-2316D, dated 29 May 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "Federal". Add "PPP-S-760 - Strapping, Nonmetallic (and connectors)".

PAGE 8

3.6.2.3, at the end of the paragraph. Add "Alternatively, ovens weighing up to 750 lbs. net weight shall have the components packaged as specified in 3.5, placed within the oven and cushioned and blocked with fiberboard pads and forms. The oven shall be placed back down, doors up, on a sheet of cushioning material placed over a fully sheathed skid base. The base shall be provided with a full length and width retaining frame made from four pieces of wood, two minimum 1-3/4 x 1-3/4 inch and two minimum 3/4 x 1-3/4 inch securely nailed to the top deck of the base. The deck shall be nominal 1 inch lumber and skids nominal 2 x 4 inch lumber. The skids shall be positioned so as to support the box cover on four sides. The oven shall be secured to the base by four bolts or four bolted clips. Bolts, when clips are used, shall be minimum 3/8 inch carriage bolts long enough to go through the skid or 2 x 4 inch sleeper, deck boards and 1-3/4 x 3/4 inch retainer frame and through the clip. Bolts, when used to bolt to the frame of the unit shall pass through the skid or 2 x 4 inch sleeper, deck and the oven frame. Each bolt shall be secured with a lock-washer and a nut. The clip shall engage the frame, 2 each side and a minimum of 11 gage thick and 2 inches wide. The oven doors shall be secured by 2 bands of 5/8 x .020 inch steel strap encircling the oven and wood base. Edge protectors shall be placed between the strap and oven. The oven shall be completely covered by a full height shroud made from minimum 4 inch polyethylene or material conforming to class E-2, E-1, H-5 or M-1 of PPP-B-1055. The box cover shall be an inverted 1/2 slotted HSC triple wall

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.

box conforming to style E, class 2 of PPP-B-640. The box cover shall be placed over the oven and onto the base skids. The box cover shall be secured to the retaining frame with not less than 5 staples each side. The staples shall have a crown length of not less than 1-1/4 inches. The box cover shall then be strapped with two bands of nonmetallic strapping encircling the box cover and base. The strapping shall have a minimum break strength of 790 lbs. and be in accordance with type II or III of PPP-S-760. There shall be a minimum of 1 inch clearance between the interior of the top, sides and ends of the container and the oven."

Custodians:

Army - GL
Navy - YD
Air Force - 84

Preparing activity:

Army - GL

Project No. 7310-0461

Review activities:

Army - MD
Navy - MC

☆ U.S. GOVERNMENT PRINTING OFFICE: 1974--713-155/6735

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:42Z
Check the source to verify that this is the current version before use.