INCH POUND

MIL-DTL-2211F
29 JULY 2008
SUPERSEDING
MIL-T-2211E
21 JUNE 1973

DETAIL SPECIFICATION

TABLE, LAUNDRY, FOLDING, 3 BY 8 FEET

INACTIVE FOR NEW DESIGN AFTER 29 JULY 2008

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type and size of folding laundry table (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in section 3, 4, or 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this standard, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, Standards, and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

FEDERAL SPECIFICATIONS

QQ-S-698	Steel, Sheet and Strip, Low Carbon
TT-C-490	Chemical Conversion Coatings and Pretreatments for Ferrous Surfaces (Base for Organic Coatings)

FEDERAL STANDARDS

FED-STD-595/24084	Green, Semigloss

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-130	Identification Marking of U.S. Military Property

(Copies of these documents are available online at http://assist.daps.dla.mil. or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

Comments, suggestions, or questions on this document should be addressed to Defense Supply Center Philadelphia (DSCP), ATTN: DSCP-NASA, 700 Robbins Avenue, Philadelphia, PA 19111-5096 or e-mail to dscpg&inspecomments@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

2.2.2 Other Government documents. drawings,. and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents are those cited in the solicitation or contract.

US ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

5-13-2498	Table, Laundry, Folding; Assembly
5-13-2499	Table, Laundry, Folding; Details

(Copies of these drawings are available from the US Army Natick Research and Development Center, 15 Kansas St., Natick, MA 01760.)

US DEPARTMENT OF COMMERCE

Product Standard PS 1	Structural Plywood

(Copies of this document are available online at http://ts.nist.qov/docvps or from the Standards Services Division, National Institute of Standards and Technology, 100 Bureau Drive, MS 2150, Gaithersburg, MD 20899-2150.)

2.3 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR TESTING AND MATERIALS STANDARD (ASTM)

ASTM A575	Standard Specification for Steel Bars, Carbon, Merchant Quality, M -Grades
ASTM B209	Standard Specification for Aluminum and Aluminum-Alloy Sheet and Plate
ASTM D4690	Standard Specification for Urea-Formaldehye Resin Adhesives

(Copies o f these documents are available from http://www.astm.org or ASTM International, 100 Barr Harbor Drive, W. Conshohocken, PA 19428-2959.)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ Z1.4	Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available from http://www.asq.org or the American Society for Quality, 611 East Wisconsin Avenue, Milwaukee, WI 53202.)

MASTER PAINTERS INSTITUTE (MPI)

MPI # 28	Varnish, Marine Spar, Exterior, Gloss (MPl Gloss Level 6)

(Copies of this document are available from http://www.mpi.net.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the reference cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.2 Materials. Materials not definitely specified shall be of the quality normally used for the purpose in commercial practical.

3.2.1 Plywood. Plywood used for the tabletop and battens shall be exterior type, grade A-B, sanded two sides, conforming to group 1 of Product Standard PS 1.

3.2.2 Aluminum and steel angles and shapes.

3.2.2.1 Aluminum angles. Aluminum angles shall be fabricated of alloy 3003 conforming to the requirements of ASTM B209.

3.2.2.2 Steel, bar size shapes. Bar size shapes shall conform to ASTM A575 or if formed from steel sheet or strip shall conform to QQ-S-698.

3.2.3 Hardware. Nuts and bolts, wing nuts, wood screws, washers, rivets, and cotter pins shall be standard commercial products, fabricated from steel and except for wood screws shall be zinc plated.

3.2.4 Enamel. Enamel shall be a combination of air-drying and baking enamel that provides a smooth, semigloss, possessing excellent corrosion-inhibiting properties. The color shall be olive drab 24084 conforming to FED-STD-595.

3.2.5 Varnish, spar. Spar varnish shall conform to the requirements of MPI # 28.

3.2.6 Adhesive. Adhesive shall be urea-resin-type conforming to ASTM D4690.

3.3 Construction. The construction of all components and assemblies of the item covered by this specification shall conform to requirements herein and the design, details, dimensions, material classification and sizes specified on Drawing 5-13-2498.

3.3.1 Top. The top shall be plywood specified in 3.2.1 and sanded smooth.

3.3.1.1 Reinforcing and edging. The top shall be reinforced with steel angles specified in 3.2.2.2 and securely held to plywood top with wood screws. All edges of top shall be protected with aluminum angles specified in 3.2.2.1, and securely held to plywood top with wood screws.

3.3.2 Battens. The battens shall be plywood specified in 3.2.1 and with all sides and edges sanded smooth. Battens shall be fastened to plywood top with adhesive specified in 3.2.6 and securely held in place with wood screws.

3.3.3 Hinges. Angles and channels forming hinges shall be firmly bolted through the battens and the top with 3/8-inch carriage bolts, countersunk into the top and the nuts tightly drawn against lock washers.

3.3.4 Legs end braces. The legs, stretchers and braces shall be formed from the steel sheet or strip specified in 3.2.2.2.

3.3.5 Finish.

3.3.5.1 Plywood. All exposed surfaces of plywood parts shall be cleaned of all dust and dirt. Exposed plywood shall be coated with spar varnish as specified in 3.2.5, before assembly and with a sufficient number of coats to produce a uniformly glossy appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

3.3.5.2 Metal. All metal surfaces, except aluminum angles and the heads of carriage bolts, shall be prepared for painting according to type I or II of TT-C-490, and shall be coated with enamel specified in 3.2.4.

3.4 Marking for identification. Marking for identification of the tables shall be on the underside of the top and shall be in accordance with the requirements of MIL-STD-130.

3.5 Workmanship. Tables shall be free from defects such as fractures, splits, punctures, or dents. There shall be no sharp edges, slivers, burrs, or projections.

3.5.1 Application of finish, The finish applied to the end item shall be continuous, smooth, adherent without discoloration or foreign material imbedded and contains no sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, scratches, pores, pits, lumps, flux, or orange peel. No rust, rough grinds or tool marks shall show through the coating.

3.5.2 Welding. All surfaces of parts to be welded shall be clean. Welding shall be accomplished in a manner which will prevent the occurrence of burn holes, cracks, fractures or incomplete fusion. All scale and flux deposits shall be removed from finished welds.

3.5.3 Bolts, nuts, screws, studs, and other threaded fasteners. Threaded fasteners shall not be broken, stripped, fractured, or loose.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Conformance inspection (see 4.3)

4.2 First article inspection. When a first article is required, it shall be examined for defects listed in table II and specified dimensions. The presence of any visual defect, any dimension not within specified requirements, shall be cause for rejection of the first article.

4.3 Conformance inspection. Sampling for conformance inspection shall be performed in accordance with ASQ Z1.4, except where otherwise indicated hereinafter. Unless otherwise specified, the Acceptable Quality Limits (AQLs) listed in this section shall be used to establish the sample sizes, however, the acceptance number shall be zero.

4.3.1 Inspection of materials and components. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification, or applicable purchase document.

4.3.2 In-process inspection. Examination shall be made during the manufacturing for the requirements specified in table I to establish that no deviation is made from the indicated requirements. When nonconformance is noted, correction shall be made to affected items in process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

TABLE I. In-process inspection.

Requirements	Requirement paragraph
Application of varnish prior to assembly.	3.3.5.1
Cleaning and application of enamel on metal surfaces.	3.3.5.2

4.3.3 End item inspection. A lot shall consist of all tables offered for inspection at one time. The sample unit shall be one completely fabricated folding laundry table.

4.3.3.1 Visual examination. The completely assembled end item shall be examined for defects as specified in table II. The Inspection level shall be level II and the acceptable quality limits (AQLs) shall be 4.0 for major defects and 10 total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects.

Examine	Defect	Classification	
		Major	Minor
Finish	Plywood not varnish	X	
	Steel components not enameled	X	
	Enameled not matched to color 24084, FED-STD-595		X
	Not continuous or adherent		X
	Discoloration, or imbedded foreign matter		X
	Sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, lumps, or orange peel		X
	Rust, grind or tool marks that show through finish	X	
Construction and workmanship (applicable to all components and assemblies)	Fractures, splits, punctures, or dents	X	
	Sharp edges, silver, burr or projections	X	
	Fastening assembly bolt not peened or secured with hex nut and washer	X	
	Battens not recessed	X	
Table top	Battens not glued and screwed to table top	X	
	Carriage bolt heads not countersunk	X	
	Top of edging and table not flush	X	
	Fastening assembly missing	X	
Legs	Stretcher missing	X	
	Do not fold properly	X	
	Brace not cut to fit stretcher	X	
	Omitted	X	
Welding	Burn holes, cracks, fractures, or incomplete fusion	X	
	Scale or flux deposits not removed		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects. (cont'd)

Examine	Defect	Classification Major	Minor
Threaded fasteners	Broken, stripped, missing, fractured or loose	X	
Identification marking	Missing, illegible, or incomplete, not on underside of table	X	

4.3.3.2 Dimensional examination. Inspection shall be made of the end item for compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 total defects, expressed in terms of defects per hundred units.

5. PACKAGING.

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from then managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The folding table covered by this specification is intended for use as a component of a field laundry.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required (see 3.1, 4.2, and 6.3).
(c) Packaging requirements (see 5.1).

6.3 First article. When a first article is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first production items, a standard production item from the contractor's current inventory (see 3.1) and the number of items to be tested. The contracting officer should also include specific instructions in acquisitions documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing

Assembly
Battens
Braces
Hinges

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes

Custodians:
Army - GL
Navy - YD
Air Force - 99

Preparing activity:
DLA - IS

(Project 3510-2008-004)

Review activities:
Army - CR4
Navy - MC
Air Force - 84

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:33Z
Check the source to verify that this is the current version before use.