MIL-F-2296E
9 June 1977
SUPERSEDING
MIL-F-2296D
9 November 1970

MILITARY SPECIFICATION

FILTERS, COOKING GREASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers filters for filtering cooking medium of deep fat fryers and doughnut machines (see 6.1).

1.2 Classification.

1.2.1 Filters. Filters shall be of the following types and sizes as specified (see 6.2):

Type I - Gravity drain

Size 1 - 30-pound (13.6 kg) minimum reservoir fat capacity

Type II - Pumped drain

Size 1 - 50-pound (22.7 kg) minimum reservoir fat capacity
Size 2 - 150-pound (68 kg) minimum reservoir fat capacity
Size 3 - 200-pound (91 kg) minimum reservoir fat capacity

1.2.2 Filter paper. Filter paper required for separate procurement (see 6.2) shall conform to the requirements of 3.5.1.4 or 3.5.2.7, as applicable.

1.2.3 Filtering compound. Filtering compound required for separate procurement (see 6.2) shall conform to the requirements of 3.5.2.8.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CC-M-1807	-	Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller)
PPP-B-26	-	Bag, Plastic (General Purpose)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-640	-	Box, Fiberboard, Corrugated, Triple-Wall
PPP-T-60	-	Tape, Packaging, Waterproof

MILITARY

MIL-P-116	-	Preservation-Packaging, Methods of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1186	-	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; With Appropriate Test Methods

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

UNDERWRITERS LABORATORIES INC.

UL 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, L.I., NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050; 333 Pfingsten Road, Northbrook, IL 60062 or 2602 Tampa East Boulevard, Tampa, FL 33619.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

A 580 - Stainless and Heat-Resisting Steel Wire

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, MI 48106.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard product. The grease filter shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair and parts services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards compliance. Grease filters shall conform to applicable requirements of NSF No. 4 and the entire type II grease filter or the individual electrical components shall conform to the requirements of Underwriters Laboratories Inc., standards as applicable.

3.2.1 NSF compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the grease filter he proposes to furnish under this specification meets the applicable requirements of NSF No. 4. Satisfactory evidence shall be any of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished grease filter, or

(2) A certification for the grease filter issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the grease filters are being procured, indicating that the grease filters have been tested and conform to NSF No. 4.

3.2.2 UL certification. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative, that the entire type II grease filter or the individual electrical components he proposes to supply under this specification meet the requirements of UL Standard 197, as applicable. Acceptable evidence of meeting the requirements of UL standards shall be the UL label, a UL listing mark for the filter or the components, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the entire type II grease filter or the individual electrical components offered have been tested and conform to the requirements of applicable UL standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for his commercial cooking grease filters provided the completed items comply with all provisions of this specification.

3.3.1 Stainless steel.

3.3.1.1 Sheet and strip. Stainless steel sheet and strip shall conform to the chemical composition of type 302 or 304 of ASTM A 167.

3.3.1.2 Wire. Stainless steel wire shall conform to the chemical composition for type 302 or 304, condition A (annealed) of ASTM A 580.

3.4 Design.

3.4.1 Type I. The type I filter shall be designed to filter cooking medium of deep fat fryers and 35 dozen per hour doughnut machines, and shall consist of a fat reservoir, grid, filter paper, and supporting rack. The filter shall allow filtering of liquefied frying medium by placing the adapter rack with reservoir across the top of the fryer well and hand-pouring the fat into the reservoir and gravity draining filtered fat into the fryer. The filter assembly shall satisfactorily filter hot fat when tested as specified in 4.3.3.

3.4.2 Type II. The type II filter shall be designed to filter and return the cooking medium of deep-fat fryers and doughnut machines by means of motor-driven pump. The filter shall consist of an electric motor(s), pump(s), and reservoir, hoses, filter, and controls and fittings necessary for safe operation. The design shall allow filtering of melted, solidifying or nonsolidifying frying medium. A means for fast, complete drainage of pumps, valves, lines, and fittings shall be provided. When necessary for liquefying solidified fat in pumps, valves, and other transfer equipment, a heating element shall be provided. The assembly shall be capable of filtering frying medium at a minimum rate of 3-1/2 gallons (13 liters) per minute when tested as specified in 4.3.4. The assembly shall be mounted on casters. The filter fat reservoir shall have a height not exceeding 13-1/2 inches, (343 mm) not including handle, so that filter will roll under fryer drain valve on drain valve extension.

3.5 Construction.

3.5.1 Type I construction.

3.5.1.1 Fat reservoir. The fat reservoir shall be fabricated of minimum 0.0335 inch (0.85 mm) stainless steel specified in 3.3.1.1 or minimum 0.069 inch (1.75 mm) thick aluminum. When tested as specified in 4.3.5, the reservoir shall have a minimum capacity of 30 pounds (13.6 kg) and shall not leak. The top of the reservoir shall have a rolled, half-round, open edge.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T14:39Z
Check the source to verify that this is the currentversion before use.

The bottom shall be provided with an offset shoulder to support the grid and to fit the adapter rack supports. Two handles of the same material as the reservoir body shall be provided and shall be welded or riveted 180 degrees apart on the outside of the body.

3.5.1.2 Rack. The rack shall be fabricated of stainless steel specified in 3.3.1.1 and shall have an overall length and width of 24-1/2 inches (622 mm) by 11-1/2 inches (292 mm) respectively, plus or minus 1/2 inch (12.7 mm). The frame shall be rectangular in shape and shall be fabricated of angles or flat or round-bar stock. Means shall be provided in the center of the rectangular frame to support the fat reservoir. The rack shall be capable of supporting a load of 60 pounds (27 kg) without permanent distortion when tested as specified in 4.3.1.

3.5.1.3 Grid. A stainless steel grid for supporting the filter paper shall be provided. The grid shall be constructed of stainless steel wire as specified in 3.3.1.2 and shall consist of an outer ring with crosswires welded thereto. The grid shall fit into the reservoir and shall rest on the offset shoulder of the reservoir.

3.5.1.4 Filters. One-hundred cotton-wadding filter papers shall be supplied with each type I grease filter. The filters shall be sized and shaped to fit into the fat reservoir and on the grid. Filters shall be capable of retaining particles 10 microns (0.01 mm) and larger.

3.5.2 Type II construction.

3.5.2.1 Electrical characteristic. Unless otherwise specified (see 6.2), the grease filter shall be wired for use on a nominal 120-volt, 1-phase, 60-Hertz system.

3.5.2.2 Motor. The transfer motor(s) shall be not less than 1/4 horsepower (186 Watts) and shall drive the pumps at a speed to maintain the required pump capacity. The motors shall conform to the requirements of CC-M-1807 and shall be mounted in a fully enclosed housing away from grease spillage. An overload protective device shall be provided for the motor(s) (see 4.3.2).

3.5.2.3 Wiring and controls. A minimum 6-foot (1.8 m) long type SO, ST, SJO, or SJT power supply cord shall be provided. The grease filter shall be grounded by use of a grounding type attachment plug. A bracket for storing the cord when not in use shall be provided on the filter. Controls for motor(s) and pump(s) operation shall be provided and shall be rigidly mounted in a location easily accessible to the attendant. An indicating light shall be provided to show when the preheater is energized. Electrical controls and other electrical components shall operate without malfunction, binding, or looseness when tested as specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

3.5.2.4 Pumps. Transfer pump(s) shall be driven direct from the motor, or by pulley and "V" belt. Pumps shall be capable of transfering cooking medium at the minimum rate specified in 3.4.2.

3.5.2.5 Reservoir. A reservoir for containing cooking medium during the filtering operation shall be provided. The reservoir shall be fabricated of minimum 0.025-inch (0.64 mm) thick stainless steel specified in 3.3.1.1. The reservoir shall have a minimum fat capacity of 50 pounds (22.7 kg) for size 1, 150 pounds (68 kg) for size 2 and 200 pounds (91 kg) for size 3. When tested as specified in 4.3.5 the reservoirs shall not leak and shall have the minimum capacity specified herein.

3.5.2.6 Transfer components. Transfer hose(s) shall be fabricated of a material acceptable for food handling service and capable of withstanding the temperatures at which the manufacturers' instruction indicate the filter should be operated. Hoses shall be provided with necessary fittings for drainage and refilling, and shall be removable for replacement. The hose(s) shall be sized for performing discharge and suction operations and the length of the hose used for discharging shall be not less than 6 feet (1.8 m). Hose(s) used for discharge and suction shall be provided with an insulated type handle. When tested as specified in 4.3.5 there shall be no leakage at joints, fittings, or hoses.

3.5.2.7 Filters. The filter design and material shall be the manufacturer's standard product. Removal and replacement shall be easily accessible. The filter shall be located so the cooking medium is filtered prior to entering the pump. Each assembly shall be provided with the type and quantity of filters necessary for 100 filtering operations. Filters shall be capable of retaining particles 10 microns (0.01 mm) and larger.

3.5.2.8 Filtering compound. When a filtering compound is necessary to perform complete filtering operations, the contractor shall furnish a 50-pound (22.7 kg) bag of compound for restoring color and for removing odor and taste of frying medium.

3.5.2.9 Casters. The grease filter assembly shall be mounted on not less than three casters. Casters shall be sleeve or roller or ball-bearing swivel type with phenolic or neoprene composition tires and minimum 1-1/2 inch (38 mm) diameter wheels. Bearings shall be permanently lubricated or provided with a means for lubrication of both wheel and swivel bearings. When tested as specified in 4.3.6, the casters shall be capable of supporting the weight of the filter plus a reservoir load of 65 pounds (29 kg) for size 1, 165 pounds (75 kg) for size 2, and 215 pounds (98 kg) for size 3 without deformation or marking of the floor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

3.6 Marking.

3.6.1 Identification. Filters shall be permanently marked on an identification plate and shall include the manufacturer's name, trade name, or trademark, serial number, and model number. Electrical characteristics and pump capacity shall be included for type II filters.

3.6.2 User's instructions. Each type II filter assembly shall be equipped with a user's instruction plate, permanently fastened to any exterior surface in a readily visible area. The plate shall be fabricated of corrosion-resistant metal and shall contain the manufacturer's standard operating instructions etched, embossed, or die stamped thereon.

3.7 Welding. When welding is employed, all surfaces to be welded shall be free from oxide, scale and grease. Welds shall be sound, and ground smooth and shall be free from incomplete fusion, porosity, cracks, undercuts, burn-through and deformation of material. All flux deposits (when flux is used) shall be removed from welds.

3.8 Finish. The filter shall be smooth on all surfaces and edges; free from discoloration and stains and shall be finished in accordance with the manufacturer's standard practice.

3.9 Workmanship. The filter shall not contain any rough or sharp edges, burrs, or slivers and shall be clean and free from rough grind, die and trimming marks, rust, and scale. Holes for bolts and rivets shall be accurately punched or drilled and any obstruction that will prevent proper seating of the rivets shall be removed. Rivets when required, shall be fully peened with heads in full contact with riveted members and the driven rivets shall completely fill the hole. Threaded fasteners, where required, shall not be stripped, fractured, or loose. All components shall be assembled in a neat, workman-like manner and in proper alignment.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The lot shall consist of all grease filters of one type and size offered for inspection at one time. The sample unit shall be a completely fabricated grease filter.

4.2.2.1 Visual examination. Examination shall be made of the grease filters for the defects classified in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Finish discolored or stained	X	
Design, construction and workmanship (general)	Any component missing	X	
	Any component that is inoperative or will not operate as intended	X	
	Any part misplaced, not in proper alignment, or not joined properly	X	
	Any part loose	X	
	Any kinks or twist on metals	X	
	Any burr, sliver, sharp edge, or any rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, dented, punctured, or malformed	X	
Threaded fasteners	Threaded fasteners loose	X	
	Missing, stripped, or fractured	X	
Welding (when applicable)	Not free from oxide scale	X	
	Excessive flux not removed	X	
	Not sound, smooth, or free from pits, flash, porosity, cracks incomplete fusion, undercut, or deformation of material	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Riveting (when applicable)	Rivets not secure (not set or loose)	X	
Filters	Not easily removable	X	
	Not proper number		X
Detailed construction	Top edge of fat reservoir not rolled as specified	X	
Type I	Handles not located as specified	X	
	Rack not fabricated as specified	X	
	Rack supports do not rigidly support reservoir	X	
	Grid not fabricated as specified	X	
	Grid will not fit in body of reservoir or is too loose (does not fit on offset shoulder of reservoir)	X	
Type II Electrical characteristics	Overload protection missing	X	
	Heating element missing (when required)	X	
	Not grounded as specified	X	
	Indicator light missing or not as specified	X	
	Cord not provided with type cap specified	X	
Transfer equipment	Motor and pump not protected from spillage of fats	X	
	Hose fittings and attachments missing or not as specified	X	
	Bracket for hanging transfer hoses missing	X	
	Handle or grip missing	X	
	Handle or grip not insulated type	X	
	"V" belt missing (when required)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Casters	Not type or number specified	X	
	Caster missing	X	
Filtering compound (when applicable)	Missing	X	
	Instructions missing	X	
Instructions	Missing, incomplete, incorrect or not legible	X	
Manuals (when applicable) (see 6.3)	Missing, incomplete, incorrect or not legibly printed	X	
Marking	Missing or not as specified		X

4.2.2.2 Dimensional examination. Examination shall be made of the filter assembly for compliance with dimensions specified. Any nonconformance shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects expressed in terms of defects per hundred units.

4.2.2.3 End item testing. One sample unit shall be selected at random from each lot and tested in accordance with 4.3.1 through 4.3.6, as applicable. Failure of any test shall be cause for rejection of the inspection lot.

4.2.3 Examination of packaging. An examination shall be made to determine whether the preservation-packaging, packing, and marking complies with the section 5 requirements. Defects shall be as listed in table II. The lot size shall be the number of shipping containers in the end item inspection lot. The sample unit shall be one shipping container fully packaged, except that it need not be closed. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of packaging

Examine	Defect
Marking (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or not as specified.
Contents (filters)	Number per container is more or less than required.
Preservation	Preservative improperly applied or missing.
Workmanship	Inadequate application of components, such as: incomplete closure of interior fiberboard box flaps, improper taping of bags. Hoses and cord not coiled and secured with tape. Incomplete wrap, package wrap not secured. Components not arranged in sequence specified. Incorrectly fabricated plastic bag. Open and non-continuous heat sealed seams of polyethylene bags. Bulged or distorted interior fiberboard box.

4.2.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, PPP-B-621, PPP-B-636 or PPP-B-640, examination for defects in closure and strapping shall be in accordance with the appendix of the applicable container specification. Examination for defects in cushioning, blocking and bracing, and waterproofing shall be in accordance with MIL-STD-1186.

4.2.4 Standard compliance. Proof of compliance with NSF No. 4 and the UL requirements of 3.2, shall be submitted to the Government representative.

4.3 Test methods.

4.3.1 Load test (type I). The rack shall be placed on two 1-inch (25.4 mm) wide supports located one inch (25 mm) in from each end of the rack frame. The supports extend across the 11-1/2 inch (292 mm) dimension of the frame. The fat reservoir shall be placed in position on the rack and weights totaling 60 pounds (27 kg) shall be placed in the reservoir and allowed to remain for 30 minutes. After 30 minutes has elapsed, the weights shall be removed and the rack and reservoir examined to determine conformance with the deformation requirements of 3.5.1.2. Inability of the rack to meet specified requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

4.3.2 Electrical controls (type II). The unit shall be connected to an electrical supply having characteristics similar to those specified in the contract or order. The unit shall be operated without load for a period of 10 minutes. During this time, controls and switches shall be operated through a minimum of three cycles at all positions to determine conformance with the requirements of 3.5.2.3. The motor shall be loaded to determine the overload device operates satisfactorily (see 3.5.2.2). Any nonconformance shall constitute failure of this test.

4.3.3 Performance (type I). The type I filter shall be placed over an open container or fryer well and 30 pounds (14 kg) of hot fat shall be poured into the fat reservoir. The filter assembly shall be checked to determine conformance with the filtering requirement in 3.4.1. Inability to meet specified requirements shall constitute failure of this test.

4.3.4 Performance (type II). A sufficient amount of 400°F (204°C) frying medium shall be placed into a container adjacent to the filtering unit, or the filter shall be located adjacent to a doughnut machine containing a sufficient amount of 400°F (204°C) fat. The suction hose shall be placed into the frying medium. The unit shall be started and the time noted. The unit shall be operated a sufficient amount of time, minimum 15 minutes, necessary to determine conformance with the filtering rate requirements of 3.4.2. Any nonconformance with specified requirements shall constitute failure of this test.

4.3.5 Reservoir capacity and leakage. The reservoir capacity of type I and II filters shall be checked to determine conformance with the requirements of 3.5.1.1 and 3.5.2.5 respectively, and the entire unit shall be checked to determine conformance with leakage requirements of 3.5.2.5 and 3.5.2.6. Inability to meet capacity and leakage requirements shall constitute failure of this test.

4.3.6 Casters. Weights in accordance with 3.5.2.9 shall be uniformly distributed in the reservoir and the assembly shall be rolled on a clean, smooth, concrete surface for two minutes to determine conformance with the nonmarking requirements of 3.5.2.9. At the end of this period, the unit with the load applied shall be allowed to stand for a minimum period of 8 hours to determine conformance with the nondeformation requirements of 3.5.2.9. Inability of the casters to meet specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Preservation. Casters for the type II grease filters shall be preserved by lubricating to capacity with the manufacturer's recommended lubricant containing a rust-inhibitor when applicable.

5.1.1.2 Unit packaging.

5.1.1.2.1 Filters. One hundred cloth or paper filter disks, or bag type filters; or twelve paper fabricated filters in excess of 1/2-inch (12.7 mm) in thickness, shall be packaged in a close-fitting cellophane bag in accordance with type II, style A or B, class 1 or 2 of PPP-B-26.

5.1.1.2.2 Type I, size 1 grease filter complete with components. Each complete type I, size 1 grease filter with components, shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. The box shall be designed to fit the contents in a compact manner. Arrangement of components shall be as follows: The adapter rack shall be placed right side up in the bottom of the box on built-up fiberboard pads designed to allow 1/4-inch (6 mm) clearance for the fat reservoir. The built-up fiberboard pads shall be made of the same material as the box. The fat reservoir shall be placed into position on the adapter rack. The grid shall be completely wrapped in kraft paper or placed in a cellophane bag made of the same material as specified in 5.1.1.2.1. The kraft paper wrap shall be secured with pressure-sensitive tape. The bag of filter disks unit-packaged as specified in 5.1.1.2.1, and grid unit, packaged as specified herein, shall be placed within the fat reservoir. Shredded wax paper shall be used on the inside of the fat reservoir to keep the component parts from moving while in transit. Each box shall be closed with 2-inch minimum width gummed or pressure-sensitive paper tape.

5.1.1.2.3 Type II, sizes 1, 2 or 3 grease filter and transfer equipment. The suction and discharge hose, when practical, shall be neatly coiled around the outside diameter of the reservoir and secured with tape. The power supply cord shall be tightly coiled and secured to the body of the grease filter with tape. The tape as specified herein, shall conform to type III or IV of PPP-T-60.

5.1.1.2.4 Type II, sizes 1, 2 or 3 filtering compound. When required (see 3.5.2.8), 50 pounds (22.6 kg) of filtering compound shall be packaged in a close-fitting cellophane bag. The bag shall be as specified in 5.1.1.2.1. The bagged filtering compound shall then be packaged in a snug-fitting fiberboard box conforming to style RSC-L, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. The inside of each box shall be fitted with a taped liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each box shall be closed with 2-inch minimum width gummed or pressure-sensitive tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

5.1.1.2.5 Instruction manual. Each instruction manual shall be packaged in accordance with method IC-1 of MIL-P-116.

5.1.2 Level C. Each complete grease filter shall be preserved and unit packaged to afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Type I grease filter complete with components. Four type I, size 1 grease filters complete with components preserved and packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard container shall be closed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.1.2 Type II, grease filters complete. Each type II, size 1, 2 or 3, complete grease filter, preserved and packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type of PPP-B-601, or class 2, style 2 or 4 of PPP-B-621. The packaged filtering compound, the bag or tube containing filters and the prepared instruction manual, shall be placed in an unused portion of the shipping container or within the grease filter reservoir. Contents of each shipping container shall be cushioned, blocked and braced, and waterproofed in accordance with MIL-STD-1186. A minimum clearance of three-fourths of an inch shall be maintained between the bottom of the casters of the grease filter and the interior surface of the base of the container. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.2 Level B packing.

5.2.2.1 Type I grease filter complete with components. Four type I, size 1 grease filters complete with components, preserved and packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.

5.2.2.2 Type II, grease filters complete. Each type II, size 1, 2 or 3 complete grease filters, preserved and packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to domestic type, style A or B of PPP-B-601; or class 1, style 2 or 4 of PPP-B-621, or class 1, style E of PPP-B-640. The packaged filtering compound, the bag containing filters and the prepared instruction manual, shall be placed in an unused portion of the shipping container or within the grease filter reservoir. Contents of each shipping container shall be cushioned, blocked and braced in accordance with MIL-STD-1186. A minimum clearance of three-fourths of an inch shall be maintained between the bottom of the casters of the grease filter and the interior surface of the base of the container.

5.2.3 Level C packing. Each complete grease filter, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The grease filters covered herein are intended for use in kitchens and galleys to reclaim cooking medium in deep fat fryers and doughnut machines. The type I filter is intended for use with deep fat fryers and the 35-dozen per hour doughnut machine. The type II, size 1 filter is intended for use with small size deep fat fryers, the size 2 filter is intended for use with the 100-dozen per hour doughnut machine and the type II, size 3 filter is intended for use with the 200-dozen, 400-dozen, and 600-dozen doughnut machines covered by 00-D-582.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and size of filter required (see 1.2.1).
(c) Quantity of filter papers required for separate procurement (see 1.2.2).
(d) Amount of filtering compound required for separate procurement (see 1.2.3).

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

(e) Electrical characteristics, if other than specified, (see 3.5.2.1).
(f) Selection of applicable levels of preservation-packaging, and packing (see 5.1 and 5.2).
(g) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1.1).

6.3 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Preparing activity:

Army - GL

Project No. 7330-0502

Review activities:

Army - MD
Navy - MS

☆ U. S. GOVERNMENT PRINTING OFFICE: 1977 -703,020/3725

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:39Z
Check the source to verify that this is the current version before use.