MIL-G-2338L

24 October 1985
SUPERSEDING
MIL-G-2338K
11 December 1979

# MILITARY SPECIFICATION

## GRIDDLES, SELF-HEATING, ELECTRIC; AND STANDS, GRIDDLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This document covers commercial electric griddles for counter top, stand mounting, or dresser mounting and griddle-stands.

* 1.2 Classification. Griddles shall be of the following types, sizes, classes and styles as specified (see 6.2):

Type I - For counter top use
Type II - Stand mounted
  Style 1 - Stand with plain legs
  Style 2 - Stand with castered legs
  Style 3 - Stand with bolt-down legs
Type III - For flush installation into dresser top

Size 1 - Nominal 18 inches (in.) deep by 36 in. wide
Size 2 - Nominal 24 in. deep by 36 in. wide
Size 3 - Nominal 24 in. deep by 72 in. wide
Size 4 - Nominal 18 in. deep by 24 in. wide
Size 5 - Nominal 24 in. deep by 24 in. wide
Size 6 - Nominal 24 in. deep by 48 in. wide

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

Class 1 - 208 Volts, 60 Hz, 1 phase
Class 2 - 208 Volts, 60 Hz, 3 phase
Class 3 - 220 Volts, 60 Hz, 3 phase
Class 4 - 220 Volts, 50 Hz, 1 phase
Class 5 - 220 Volts, 50 Hz, 3 phase
Class 6 - 380 Volts, 50 Hz, 3 phase
Class 7 - 440 Volts, 60 Hz, 3 phase (shipboard use)

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

FF-C-77 - Casters, Rigid and Swivel (Institutional Duty)

MILITARY

MIL-R-11337 - Ranges, Packaging and Packing Of

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

UNDERWRITERS LABORATORIES INC

Standard No. 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)



Source: https://assist.dla.mil -- Downloaded: 202610-16T14:47Z
Check the source to verify that this is the current version before use.

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip
E 165 - Liquid Penetrant Inspection Method

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Standard product. The griddles shall, as a minimum, be in accordance with the requirements of this document and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this document. Modification to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this document shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Standard compliance. Unless otherwise specified herein, the griddles shall conform to the applicable requirements of UL Standard No. 197 and NSF Standard No. 4. Stands shall conform to the applicable requirements of NSF Standard No. 2. Satisfactory evidence that these requirements have been met



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.3).

3.3 Materials (see 6.3) and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial electric griddles and griddle stands, provided the completed items comply with all provisions of this document.

3.3.1 Stainless steel. Stainless steel shall conform to any of the type 300 or 400 series steels specified in ASTM A 167 or A 176, respectively.

3.4 Griddle design. Type I griddles shall be designed for counter top use. Type II griddles shall be designed for stand mounting. Type III griddles shall be designed for flush installation into dresser top. Griddles shall be of the compact design with provisions for knock-out in the back or bottom for conduit or power-cord connection. Type I and type II shall be capable of being banked side by side. Griddle dimensions shall be as shown in table I.

TABLE I. Dimensions, inches

| | Types I, II and III | | | | | |
|---|---|---|---|---|---|---|
| | Size 1 | Size 2 | Size 3 | Size 4 | Size 5 | Size 6 |
| Griddle | | | | | | |
| Overall height 1/ (maximum) (to cooking surface) | 14 | 14 | 14 | 14 | 14 | 14 |
| Overall width | 36 to 38 | 36 to 38 | 69 to 72 | 24 to 26 | 24 to 26 | 48 to 50 |
| Overall depth (front to rear) | 20 to 26 | 26 to 32-1/2 | 26 to 32-1/2 | 20 to 26 | 24 to 30 | 26 to 32-1/2 |
| Effective cooking surface, square inches, min. | 544 | 805 | 1595 | 352 | 420 | 980 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions, inches (cont'd)

| | Types I, II and III | | | | | |
|---|---|---|---|---|---|---|
| | Size 1 | Size 2 | Size 3 | Size 4 | Size 5 | Size 6 |
| Griddle with stand | | | | | | |
| Floor to cooking surface | 34 to 36 | 34 to 36 | 34 to 36 | 34 to 36 | N/A | N/A |

1/ Griddle overall height includes legs 4-inches in length except for type III griddles.

3.4.1 Electrical characteristics. The input to each griddle shall be at least 18 watts per square inch of effective cooking area. All griddles shall be grounded. Griddles shall be designed for operation on nominal voltage ratings, hertz and phases as specified by class in 1.2.

3.4.2 Temperature time limit. The cooking surface of all griddles shall heat to a temperature of at least 350°F in not more than 12 minutes when tested as specified in 4.4.1.

3.4.3 Shipboard performance. Griddles procured for shipboard installation (see 6.2), shall be designed so that there will be no spillage of grease or product when the griddle is inclined 15-degrees each side of the vertical in each of two vertical planes at right angles to each other, when tested as specified in 4.4.6.

3.5 Griddle construction.

3.5.1 Body. The griddle plate shall be supported by an inclosed cabinet-type body of stainless steel as specified in 3.3.1. The griddle bottom shall be of sheet steel treated to resist corrosion. Griddles shall support a uniformly distributed load of 75 pounds per square foot on the cooking surface with no evidence of breakage or permanent distortion when tested as specified in 4.4.3. All type III griddles shall be equipped with mounting flange, top support frame with securing clamps, and sealing gasket. Means shall be provided to prevent grease penetration to the underside.

3.5.2 Griddle surface. The griddle surface shall be one piece of cast iron, carbon steel or stainless steel, with a minimum thickness of 7/16 inch. The surface shall not be porous, pitted, cracked, or distorted. Size 1, 2, 4, and 5 griddles shall have at least one grease trough extending the full griddle width or the full griddle length. Size 3 and size 6 griddles shall have one grease



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

trough extending the full griddle width. Drain holes shall be at least 3 inches by 1 inch for sizes 1, 2, 4, and 5 griddles. Sizes 3 and 6 griddles shall each have either a single 4 inches by 1 inch drain hole, or two 3 inches by 1 inch drain holes.

3.5.3 Grease receptacle. The grease receptacle shall be fabricated from minimum 24-gauge stainless steel, carbon steel, or a combination of both. Sizes 1, 2, 4, and 5 griddles shall have at least one grease receptacle with a capacity of 4 quarts minimum, and sizes 3 and 6 griddles shall have either one or two grease receptacles, each with a capacity of 4 quarts minimum, when tested as specified in 4.4.2. Sizes 1, 2, 4 and 5 griddles shall have at least two vertical baffles and sizes 3 and 6 griddles shall have at least four vertical baffles. Grease receptacles designed to retain grease without baffles are acceptable for the type III, size 3 griddle. Grease receptacles shall be rigidly supported, provided with a handle and vertical baffles, and shall be readily removable from the front of the griddle. For Naval shipboard installations, grease receptacles shall be provided with a positive latch to prevent spillage.

3.5.4 Splash guard. The griddle shall have a splash guard around the back and two sides. The splash guard shall be fabricated of minimum 18-gauge stainless steel and shall be at least 3-inches high at the rear and sides with the front corners tapered or rounded. The splash guard sides and back shall be welded with a continuous weld to form a grease tight seal around the edges of the griddle and splash guard when tested as specified in 4.4.7. A splash guard is not required on type III (dresser top) griddles.

* 3.5.5 Controls. The temperature of each griddle section shall be controlled by a snap-action adjustable thermostat and separate switch or by a thermostat with an "OFF" position. Each thermostat shall have a signal light that glows when the heating element is drawing current and goes out when the set temperature is reached (see 4.4.5). Thermostat dials shall have graduations at intervals not greater than 25°F with a minimum operating range of 200° to 450°F. All switches and thermostats shall be conveniently located on the front panel, and be either recessed or provided with a protector bar around the knobs to prevent damage to stems and knobs. When tested as specified in 4.4.5, the surface temperature on each section shall not vary more than 25°F from the thermostat setting except that for those areas adjacent to the splash guards, the surface temperature shall not vary more than 30°F from the thermostat setting. No point on the surface of the heating section shall vary more than 30°F from any other point.

3.5.6 Heating elements. The griddle shall have heating elements arranged so that different areas of the griddle may be controlled independently. A minimum of one heating element shall be furnished for each linear foot of the griddle plate. The elements shall be the tubular enclosed coil type and shall be securely clamped to the bottom of the griddle plate. Each heating section shall be controlled by a thermostat. The bottom of the heating elements shall be



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

enclosed by a heat insulating pad or by a system of heat-reflecting baffles constructed of minimum 24-gauge stainless steel or polished cold-rolled sheet steel treated to resist corrosion. Both methods shall be designed to isolate the heating elements by reducing the amount of heat radiated downwards. When an insulating pad is used, it shall be of rock wool or glass fibers and shall be at least 3/4 inch thick and suitable for the temperatures generated in this area. The insulating pad shall be enclosed in a minimum 24-gauge steel housing. The housing may be stainless steel or steel treated to resist corrosion. Heating elements shall be readily accessible for repair or replacement. The terminals of the heating elements shall project a sufficient distance to permit easy access to the connections. All internal wiring shall be free of stress or tension and shall be coated with high-heat resistant insulation to resist water or grease.

3.6 Griddle stand-design and construction. Griddle stands for type II griddles shall be of open type design, so constructed that they can be banked together in battery alignment without space between the tops. The stand shall be fabricated from stainless steel specified in 3.3.1. Means shall be included to secure the griddle to the stand to allow removal of the griddle. Stands shall be as specified in 1.2, with plain legs, castered legs or bolt-down legs. Style 2 griddle stands shall be provided with four casters, two casters shall be rigid type and two casters shall be swivel type or four swivel casters. Two of the swivel type casters shall be provided with brakes. Casters shall conform to type I (rigid) and type II (swivel), class B minimum, wheel diameter 3-inches, style b, mounting optional of FF-C-77. When dragged by a lower leg across a concrete floor, the stand shall support a griddle without dislodgement, breakage, or permanent damage to any part when tested as specified in 4.4.4. Each stand shall support a griddle, with a uniformly distributed load of 200 pounds on the heating surface, without damage to any part of the stand, when tested as specified in 4.4.4.

3.7 Marking. Identification markings shall be permanently marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Markings shall be stamped, embossed, engraved, or photosensitive. The plate thickness shall be not less than 0.012 inch.

3.7.1 Identification plate. Each griddle identification plate shall be marked with the manufacturer's model and serial number, name, trade name, or trademark of such known character as to be readily identifiable with said manufacturer.

3.8 Finish. All stainless steel surfaces exposed to view, except griddle tops, shall have a No. 3 finish or better. All other surfaces shall have the manufacturer's standard finish. Griddles and stands shall be free from discoloration or stains and smooth on all surfaces and edges.

3.9 Workmanship. All components and assemblies of the griddle and stand, as applicable, shall be free from dirt and other harmful extraneous material,



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

burrs, slivers, rough die, tool and grind marks, dents, and cracks. Castings, molded parts, and stampings, if used, shall be free of sand, fins, pits, blow holes, and sprues. External surfaces shall be free from sharp edges and corners except when corners are required.

3.9.1 Metal fabrication. Metal used in fabrication of the griddle and stand, as applicable, shall provide for original quality surface finish and shall be free from kinks and unspecified bends. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and true and all bends of major nature shall be made with dies or fixtures to insure uniformity of size and shape.

3.9.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be smooth and free from cracks, burn holes, undercuts, or incompleted fusion. All scale and flux shall be removed from the finish weld area.

3.9.3 Fastening devices. Threaded fasteners and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked, or stripped and shall be torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

3.9.4 Wiring. Wiring shall be enclosed, supported, and adequately protected from food spillage and against mechanical damage. Metal edges with which wire may come in contact shall be smooth and free of sharp edges.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 In-process testing. Prior to assembly, each griddle plate with welded splash guard shall be tested as specified in 4.4.7. Evidence of any weld crack shall constitute failure of the unit.

* 4.2.3 End item visual examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of end items. The sample unit shall be one completely fabricated end item. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE II. End item visual defects.

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Finish | Not finished where required | X | |
| | Type of finish not as specified | X | |
| | Evidence of discoloration or stains | X | |
| | Surface and edges not smooth | X | |
| Construction, design, and workmanship | Part missing | X | |
| | Any component fractured, buckled, punctured, dented, or malformed | X | |
| | Any component misplaced, loose, or not in proper alignment | X | |
| | Component non-accessible for servicing, adjustment, or replacement when required | X | |
| | Griddle body not enclosed cabinet-type | X | |
| | Griddle bottom not of sheet steel treated to resist corrosion | X | |
| Electrical | Griddles not furnished with provisions for permanent electrical connection | X | |
| | Griddle not grounded | X | |
| Heating elements | Not securely installed | X | |
| | Terminals not accessible | X | |
| | Number of elements not as specified | X | |
| | Bottom of elements not enclosed as specified | X | |
| | Not insulated as specified (pad-type) | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-16T14:47Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects. (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Controls | Not specified number of switches or thermostats | X | |
| | Thermostat dials not graduated | X | |
| | Thermostat dials not recessed or protector bar missing | X | |
| Griddle surface | Not one piece | X | |
| | Porous, pitted, cracked, or distorted | X | |
| Grease trough | Drain not provided | X | |
| Grease receptacle | Not removable from the front | X | |
| | Number of baffles not as specified | X | |
| | Not provided with a positive latch (for Naval shipboard installations only) | X | |
| Griddle stand | Not open construction | X | |
| | Not provided with casters (when applicable) | X | |
| | Not provided with means to secure griddle to stand | X | |
| Style 2 casters | Not type specified | X | |
| | Two swivel type not provided with brakes | X | |
| Welding (when applicable) | Not free of oxide, scale, paint, or grease | X | |
| | Not continuous, sound, smooth, or free from porosity, cracks, incomplete fusion, or deformation of material | X | |
| | Flux (when used) not removed | | X |
| Thread fasteners and rivets | Missing, broken, stripped, or fractured | X | |
| | Loose | | X |
| | Rivets not fully peened or upset | | X |
| | Rivets head(s) not in full contact with riveted members | | X |
| Marking for identification | Missing, incomplete, not legible, plate not of the specified material | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

* 4.2.4 End item dimensional examination. The end item shall be examined for conformance to dimensions specified in table I and 3.5. Any dimension not as specified shall be classified as a defect. The lot size shall be expressed in units of end items. The sample unit shall be one end item. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

* 4.2.5 End item testing.

* 4.2.5.1 Representative item testing. One representative end item of the specified type, size, class, and style selected from the lot shall be tested as specified in 4.4.1, 4.4.2, and 4.4.6 (when applicable). Any test failure shall be cause for rejection of the lot.

* 4.2.5.2 Performance testing. The end items shall be tested as specified in 4.4.3, 4.4.4, and 4.4.5. Any test failure shall be recorded as a defect. The lot size shall be expressed in units of end items. The sample unit shall be one end item. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.2.6 Packaging inspection. The inspection shall be in accordance with the quality assurance provisions of MIL-R-11337.

4.3 Certificate compliance examination. Certifications, certified test reports or listing marks for standards submitted in accordance with 3.2 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the griddles and stands he proposes to furnish meet the applicable requirements of UL and NSF as follows:

4.3.1 UL. Acceptable evidence of meeting the applicable requirements of UL Standard No. 197 shall be a UL listing mark or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the griddles have been tested and conform to the applicable requirements of UL Standard No. 197.

4.3.2 NSF. Acceptable evidence of meeting the requirements of NSF Standard No. 4 for griddles, and NSF Standard No. 2 for stands shall be one of the following:

a. A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished griddles and stands, or

b. A certification for the griddles and stands issued by NSF under their special one-time contract evaluation/certification service, or

c. A certified test report, acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

indicating that the griddles and stands have been tested and conform to the respective NSF standards.

4.4 Methods of inspection.

4.4.1 Temperature time limit test. The griddle shall be operated in an ambient temperature of 75°F plus or minus 5°F using electrical characteristics specified in the contract or purchase order. Surface temperatures shall be obtained by use of a recording type temperature indicating device. An observation shall be made to determine that the electrical circuit through the heating elements is interrupted within 12 minutes for all griddles to determine compliance with the time and temperature requirements of 3.4.2. Inability of the griddle to meet the requirements of 3.4.2 shall constitute failure of this test.

4.4.2 Grease receptacle capacity test. The grease receptacle shall be filled to capacity with water. The water in the grease receptacle shall then be poured into a graduated container of known capacity to determine compliance with the capacity requirement of 3.5.3. Inability of the grease receptacle to meet the capacity requirements of 3.5.3 shall constitute failure of this test.

4.4.3 Griddle body test. The cooking surface of the griddle shall be uniformly loaded with 75 pounds per square foot for 15 minutes and the griddle body (and legs if applicable) examined to determine compliance with the strength requirement of 3.5.1. Inability of the griddle to meet the strength requirements of 3.5.1 shall constitute failure of this test.

4.4.4 Static and dynamic tests for type II griddles. The type II griddle with a uniformly distributed load of 200 pounds on griddle surface shall be placed on the stand and the stand shall be examined for compliance with the dislodgement, breakage, and permanent damage requirements of 3.6. The 200-pound load, and casters of style 2 models, shall then be removed and the stand with griddle shall be dragged by the lower end of each leg in turn across a level concrete floor for 3 feet. The stand shall then be examined for compliance with the requirements of 3.6. Inability of the griddle stand to meet the requirements of 3.6 shall constitute failure of this test.

* 4.4.5 Thermostat test. The griddle shall be connected to the specified power source. The thermostat shall be set at 300°F and the griddle allowed to operate until the signal light has cycled "on" and "off" through at least three cycles at this setting. The griddle surface shall then have five temperature readings taken per heating section. The readings shall be taken 4 inches in from each corner and at the center of the heating section (i.e., at the intersection of the diagonals from corner to corner of each heating section.) The heating section surface temperature shall be measured at each of the five points by taking the average of the high and low temperatures during a complete cycle at each of those points. This procedure shall be repeated at 325°F and 350°F. Any failure to meet thermostat or signal light requirements of 3.5.5 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

4.4.6 Incline test (shipboard installation). The grease receptacle shall be 3/4 filled with liquid and hamburger patties shall be placed at the center of the cooking surface. The griddle shall be energized and inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other. Determination shall be made that the griddle operates as intended without spillage of liquid or product as required in 3.4.3. Failure to meet the requirement in 3.4.3 shall constitute failure of the test.

4.4.7 Liquid penetrant weld test. The splash guard welds shall be tested between the griddle edge and the splash guard in accordance with ASTM E 165 for compliance with grease tight seal requirements of 3.5.4. Evidence of any weld crack shall constitute failure of this test.

5. PACKAGING

5.1 Preservation, packing and marking. Preservation, packing and marking for levels A, B, or Commercial shall be in accordance with MIL-R-11337 (see 6.2).

6. NOTES

6.1 Intended use. Self-heating electric griddles are intended for use in kitchens and shipboard galleys for griddling various foods.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type, size, class and style required (see 1.2 and 3.4).
c. When griddles are required for shipboard installation (see 3.4.3).
d. Selection of applicable levels of preservation and packing (see 5.1).

6.3 Recycled materials. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.4 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - CE, MD
Navy - MC, SA
Air Force - 84
DLA - GS

Preparing activity:

Army - GL

Project No. 7310-0692



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:47Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-G-2338L | Griddles, Self-Heating, Electric; and Stands, Griddles |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

NATICK OP 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.