INCH-POUND
MIL-G-2338L
INT. AMENDMENT 2(SH)
28 October 1992
USED IN LIEU OF
AMENDMENT 1
19 April 1988

MILITARY SPECIFICATION

GRIDDLES, SELF-HEATING, ELECTRIC; AND STANDS, GRIDDLE

This interim amendment is approved for use within the Naval Sea Systems Command, Department of the Navy, with MIL-G-2338L, dated 24 October 1985.

PAGE 2

2.1, under "Standards/Military": add the following:

"MIL-STD-167/1 - Mechanical Vibrations of Shipboard Equipment Type I - Environmental and Type II - Internally Excited.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities."

PAGE 5

Add the following paragraphs:

"3.4.4 Shipboard vibration. When specified for shipboard use (see 6.2), griddles shall be capable of withstanding ships vibration. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested as specified in 4.4.8.

3.4.5 Electromagnetic compatibility. When specified for shipboard use (see 6.2), the units shall be designed and equipped for electromagnetic compatibility in accordance with the requirements of MIL-STD-461, class A4 for surface ships and class A5 for submarines. The equipment shall meet the emission and susceptibility requirements for CE01, CE03 and RE02 (see 4.4.9).

AMSC N/A FSC 7310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:47Z
Check the source to verify that this is the current version before use.

3.4.6 Human factors criteria. When shipboard use is specified (see 6.2), human factors engineering criteria, principles and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the griddles. The equipment shall be designed such that all maintenance and operation shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in sections 5.6 and 5.9 of MIL-STD-1472. All controls, switches and gages shall be selected and integrated into the design of the griddles so as to meet the applicable requirements of section 5.2 and 5.4 of MIL-STD-1472 and they shall be clearly and appropriately labeled to identify function. The clearance or free area required around an item shall permit an individual with applicable 5th to 95th percentile body dimensions and physical capabilities, as defined in MIL-STD-1472, to safely operate, maintain, remove or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for any tools, test equipment and replacement parts needed. When inspecting for defects and performing tests (see section 4), the equipment shall adhere to the human factors engineering considerations listed herein.

* 3.4.7 High voltage labels. When specified for shipboard use (see 6.2), a Danger High Voltage label shall be affixed to the equipments outer case assembly, on or adjacent to each service access cover and adjacent to one of the fasteners which secures the cover. A high voltage warning label shall also be placed near the high voltage components inside the equipment. The label shall include but is not limited to the following warnings:

a. A warning of high voltage.
b. Power supply must be disconnected before using.
c. Access covers must be in place during use.
d. Servicing should be done by authorized individuals."

PAGE 6

3.5.2, after the last sentence add the following sentence:

"When specified for shipboard use (see 6.2), griddles shall have grease chutes that lead only from the front grease trough to the spillage drawer so grease and debris collect in the front of the drawers first."

3.5.5, line 3, after "shall have a": add "white".

3.5.5, line 5, after "(see 4.4.5)": add the following sentence:

"A white indicator light shall be located on the front of the griddle and glow when the griddle is energized."

3.5.5, line 9 after "knobs.": add the following sentence:

"When specified for shipboard use (see 6.2), the temperature controls shall be arranged horizontally, each corresponding to their respective griddle sections, orientated from left to right."

Source: https://assist.dla.mil -- Downloaded: 202640-16T14:47Z
Check the source to verify that this is the current version before use.

PAGE 8

3.9.4, add the following sentence at the end of the paragraph:

"When specified for shipboard use (see 6.2), suitable shields or baffles shall be installed to prevent wiring from hanging into any areas where personnel or removable parts, such as grease drawers, can contact them."

PAGE 10

Table II, add the following:

Examine	Defect	Classification Major	Minor
Electrical	Baffles or protective shielding of wires not provided	X	
Grease trough	Grease chutes from front of grease trough not provided (for Naval shipboard installation)"	X	

PAGE 11

4.2.5.1, line 3, after "4.4.6": add ",4.4.8 and 4.4.9".

PAGE 13

Add the following paragraphs:

"4.4.8 Shipboard vibration test. When required for shipboard use, the griddle under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, Type I equipment. The griddle shall be secured to the test machine in the same manner that it will be secured on shipboard (see 3.9.3). Failure of the griddle to perform its function during and after testing, or meeting requirements of 3.4.4 shall constitute failure of this test.

4.4.9 Electromagnetic interference test. When required for shipboard use, the unit shall be tested by the contractor in accordance with test methods CE01, CE03 and RE02 of MIL-STD-462. The contractor shall furnish written certification (see 6.2.1), that the equipment meets the MIL-STD-461 requirements. Nonconformance with the requirements specified shall constitute failure of the test."

6.2c, after "3.4.3": add "3.4.4, 3.4.5, 3.4.6 and 3.4.7."

Source: https://assist.dla.mil -- Downloaded: 202640-16T14:47Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

* "6.2.1 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs:

Paragraph No.	Data requirement title	Applicable DID No.	Option
4.4.9	Certification/Data Report	DI-MISC-80678"	

Add the following paragraph:

* "NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Preparing activity:
Navy - SH
(Project 7310-N816)

Source: https://assist.dla.mil -- Downloaded: 202640-16T14:47Z
Check the source to verify that this is the current version before use.