INCH-POUND

MIL-S-2329C
INTERIM AMENDMENT 1 (GL)
3 August 1990

MILITARY SPECIFICATION

SHEATH, MACHETE (FOR 18 INCH LONG, 2-1/4 INCH WIDE BLADE)

This interim amendment is approved for use within the Department of the Army with MIL-S-2329C, dated 3 December 1975.

PAGE 1

2.1, Under "SPECIFICATIONS FEDERAL": Delete "QQ-Z-325" and its title.

Add the following:

"T-T-E-529 - Enamel, Alkyd, Semigloss, Low VOC Content"

2.1, Under "SPECIFICATIONS MILITARY": Delete "MIL-E-480" and its title.

2.1, Add the following:

"MIL-L-35078 - Loads, Unit: Preparation of Semiperishable subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for."

PAGE 2

2.1, Under "STANDARDS MILITARY", Add:

"MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

2.2, Delete entirely and substitute:

"2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:44Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 412 - Rubber Properties in Tension
D 638 - Tensile Properties of Plastics
D 747 - Stiffness of Plastics by Means of a Cantilever Beam
D 1505 - Density of Plastics by the Density-Gradient Technique
D 1525 - Vicat Softening Temperature of Plastics
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 9

4.4.2.3, Delete entirely and substitute:

"4.4.2.3 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Contents	Number per container is more or less than required

4.4.2.4 Palletization examination. The fully packaged and palletized end items shall be examined for defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:44Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.4.2.4: Renumber to 4.4.2.5

Section 5, Delete entirely and substitute the following:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Ten sheaths with the sharpeners in the "up" position shall be alternately reversed end for end and stacked to form a bundle. The stacking shall be such that only the blade portion of each sheath is placed on top of another with the tip just short of the shoulder of the adjacent sheath. The bundle shall be securely tied with cotton tape or twine approximately 4 inches in from each end of the bundle. An instruction sheet shall be compactly folded and inserted into the mouth of each sheath (see 3.8).

5.2.1 Commercial preservation. Sheaths shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. Fifty sheaths, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of the box shall be approximately 22-1/2 inches in length, 17-1/2 inches in width and 8 inches in depth. Approximate dimensions are furnished as a guide only. Each box shall be closed, waterproofed and reinforced in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Fifty sheaths, preserved as specified in 5.1 shall be packed in a shipping container conforming to style RSC-L, type CF (variety SW)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:44Z
Check the source to verify that this is the current version before use.

or SF, class domestic, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 22-1/2 inches in length, 17-1/2 inches in width, and 8 inches in length. Approximate dimensions are furnished as a guide only. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method II of PPP-B-636.

5.2.3 Commercial packing. Sheaths, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), sheaths, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallets shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III or IV of MIL-STD-731. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 1 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable."

PAGE 12

6.2 Add:

"(e) Type and class of unit load required (see 5.2.1).

(f) When palletization is required (see 5.3)."

Custodians:

Army - GL
Navy - MC
Air Force - 82

Preparing activity:

Army - GL

(Project 8465-A073)

Review activities:

Army - ME
Air Force - 69

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:44Z
Check the source to verify that this is the current version before use.